



DESIGN

| | |
|-------------------------|--|
| Product Type: | Floating LVT |
| Overall Thickness: | 3.2 mm (.13") |
| Wear Layer: | 12 mil (0.3 mm) |
| Finish: | Enhanced Urethane |
| Size: | 150mm x 1235mm (actual) 6" x 48"L (nominal) |
| Square Feet Per Carton: | 31.9 sf/ctn |
| Pieces Per Carton: | 16 pieces/ctn |
| Pounds Per Carton: | 47.41 lbs/ctn |
| Installation Method: | Floating LVT with Uniclic Locking System |
| Recommended Adhesive: | None Required |
| Underlayment: | Mohawk ActiveSound |

SUSTAINABILITY

| | |
|----------------|-----------------------|
| Certification: | FloorScore® certified |
|----------------|-----------------------|

PERFORMANCE

| | |
|--------------------------|---|
| Construction: | Light Commercial Grade Luxury Vinyl Tile |
| Classification: | ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed |
| Squareness: | ASTM F2055 - Passes - 0.010 in. max |
| Size And Tolerance: | ASTM F2055 - Passes - ±0.016 in. per linear foot |
| Thickness: | ASTM F386 - Passes - as specified ±0.005 in. (±0.13 mm) |
| Flexibility: | ASTM F137 - Passes - ≤ 1.0 in., no cracks or breaks |
| Dimensional Stability: | ASTM F2199 - Passes - 0.15% max (0.020 in. per linear foot) |
| Residual Indentation: | ASTM F1914 - Passes - Average less than 8% |
| Resistance To Chemicals: | ASTM F925 - Passes - No Change |
| Resistance To Light: | ASTM F1515 - Passes - ΔE ≤ 8 |
| Resistance To Heat: | ASTM F1514 - Passes - ΔE ≤ 8 |
| Critical Radiant Flux: | ASTM E648 - Passes - ≥ 0.45 watts/cm2, Class 1 |
| Smoke Density: | ASTM E662 - Passes - < 450 |

SERVICE

| | |
|-------------|---|
| Warranties: | Limited 10 Year Light Commercial Warranty |
|-------------|---|



233
Gally Gold
Quickship Available



242
Honeytone
Quickship Available



258
Realist
Quickship Available



262
Pier
Quickship Available



717
Winter White
Quickship Available



822
Blondie
Quickship Available



857
Woodridge
Quickship Available



872
Bombay
Quickship Available



881
Armoire
Quickship Available



988
Key-Note
Quickship Available