


DESIGN

Product Type:	Glue Down LVT
Overall Thickness:	2.5 mm (.1")
Wear Layer:	20 mil (0.5 mm)
Finish:	M-Force
Size:	152.4mm x 1219.2mm (actual) 6"W x 48"L (nominal)
Square Feet Per Carton:	36 sf/ctn (3.34 m ² /ctn)
Pieces Per Carton:	60 cartons/pallet
Pounds Per Carton:	29.7 lbs/ctn
Installation Method:	Glue Down
Recommended Adhesive:	M95.0 Resilient Flooring Adhesive, M99 Resilient Flooring Adhesive, or M700 Adhesive
Underlayment:	Mohawk AccuSound™ (Optional)

SUSTAINABILITY

Certification:	FloorScore® certified
----------------	-----------------------

PERFORMANCE


Construction:	Commercial Grade Luxury Vinyl Tile
Classification:	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
Squareness:	ASTM F2055 - Passes - 0.010 in. max
Size And Tolerance:	ASTM F2055 - Passes - ±0.016 in. per linear foot
Thickness:	ASTM F386 - Passes - As Specified ±0.005 in.
Flexibility:	ASTM F137 - Passes - ≤ 1.0 in., no cracks or breaks
Dimensional Stability:	ASTM F2199 - Passes - ≤ 0.020 in. per linear foot
Static Load:	ASTM F970 - Passes, modified - 1000 psi
Residual Indentation:	ASTM F1914 - Passes - Average less than 8%
Resistance To Chemicals:	ASTM F925 - Passes - No Change
Resistance To Light:	ASTM F1515 - Passes - ΔE ≤ 8
Resistance To Heat:	ASTM F1514 - Passes - ΔE ≤ 8
Critical Radiant Flux:	ASTM E648 - Passes - ≥ 0.45 watts/cm ² , Class 1
Smoke Density:	ASTM E662 Part A - Passes - < 450


SERVICE

Warranties:	Limited 15 Year M-Force Commercial Warranty
-------------	---------------------------------------------


W123
Western Woods

W141
Gold


W142
Sable

W332
Cedar

W342
Down Town

W358
Brick

W363
Regal Red

W372
Suede

W812
Tan Tone



W829
Sandy



W838
Beagle



W851
Too Tan



W918
Silver



W938
Pigeon



W949
Gorgeous Gray



W958
Two Tone



W966
Shadow



W989
Lead