Ⅲ Mohawk Group

Trenta Collection



|--|

Product Type: Glue Down LVT Overall Thickness: 3 mm (.12") 30 mil (0.7 mm) Wear Layer: Finish: M-Force Ultra Size: 7.25"W x 48"L 38.7 sf/ctn Square Feet Per Carton: Pieces Per Carton: 16 pieces/ctn Pounds Per Carton: 43.40 lbs/ctn Installation Method: Glue Down

M95.0 Resilient Floor Adhesive, MS160 Spray Adhesive or M700 Pressure Sensitive Adhesive Recommended Adhesive:

SUSTAINABILITY

FloorScore® certified Certification:

PERFORMANCE

Heavy Commercial Grade Luxury Vinyl Tile Construction: Classification: ASTM F1700 - Class III, Type A - Smooth, Type B -

Squareness: ASTM F2421 - Passes - 0.010 in. max

Size And Tolerance: ASTM F2421 - Passes - ±0.016 in. per linear foot

Thickness: ASTM F386 - Passes - Nominal ±0.005 in.

Flexibility: ASTM F137 - Passes - 1.0 inch mandrel, no cracks or

Dimensional Stability: ASTM F2199 - Passes - \leq 0.020 in. per linear foot

ASTM F970 - Passes - <= 0.005, modified at 2500 Static Load:

Residual Indentation: ASTM F1914 - Passes - Residual $\leq 8\%$

ASTM D2047 - Passes - > 0.6 Dry Slip Resistant: Resistance To Chemicals: ASTM F925 - Passes - No Change

ASTM F1515 - Passes - ∆E ≤ 8 Resistance To Light: Resistance To Heat: ASTM F1514 - Passes - $\Delta E \le 8$

Critical Radiant Flux: ASTM E648 - Passes - ≥ 0.45 watts/cm2, Class 1

Smoke Density: ASTM E662 - Passes - ≤ 450

Impact Insulation Class: ASTM E989 / E492 - 59 IIC

SERVICE

Warranties: Limited 20 Year M-Force Ultra Commercial





Pismo Beach



882

Havana

172

Dune

858 Mink



898 Chestnut



Starlet



Copenhagen

378

Gingersnap

939 Pewter



Trenta Collection

