



DESIGN

Product Type:	Tile
Construction:	Tufted
Minimum Sq Yd:	No Minimum
Surface Texture:	Level Patterned Loop
Gauge:	1/12 (49.00 rows per 10 cm)
Tufted Pile Weight:	14.0 oz. per sq. yd. (474 g/m ²)
Finished Pile Thickness:	.100" (2.54 mm)
Total Thickness:	.242" (6.13 mm)
Stitches Per Inch:	9.3 (36.61 per 10 cm)
Dye Method:	Solution Dyed
Fiber Type:	Colorstrand® SD Nylon
Stain Release Technology:	EcoSentry Plus Stain Protection
Soil Release Technology:	EcoSentry Soil Protection
Density:	5,040
Weight Density:	70,560
Backing Material:	EcoFlex Matrix
Alternate Backing:	EcoFlex AIR - Minimum SY Required
Installation Method:	Monolithic, Quarter Turn, Vertical Ashlar, Brick Ashlar, Multi Directional
Size:	24" x 24" (.6096 m x .6096 m)
Pattern Repeat:	Not Applicable

SUSTAINABILITY

Pre-Consumer Recycled Content:	48%
NSF 140:	EcoFlex Matrix - NSF 140 Gold
Indoor Air Quality:	CRI Green Label Plus GLP1171
Declare Label:	Declared Red List Free

PERFORMANCE

Flammability:	ASTM E 648 Class 1 (Glue Down)
Smoke Density:	ASTM E 662 Less than 450
Static Propensity:	AATCC-134 Under 3.5 KV
Foot Traffic Recommendation TARR:	Heavy
GSA Stain Release Rating:	Pass

SERVICE

Warranties:	Lifetime Limited Carpet Tile Warranty, Lifetime Limited Colorfastness to Light, 10 Year Limited Colorfastness to Atmospheric Contaminants, 10 Year Limited Stain Warranty, Lifetime Static
-------------	--



7238
Pumice
Quickship Available



7358
Breccia



7559
Opal
Quickship Available



7568
Marble
Quickship Available



7656
Gabbro



7688
Ore



7728
Chert
Quickship Available



7858
Feldspar



7879
Basalt

Bending Earth Collection

Mohawk Group



7927
Shale



7948
Granite
Quickship Available