Porcelain Stone®

Available Colors



JAZ01 ▶ Louis



JAZ02 ▶ Duke



JAZ03 ▶ Count



JAZ04 ▶ Billie

Features and Benefits

- Jazz Age into Crossville's softest wood-look porcelain The look of aged hardwood with authentic, timeworn patina
- Authentic, aged hardwood patina 8x48 rectified planks with a minimum 3mm grout joint
- Coordinating trim and mosaic for fully-finished style
- Herringbone and 2x2 mosaics with matching bullnose and cove base trim to finish the look
- · Globally sourced



Porcelain Stone®

Herringbone Mosaic







JAZ02.1BONEMOS ▶ Duke



JAZ03.1BONEMOS ▶ Count



JAZ04.1BONEMOS ▶ Bille

2 x2 Mosiacs



JAZ01.10202MOS ▶ Louis



JAZ02.10202MOS ▶ Duke



JAZ03.10202MOS ▶ Count



JAZ04.10202MOS ▶ Billie





Porcelain Stone®

Sizes (Shown in JAZ02 Duke)



Get Planked!

Our Porcelain Stone® products are available in popular plank shapes with no minimum order and quick fulfillment.

See website for more details and sizes.



Sizes & Finishes

Field Tile - RectifiedAvailable in all colorsNominal (in)Actual (mm)Thickness (mm)Finish8 x 48197 x 119610UP

Crossville recommends a grout joint of 3mm.

Actual measurements stated in inches indicate tile is calibrated (non-rectified).

Actual measurements stated in mm indicate tile is rectified.

4	Mosaics		Available in all colors	
	Nominal (in)	Actual Size (mm)	Thickness (mm)	Finish
	2 x 2*	299 x 299	10	UP
	Herringbone**	295 x 341	10	UP

^{*}Mounted on 12 x 12 sheet with 4.3mm grout joints

Coordinating Trim

Nominal (in)	Actual (mm)	Thickness (mm)	Finish
6 x 12 Cove Base	147 x 297	10	UPS†
4 x 24 Single Bullnose	97 x 597	10	UP

† Manufactured in the USA



4 x 24 Bullnose

6 x 12 Cove Base

Product Performance

Breaking Strength	>500 lbf	ASTM C648
Bond Strength	>200 psi	ASTM C482
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.20%	ASTM C373

Wet Dynamic Coefficient of Friction Range

UP 0.42 - 0.52 AcuTestsm

Shade & Texture Index

Jazz Age has a shade variation of V2.



This porcelain tile product is produced with a V2 variation. Expect that the amount of color and texture on each piece may vary slightly. Inspect the product upon delivery and for best results, blend tile from several cartons during installation.



^{**}Mounted on 12 x 15 sheet with 2.5mm grout joints

Crossville, Inc.

PO Box 1168 Crossville, TN 38557

Phone 931.484.2110 931.456.2956 Fax

E-Mail Crossc@CrossvilleInc.com

Web CrossvilleInc.com

Recommended Use

Jazz Age is recommended for interior floors, walls, countertops, and exterior walls in both residential and commercial applications. Jazz Age is not recommended for exterior horizontal surfaces or exterior paving. If offset pattern is required for tiles 15 inches or longer, Crossville® recommends an offset of not greater than 33%. See CrossvilleInc. com for detailed installation instructions.

Wet Area Use for Jazz Age Mosaics

Jazz Age 2 x 2 and herringbone mosaics are made in an unpolished finish and the AcuTestsm wet Dynamic COF is ≥ 0.42. Their small sizes ensure frequent grout joints which provides traction and drainage. Crossville cannot control situations involving incorrect installation, improper slope to the drain for elimination of standing water and poor surface cleaning.

This information is provided so that customers may make a realistic and informed decision when comparing Jazz Age to other tile products in wet area environments, such as residential/commercial bathrooms, showers, and interior pool decks.

Information listed here is subject to change. Please refer to CrossvilleInc. com for the latest, most accurate information.

CrossvilleInc.com

If you want a better idea of what Crossville tile would look like in a particular room setting, simply visit our website and click on Cross-Vision. This powerful software tool allows you to visualize different types of Crossville tile. In addition, you'll find comprehensive information about Crossville's entire portfolio of products. You can also learn about the latest styles and trends from industry experts, download detailed care and maintenance instructions for our various products, or browse electronic versions of Crossville's product brochures. So whether you need information about Crossville products or tile in general, please visit us at CrossvilleInc.com. Information listed here is subject to change.


Our Warranty

Crossville Inc. guarantees that its products will meet or exceed the performance specifications outlined in ANSI A137.1- 2012 and in the performance data section of the Crossville, Inc. general product catalog. For complete details check our website at CrossvilleInc.com.

Hydrotect

Our porcelain tiles are available with Hydrotect. Crossville's revolutionary invisible coating harnesses the power of light, water, and oxygen to create the best defence against dirt and pollution. Whether indoors or out, floors and walls stay cleaner, providing a superior experience in any space. Please request a sample before ordering. For complete details check our website at CrossvilleInc.com.

₩ HYDROTECT



For over 20 years we have been offering Porcelain tile to commercial customers at National Accounts pricing programs with special discounts. The National Accounts department provides materials forecasting, sales support and samples.

Exterior Cladding

Crossville's Porcelain Stone® Exterior Cladding Systems are suitable for virtually any conventional masonry application. When used in conjunction with our exterior cladding systems, Crossville's Porcelain Stone offers clear advantages: decreased construction costs, less site disturbance, low-tozero maintenance after installation, accelerated construction schedules and greater strength than traditional masonry.

>>> Crossville® Sample Express

Complimentary Samples are available at CrossvilleInc.com/products/Jazz Age/

Samples may also be ordered through customer service by email or phone.

Sample Fulfillment & Help Line

Samples@CrossvilleInc.com 1800221.9093

Loose Tile Samples for Architects & Designers

Loose Tile Samples

Sizes may vary depending on product series Max. of 4 large field tile per order

Replacement Chips for PSS Rack Max. of 5, 2 x 2 chips per color

Sandard Shipping UPS Ground











