

SOUND & FURY

Gesture / Intensity



PRICE

Milliken™



INSPIRED. INSPIRING.

I close my eyes, feel the weight of the paintbrush in my hand, and with the first touch of paint to canvas, lose myself in the music. Moments pass and suddenly I discover a finished painting in front of me. In its texture, I see the thick strokes of the bass line and the delicate, rhythmic marks of a piano solo. In its color, I see the brightness of a trumpet blare. In the painting, I see the song. In Sound and Fury, I see the same.



Intensity in Rhythm, ashlar tile installation, with Gesture in Percussion accents.



Get more at millikencarpetsamplestudio.com

Gesture and Intensity in Dynamic, ashlar tile installation.

Gesture

Get more at millikencarpetsamplestudio.com

Gesture in Stereo, quarter-turn installation.

Gesture in Stereo, monolithic tile installation.

Gesture in Stereo, ashlar tile installation.



Gesture

Gesture in Rhythm and Equalizer, ashlar tile installation.



Gesture in Equalizer, ashlar tile installation.



Get more at millikencarpetsamplestudio.com

Gesture in Fidelity, ashlar tile installation, with Intensity in Rhythm accents.

Intensity

Get more at millikencarpetsamplestudio.com

Intensity in Stereo, monolithic tile installation.

Intensity in Stereo, ashlar tile installation.

Intensity in Stereo, quarter-turn installation.

Intensity



Intensity in Decibel, ashlar tile installation.

Get more at millikencarpetsamplestudio.com



Intensity in Rhythm, ashlar tile installation.



Intensity in Dynamic, ashlar tile installation.

SOUND & FURY

Gesture / Intensity

Have you seen our other collections? Visit us online today.



Art Media



Ghost Artist



Inis Mór



Lindstrom



Construction

Tufted, Textured Loop

Tile Size

50 cm x 50 cm (19.7" x 19.7")

50 cm x 1 m (19.7" x 39.4")

Yarn Type

Econyl® Solution-Dyed Nylon
Type 6

Stain Resist / Soil Release

StainSmart®

Tufted Face Weight

17 oz/yd² (576.4 g/m²)

Pile Height

Gesture: 0.07" (1.8 mm)

Intensity: 0.06" (1.5 mm)

Average Density

Gesture: 8,163

Intensity: 9,545

Standard Backing

PVC-Free WellBAC™ Comfort
Cushion

Available with TractionBack®

Texture Appearance Retention Rating (TARR)

Gesture: Heavy

Intensity: Severe

Recommended Installation Methods



monolithic



quarter-turn



ashlar



ALL PLANK
METHODS



This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice.

Growing greener for over 100 years.

This product has a UL® Environment 3rd party verified Environmental Product Declaration (EPD). A copy of the EPD is available online at millikencarpet.com/epd and productguide.ulenvironment.com.

Customer Concierge 800.824.2246 | millikencarpet.com
© 2011 Milliken & Company | Made in the USA

Cover image: Abstract hand painted art for background,
by Janaka Dharmasena. © 2011 Shutterstock

2710016371
0720