

OBEX™ TILE: CUTX

Entrance Flooring

MODULAR TILE

Construction

Tufted, Cut Pile

Tile Size

19.7" x 19.7" (50 cm x 50 cm)

Textile Yarn Type

Milliken-Certified WearOn® Nylon and Monofilament

Dye Method

PrintWorks™ Precision Dye

Gauge

5/32

Stitches Per Inch

9.5

Tufts

60.8/in² (942/100 cm²)

Finished Pile Height

0.186" (4.72 mm)

Average Density

4,684

Nominal Total Thickness

0.50" (12.7 mm)

Nominal Total Weight

125 oz/yd² (4,238 g/m²)

Standard Backing

PVC-Free WellBAC®
Comfort Plus Cushion
(Available with TractionBack®)

Recycled Content by Total Weight

37.5% Pre-Consumer,
0.0% Post-Consumer

Radiant Panel (ASTM-E-648-10)

Class I

Smoke Density (NPA-258 or ASTM-E-662-06)

≤ 450

Methenamine Pill Test (CPSC FF-1-70) or ASTM D 2859-96

Self-Extinguishing

Lightfastness (AATCC 16E)

≥ 4.0 at 80 Hours

Crocking (AATCC 165)

≥ 4.0 Wet or Dry

Static Electricity (AATCC-134) 20% R.H., 70°F

≤ 3.5 KV, Permanent Conductive Fiber

Recommended Maintenance

Hot Water Extraction or MilliCare®
Textile and Carpet Care Service Network

Indoor Air Quality - CRI Green Label Plus™

GLP.793, Carpet Category 5Y

Recommended Installation Method(s)

Monolithic, Quarter-Turn, Ashlar

Pieces Per Box

12 Tiles per box (32.292 ft²)

Installation Zone Application

Zone 2 or Zone 3

WARRANTIES

Lifetime Face Fiber Wear

Lifetime Antistatic

Lifetime Floor Compatibility

Lifetime Color Pattern Permanency

Lifetime Floor Release

Lifetime Cushion Resiliency

Lifetime Moisture Resistance

Lifetime Delamination of Backing

Lifetime Dimensional Stability

Lifetime Tuft Bind

Lifetime Edge Ravel

Flammability



This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.