

OBEX™ TILE: LOOP

Entrance Flooring

MODULAR TILE

Construction

Tufted, Multi-Level Loop

Tile Size

19.7" x 19.7" (50 cm x 50 cm)

Textile Yarn Type

ECONYL® Solution-Dyed Nylon
and Solution-Dyed Nylon
Monofilament

Dye Method

Solution Dyed

Gauge

1/12

Stitches Per Inch

11.3

Tufts

135.6/in² (2,100/100 cm²)

Nominal Pile Height

0.255" (6.48 mm)

Average Density

5,739

Nominal Total Thickness

0.391" (9.9 mm)

Nominal Total Weight

104.2 oz/yd² (3,540 g/m²)

Standard Backing

PVC-Free WellBAC® Comfort Cushion
(Available with TractionBack®)

Recycled Content by Total Weight

33.3% PreConsumer,
6.6% Post-Consumer

Radiant Panel (ASTM-E-648-15e1)

Class I

Smoke Density (NPA-258 or ASTM E 662-15a)

≤ 450

Methenamine Pill Test (CPSC FF-1-70) or ASTM D 2859)

Self-Extinguishing

Lightfastness (AATCC 16.3)

≥ 4.0 at 80 Hours

Crocking (AATCC 165)

≥ 4.0 Wet or Dry

Static Electricity (AATCC-134) 20% R.H., 70°F

≤ 3.5 KV, Permanent Conductive Fiber

Recommended Maintenance

Hot Water Extraction or MilliCare®
Textile and Carpet Care Service Network

Indoor Air Quality - CRI Green Label Plus™

GLP.793, Carpet Category 5Y

Recommended Installation Method(s)

Monolithic, Quarter-Turn, Ashlar

Pieces Per Box

12 Tiles per box (32.292 ft²)

Installation Zone Application

Zone 3

WARRANTIES

Lifetime Face Fiber Wear
Lifetime Antistatic
Lifetime Floor Compatibility
Lifetime Color Pattern Permanency
Lifetime Floor ReleaseLifetime Cushion Resiliency
Lifetime Moisture Resistance
Lifetime Delamination of Backing
Lifetime Dimensional Stability
Lifetime Tuft BindLifetime Edge Ravel
Flammability

This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.