

OBEX™ IDENTITY TILE: CUT

SPECIFICATION SHEET DATE: 10 MARCH 2020

MODULAR TILE

Construction

Tufted, Cut Pile

Tile Size

1M X 1M

1M X 2M

1M X 3M

Textile Yarn Type

Milliken-Certified WearOn® Nylon and Monofilament Type 6 and 6, 6

Dye Method

Print

Tufted Face Weight

28 oz/yd² (949 g/m²)

Gauge

5/32

Stitches Per Inch

5.6

Tufts

35.8 /in² (554/100 cm²)

Finished Pile Height

0.182 in (4.62 mm)

Nominal Total Thickness

0.50 in (12.7 mm)

Nominal Total Weight

130 oz/yd² (4,408 g/m²)

Standard Backing

PVC-Free WellBAC™

Comfort Plus Cushion

(Available with TractionBack™)

Recycled Content by Total Weight

36.2% Pre-Consumer

0.0% Post-Consumer

Flammability (Radiant Panel ASTM-E-648-10)

Class I

Smoke Density (NFPA-258 or ASTM-E-662-06)

≤ 450

Methenamine Pill Test (CPSC FF 1-70 or ASTM D 2859-96)

Self-Extinguishing

Lightfastness (AATCC 16E)

≥ 4.0 at 80 Hours

Crocking (AATCC 165)

≥ 4.0 at 80 Hours

Static Electricity (AATCC-134) 20% R.H., 70°F

≤ 3.5 KV, Permanent Conductive Fiber

Recommended Maintenance

Daily Vacuum and Deep Clean with Hot Water Extraction or milliCare® Textile and Carpet Care

Indoor Air Quality – CRI Green Label Plus™

GLP7205, Carpet Category 5Y

Warranties

Lifetime Face Fiber Wear

Lifetime Antistatic

Lifetime Floor Compatibility

Lifetime Color Pattern Permanency

Lifetime Floor Release

Lifetime Cushion Resiliency

Lifetime Moisture Resistance

Lifetime Delamination of Backing

Lifetime Staining/Soiling (StainSmart®)

Lifetime Dimensional Stability

Lifetime Tufted Bind

Lifetime Edge Ravel

Flammability



This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.