

# OBEX™ TILE: CUTX

SPECIFICATION SHEET DATE: 10 MARCH 2020

## MODULAR TILE

### Construction

Tufted, Cut Pile

### Tile Size

1M X 1M

1M X 2M

1M X 3M

### Textile Yarn Type

Milliken-Certified WearOn® Nylon and Monofilament Type 6 and 6, 6

### Dye Method

Print

### Tufted Face Weight

24 oz/yd² (949 g/m²)

### Gauge

5/32

### Stitches Per Inch

9.5

### Tufts

60.8 / in² (942/100 cm²)

### Finished Pile Height

0.186 in (4.72 mm)

### Nominal Total Thickness

0.50 in (12.7 mm)

### Nominal Total Weight

125 oz/yd² (4,238 g/m²)

### Standard Backing

PVC-Free WellBAC™  
Comfort Plus Cushion  
(Available with TractionBack™)

### Recycled Content by Total Weight

37.5% Pre-Consumer  
0.0% Post-Consumer

### Flammability (Radiant Panel ASTM-E-648-10)

Class I

### Smoke Density (NFPA-258 or ASTM-E-662-06)

≤ 450

### Methenamine Pill Test (CPSC FF 1-70 or ASTM D 2859-96)

Self-Extinguishing

### Lightfastness (AATCC 16E)

≥ 4.0 at 80 Hours

### Crocking (AATCC 165)

≥ 4.0 at 80 Hours

### Static Electricity (AATCC-134) 20% R.H., 70°F

≤ 3.5 KV, Permanent Conductive Fiber

### Recommended Maintenance

Daily Vacuum and Deep Clean with Hot Water Extraction or milliCare® Textile and Carpet Care

### Indoor Air Quality – CRI Green Label Plus™

GLP0793, Carpet Category 5Y

## Warranties

Lifetime Face Fiber Wear

Lifetime Antistatic

Lifetime Floor Compatibility

Lifetime Color Pattern Permanency

Lifetime Floor Release

Lifetime Cushion Resiliency

Lifetime Moisture Resistance

Lifetime Delamination of Backing

Lifetime Staining/Soiling (StainSmart®)

Lifetime Dimensional Stability

Lifetime Tufted Bind

Lifetime Edge Ravel

Flammability

This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

