

construction notes

WORK CHAIRS

AMICUS TASK & GUEST	4
AROUND TASK AND STOOL	5
AT	6
ESSA CHAIR	7
MARINI	8
METRIC	9
NUOVA CONTESSA	10
PROJEK TASK & STOOL	11
SABRINA TASK & STOOL	12
SAVERA TASK & STOOL	13
SAVERA XL	14
T-3	15
TONE CHAIR	16
VARIABLE MULTI-USE WORK CHAIRS & STOOL	17
VISIO	18

MULTI-USE CHAIRS

ABILITY SPINNER STOOL	19
AROUND GUEST	20
JUST-US CHAIR	21
KUPP	22
OCCO	23
SITARA	24
SPROUT STOOLS	25
SYNAPSE	26
TAIGA	27
VARIABLE CONFERENCE	28
VARIABLE HYBRED CHAIR	29

CONTINUED ON THE FOLLOWING PAGE

teknion

construction notes

STACKING CHAIRS

NAMI	30
VARIABLE 4-LEG STACKING GUEST CHAIR & STOOL	31
VOLUME	32
ZONE GUEST	33

SOFT SEATING

AEGIS	34
BANQS	35
BELIZE	37
BONDS	38
COLLABORATIVE OTTOMAN.	39
DNA	40
FERRARRA	41
TUX	42
VASARI	43
VIGNETTE	44

tekunion

construction notes

amicus task use & guest

BASE:

- reinforced nylon scuff-resistant plastic
- 26" base

CASTERS/GLIDES:

- 60mm (2-1/3") hard (carpet casters) reinforced nylon
- optional soft casters for hard floors are polyurethane coated nylon
- twin-wheeled and hooded
- 2-1/8" hard plastic glides
- soft glides have soft insert pads

PNEUMATIC CYLINDER: (GAS LIFT)

- gas-assisted pneumatic cylinder

MECHANISMS:

Synchro-Tilt:

- constructed of cast aluminum and stamped steel

SEAT:

- constructed of polyethylene + nylon

BACK:

Inner Back:

- constructed of ABS

Outer Back:

- constructed of polypropylene

Lumbar System:

- reinforced nylon

J-BAR:

- 5/16" solid steel
- epoxy powder coated

ARMS:

T-Arms:

- self-skinned urethane arm pads
- reinforced nylon armrest structure

Guest Chair Arms:

- reinforced nylon armrest

GUEST (FRAME):

Base:

- twin-wheeled and hooded
- multi-surface glides are natural polyethylene

Four-leg:

- 14 gauge steel tube

Cantilever:

- 12 gauge steel tube

FOAM:

- molded, colored, polyurethane foam for seat
- HCFC and CFC free
- 0 global warming factor
- "bumpered" as covered sides to protect furniture
- exceeds ASTM D - 3574 -91
- dynamic fatigue test by constant force pounding: thickness loss = 5% (specification calls for not more than 25%)

	Seat:	Back:
Density:	4.15 lbs./ft. 3	4.54 lbs./ft. 3
IFD @ 25%:	42 lbs	8.86 lbs
IFD @ 65%:	125 lbs	40.3 lbs
Recovery Strength		
@ 25%:	157N	32N
Recovery Ratio:	84.9%*	81.4%
Tensile Strength:	35.3 lbs./sq. in.*	13.8lbs./sq. in.*
Resiliency:	54%	67%
Flammability:	CAL 117	CAL 117

* exceeds ASTM P - 3770 - 91

construction notes

around task and stool

BASE:

- Ebony glass-reinforced nylon or polished diecast aluminum
- 26" diameter 5-star base (Aluminum), 27.5" diameter 5-star base (Plastic)

CASTERS/GLIDES:

- 60mm (2-1/3") hard (carpet casters) are glass-reinforced nylon plastic
- optional soft casters for hard floors are glass-reinforced nylon plastic with polyurethane soft band
- twin-wheeled casters
- glass filled nylon glides
- soft glides for hard floors have soft felt pads

PNEUMATIC CYLINDER:

- gas-assisted pneumatic cylinder lift

MECHANISMS:

- weight Activated Synchro-Tilt with easy override dial to fine tune tilt tension in one-rotation. Mechanism & seat sub-assembly facilitates Quick-Snap Assembly (one-way fastening) with the back sub-assembly & arms; and can be performed by manufacturer or on-site without tools
- glass-reinforced nylon plastic & steel

FOOTRING (STOOL):

- all-aluminum construction
- height-adjustable

SEAT:

Optional Seat Slider (depth):

- glass-reinforced nylon plastic
- plastic levers on left of seat control adjust

Seat Structure:

- glass-reinforced nylon plastic seat pan structure
- polypropylene plastic integrated FlexAround Seat Pan offers an advanced degree of comfort, support and ventilation

BACK:

Structural back frame:

- glass-reinforced nylon plastic frame structure designed to create a light, sculptural form with an open volume or space. Fabric-wrapped from front to back for a soft, tactile edge experience at the sides, bottom and top edge surfaces.
- back frame facilitates Quick-Snap Assembly (one-way fastening) to the mechanism & seat sub-assembly; to be performed by manufacturer or on-site without tools

MESH BACK:

- cushioned Mesh, featuring a dual-textured weave with coordinating colors on front and back. The mesh is breathable and provides user back support
 - elastic piece-dyed to prevent nylon fade
 - composition: 100% Polyester
 - weight: Approx. 300 g/sq. m
 - flammability: CAL 117
 - fastness to Light: AATCC 16.3-2014 class 5
 - abrasion Resistance: ASTM D- 4157-13, 30,000 cycles
 - piling Resistance: ASTM D-3511/D, class 5
 - cleaning: fixed covers: vacuum cleaning
- optional lumbar element constructed of polypropylene plastic

UPHOLSTERED BACK:

- Hex Suspension System - Hex-back insert constructed of polypropylene plastic flexes with the body to provide comfort and support
- adjustable lumbar elements are integrated into the design; each side can be independently controlled for asymmetrical positioning. Controls constructed of glass-reinforced nylon plastic

ARMS:

- 2D (height & width) & 4D (height, width, depth & pivot) adjustable T-Arms facilitate Quick-Snap Assembly (one-way fastening) to the mechanism & seat sub-assembly; to be performed by manufacturer or on-site without tools
- thermoplastic Polyurethane (TPU) armpad covers with flexible polyurethane foam padding
- glass-reinforced nylon plastic

SEAT FOAM:

- molded, colored, polyurethane foam for seat
- HCFC and CFC free
- 0 Global warming factor
- "bumpered" as covered sides to protect furniture

	Seat:
Density:	3.2-3.6 lbs./ft ³
IFD @ 25%:	206 N
IFD @ 65%:	529 N
Recovery Strength @ 25%:	200 N
Recovery Ratio:	85.4%*
Tensile Strength:	35.3 lbs./sq. in.*
Resiliency:	61%
Flammability:	CAL 117

* exceeds ASTM P – 3770 – 91

UPHOLSTERED BACK FOAM:

- molded, colored, polyurethane foam for back
- HCFC and CFC free
- 0 Global warming factor
- "bumpered" as covered sides to protect furniture

	Seat:
Density:	3.2-3.6 lbs./ft ³
IFD @ 25%:	206 N
IFD @ 65%:	529 N
Recovery Strength @ 25%:	200 N
Recovery Ratio:	85.4%*
Tensile Strength:	35.3 lbs./sq. in.*
Resiliency:	61%
Flammability:	CAL 117

* exceeds ASTM P-3770-91

construction notes

AT

BASE:

- diecast aluminum base
- painted or polished finish
- diameter of 26.3"

CASTERS/GLIDES:

- 60 mm (2-1/3") hard (carpet casters) are glass-reinforced nylon plastic
- optional soft casters for hard floors are glass-reinforced nylon plastic with polyurethane soft band

PNEUMATIC CYLINDER:

- gas-assisted pneumatic cylinder

MECHANISMS:

Synchro-Tilt:

- diecast aluminum, steel & plastic
- powder coating

SEAT/BACK:

Seat/Back Structure:

- glass-reinforced nylon plastic
- plastic levers on left and right of seat control adjust
- self-centering suspension ensures users body maintains its centre of gravity and comes with automatic weight adjustment

Inner Seat/Back:

- Polypropylene inner shell

ARMS:

T-Arms:

- polyurethane pads
- glass-reinforced nylon plastic

FOAM:

- molded, colored, polyurethane foam for seat
- HCFC and CFC free
- 0 global warming factor

Density:	3..2-3..6 lbs./ft. 3
IFD @ 25%:	206 lbs
IFD @ 65%:	529 lbs
Recovery Strength @ 25%:	200N
Recovery Ratio:	85.4%*
Tensile Strength:	35.3 lbs./sq. in.*
Resiliency:	61%
Flammability:	CAL 117

* exceeds ASTM F 3770 – 91

essa chair

BASE:

- glass-reinforced nylon
- 26" diameter 5-star base

CASTERS/SLIDERS:

- 60mm (2-1/3") hard (carpet casters) are glass-reinforced nylon plastic
- optional soft casters for hard floors are glass-reinforced nylon plastic with polyurethane soft band
- twin-wheeled casters
- glass filled nylon glides
- soft glides for hard floors have soft felt pads

PNEUMATIC CYLINDER:

- gas-assisted pneumatic cylinder lift. Colour coordinated with mechanism

MECHANISM:

- Weight Activated Synchro-Tilt. Mechanism
- colour coordinated glass-reinforced nylon plastic, die cast aluminum, and steel construction
- soft touch levers for enhanced tactile feel

SEAT:

Seat Structure:

- glass-reinforced nylon plastic seat pan structure

BACK:

Structural back frame:

- glass-reinforced polypropylene plastic frame structure designed to create a light, sculptural form with deepened cavity allowing thicker foam comfort. Fabric-wrapped from front to back for a soft, tactile edge experience at the sides, bottom and top edge surfaces

Outer panel:

- glass-reinforced polypropylene
- also available as upholstered

ARMS:

Height Adjustable:

- thermoplastic Polyurethane (TPU) armpad covers with flexible polyurethane foam padding
- glass-reinforced nylon plastic

Fixed Arm:

- glass-reinforced nylon plastic

SEAT FOAM:

- molded, colored, polyurethane foam for seat
- HCFC and CFC free
- 0 Global warming factor
- "bumpered" as covered sides to protect furniture

Seat:

Density:	3..2-3..6 lbs./ft. 3
IFD @ 25%:	206 lbs
IFD @ 65%:	529 lbs
Recovery Strength @ 25%:	200N
Recovery Ratio:	85.4%*
Tensile Strength:	35.3 lbs./sq. in.*
Resiliency:	61%
Flammability:	CAL 117

* exceeds ASTM F 3770 – 91

construction notes

marini

BASE:

- diecast aluminum
 - diameter of 27"
-

CASTERS/GLIDES:

- 60mm (2-1/3") hard (carpet casters) are reinforced nylon
 - optional soft casters for hard floors are polyurethane coated nylon
 - twin-wheeled
 - 2-1/8" hard plastic glides
 - soft glides have soft felt pads
-

PNEUMATIC CYLINDER (GAS LIFT):

- gas-assisted pneumatic cylinder
-

MECHANISMS:

Synchro-Tilt:

- constructed of aluminum, steel and plastic
-

SEAT:

- constructed of reinforced nylon
-

BACK:

- constructed of polypropylene and reinforced nylon
 - polished aluminum diecast inset detail
-

J-BAR:

- diecast aluminum with polished finish
-

ARMS:

Width & Height-Adjustable T-Arms:

- diecast aluminum
 - various plastics
 - self-skinned urethane arm pads
-

FOAM:

- molded, colored, polyurethane foam for seat and back
 - HCFC and CFC free
 - 0 Global warming factor
 - "bumpered" as covered sides to protect furniture
-

STANDARD SHIPPING CARTONS:

- recycled foam used to protect knocked-down chair in box
 - double wall cardboard
 - recycled and recyclable
 - 3" reinforced gum tape (recycled)
-

BASE:

- reinforced nylon, scuff resistant plastic (ebony)
- diameter of 26"

CASTERS/GLIDES:

- 60mm (2-3/8") hard (carpet casters) are reinforced nylon
- optional soft casters for hard floors are polyurethane coated nylon
- twin-wheeled
- 2-1/8" hard plastic glides
- soft glides have soft felt pads

PNEUMATIC CYLINDER (GAS LIFT):

- gas-assisted pneumatic cylinder lift

MECHANISMS:

Synchro-Tilt:

- stamped steel construction
- epoxy powder coat paint

SEAT:

- plywood seat plate

BACK:

- plywood back panel

ARMS:

T-Arms:

- polyurethane pads
- glass-reinforced nylon plastic

FOAM:

- molded, colored, polyurethane foam for seat and back
- HCFC and CFC free
- 0 global warming factor

Density:	3.2-3.6 lbs./ft ³
IFD @ 25%:	206 N
IFD @ 65%:	529 N
Recovery Strength @ 25%:	200 N
Recovery Ratio:	85.4%*
Tensile Strength:	35.3 lbs./sq. in.*
Resiliency:	61%
Flammability:	CAL 117

* exceeds ASTM P-3770-91

nuova contessa

BASE:

- diecast aluminum base
- painted or polished finish
- diameter of 27"

CASTERS/GLIDES:

- polyamide 6 hard twin-wheeled casters
- diameter of 5.9"
- optional soft type urethane casters

PNEUMATIC CYLINDER: (GAS LIFT)

- gas-assisted pneumatic cylinder lift

MECHANISMS:

Synchro-Tilt:

- diecast aluminum body
- rubber torsion mechanism

SEAT:

Seat Slider (depth):

- reinforced plastic (polyamide)

Seat Structures:

- reinforced plastic (polyamide)
- aluminum diecast frame
- 2" forward/back adjust in six positions
- levers on left and right of seat control adjust

Seat Material (All Mesh model):

- 100% polyester mesh
- zehedral braided format for optimized feel & additional support specifically tailored for the seat
- elastic piece-dyed to prevent color fade

BACK:

Frame:

- diecast aluminum external frame with paint or anodized finish
- reinforced plastic (polyamide) structural back
- maximum two visibly exposed mechanical fasteners on entire chair, bezel-recessed on side to minimize aesthetic impact and maximize structural performance.

Inner Back:

- 100% polyester mesh
- zehedral braided format for optimized feel & support, specifically tailored for your back
- elastic piece-dyed to prevent color fade

Lumbar System:

- glass-reinforced nylon plastic
- black translucent polypropylene membrane responds uniquely to individual's back curve depth & force

ARMS:

4D T-Arms:

- Smart Operations controls for seat height & back tilt/tilt-lock are integrated into levers on arms for easy access above seat level
- polyurethane pads
- reinforced plastic (nylon) structure
- button-controlled arm height adjustment and intuitive self-adjustment for width, depth and pivot

FOAM (DUAL-UPHOLSTERED MODEL ONLY):

- molded, tri-durometer polyurethane foam seat pan construction maximizes varying needs for comfort & support throughout
- 0 global warming factor
- HCFC and CFC free
- 0 global warming factor
- "bumpered" as covered sides to protect furniture

Seat:

Density: 3.2-3.6 lbs./ft. 3

IFD @ 25%: 206 lbs

IFD @ 65%: 529 lbs

Recovery Strength

@ 25%: 200N

Recovery Ratio: 85.4%*

Tensile Strength: 35.3 lbs./sq. in.*

Resiliency: 61%

Flammability: CAL 117

* exceeds ASTM F 3770 – 91

HEADREST (OPTIONAL):

- height and depth adjustable
- polyurethane pad
- reinforced plastic (nylon) structure

construction notes

projek task & stool

BASE:

- diecast aluminum 26" base
- reinforced nylon, scuff resistant plastic (ebony), 27-1/2" base

CASTERS/GLIDES:

- 60mm (2-1/3") hard (carpet casters) are reinforced nylon
- optional soft casters for hard floors are polyurethane coated nylon
- twin-wheeled
- 2-1/8" hard plastic glides
- soft glides have soft felt pads

PNEUMATIC CYLINDER: (GAS LIFT)

- gas-assisted pneumatic cylinder

MECHANISMS:

Weight-Activated Synchro-Tilt and Swivel Stool:

- constructed of aluminum, steel, and plastic
- epoxy powder coat paint

FOOTRING (STOOL):

- constructed of aluminum, steel tube and plastic spacer
- height-adjustable

SEAT:

- constructed of reinforced polypropylene

BACK:

Structural Back Outer Frame:

- constructed of glass reinforced nylon

Inner Frame:

- constructed of glass reinforced polypropylene

Lumbar System:

- constructed of polypropylene

MESH:

- Trade Name: Shrinx by k+r
- Composition: 76% Polyester, 24% Polyamide
- Weight: Approx. 380 g/lm
- Flammability: D- DIN EN 1021:2006 (as per spec sheet)
- Fastness to Light: DIN EN ISO 105-B02: 2002 5 - 7
- Fastness to Rubbing: DIN EN ISO 105-X12: 2002 4 – 5 dry and wet
- Fastness to perspiration: DIN EN ISO 105-E04: 2009 4-5 acid and alkaline
- Cleaning: fixed covers: vacuum cleaning

HEADREST:

- Frame constructed of polypropylene

ARMS:

2D Height & Width-Adjustable T-Arms:

- fiber glass reinforced nylon armrest structure
- self-skinned urethane arm pads

4D Height & Width Adjustable T-Arms with 210° Pivot:

- ebony powder coated aluminum upright
- fiber glass reinforced nylon armrest
- Self-skinned urethane arm pads

SEAT FOAM:

- molded, colored, polyurethane foam for seat
- HCFC and CFC free
- 0 Global warming factor
- "bumpered" as covered sides to protect furniture

Seat:

Density: 4.8 lbs./ft.3

IFD @ 25%: 206N

IFD @ 65%: 529N

Recovery Strength

@ 25%: 200N

Recovery Ratio: 85.4%*

Tensile Strength: 35.3 lbs./sq. in.*

Resiliency: 61%

Flammability: CAL 117

* exceeds ASTM P – 3770 – 91

construction notes

sabrina task & stool

BASE:

- ebony glass-reinforced nylon or polished diecast aluminum
- 26" diameter 5-star base

CASTERS/GLIDES:

- 60 mm (2-1/3") hard (carpet casters) are glass-reinforced nylon plastic
- optional soft casters for hard floors are glass-reinforced nylon plastic with polyurethane soft band
- twin-wheeled casters
- glass filled nylon glides
- soft glides have soft felt pads

PNEUMATIC CYLINDER:

- gas-assisted pneumatic cylinder lift

MECHANISM:

Synchro-Tilt:

- diecast aluminum, steel & plastic
- ebony powder coating

FOOTRING (STOOL):

- all-aluminum construction
- height-adjustable

SEAT:

Seat Slider (depth):

- glass-reinforced nylon plastic

Seat Structure:

- glass-reinforced nylon plastic
- formed steel plate with ebony powder coating
- plastic levers on left and right of seat control adjust

BACK:

Structural Back Frame:

- glass-reinforced nylon plastic
- polished diecast-aluminum insert

Inner Back:

- 100% polyester mesh
- elastic piece-dyed to prevent nylon fade

Lumbar Support:

- glass-reinforced nylon plastic
- ebony translucent polypropylene membrane

ARMS:

T-Arms:

- polyurethane pads
- glass-reinforced nylon plastic

HEADREST:

- glass-reinforced nylon plastic
- 100% polyester mesh

COAT HANGER:

- glass-reinforced nylon plastic

FOAM:

- molded, colored, polyurethane foam for seat
- HCFC and CFC free
- 0 global warming factor
- "bumpered" as covered sides to protect furniture

Seat:

Density: 3.2-3.6 lbs./ft³

IFD @ 25%: 206 N

IFD @ 65%: 529 N

Recovery Strength

@ 25%: 200N

Recovery Ratio: 85.4%*

Tensile Strength: 35.3 lbs./sq. in. *

Resiliency: 61%

Flammability: CAL 117

* exceeds ASTM F 3770 – 91

construction notes

savera task & stool

BASE:

- reinforced nylon plastic
- 26" base

CASTERS/GLIDES:

- 60mm (2-1/3") hard (carpet casters) are reinforced nylon
- optional soft casters for hard floors are polyurethane coated nylon
- twin-wheeled
- 2-1/8" hard plastic glides
- soft glides have soft felt pads

PNEUMATIC CYLINDER (GAS LIFT):

- gas-assisted pneumatic cylinder

MECHANISMS:

Synchro-Tilt:

- stamped steel construction
- epoxy powder coat paint

Swivel-Tilt:

- cast aluminum and stamped steel
- epoxy powder coat paint

Swivel (Stool):

- stamped steel construction
- epoxy powder coat paint

FOOTRING (STOOL):

- made of aluminum, steel tube and plastic spacer

SEAT:

- constructed of reinforced nylon

BACK:

- constructed of reinforced nylon

J-BAR:

- 5/16" solid steel
- epoxy powder coated

ARMS:

Width & Height-Adjustable T-Arms:

- reinforced nylon armrest structure
- self-skinned urethane arm pads

FOAM:

- molded, colored, polyurethane foam for seat and back
- HCFC and CFC free
- 0 Global warming factor
- "bumpered" as covered sides to protect furniture

Seat:	Back:	
Density:	2.8-3.4 lbs./ft.3	1.7-1.8 lbs./ft.3
IFD @25%:	10.77 lbs	
IFD @65%:	40 lbs	
ILD:		26-30
Flammability:	CAL 117	CAL 117

construction notes

savera xl

BASE:

- reinforced nylon plastic
 - 27" base
-

CASTERS:

- 60mm (2-1/3") hard (carpet casters) are reinforced nylon
 - optional soft casters for hard floors are polyurethane coated nylon
 - twin-wheeled
-

PNEUMATIC CYLINDER (GAS LIFT):

- heavy duty gas-assisted pneumatic cylinder
-

MECHANISMS:

Synchro-Tilt:

- stamped steel construction
 - epoxy powder coat paint
-

SEAT & BACK:

- molded plywood
-

J-BAR

- 3/8" solid steel
 - epoxy powder coated
-

ARMS:

Height-Adjustable T-Arms:

- reinforced nylon armrest structure
 - self-skinned urethane arm pads
-

FOAM:

- molded, colored, polyurethane foam for seat and back
- HCFC and CFC free
- 0 Global warming factor
- "bumpered" as covered sides to protect furniture

	Seat:	Back:
Density:	2.8-3.4 lbs./ft.3	2.8-3.4 lbs./ft.3
IFD @25%:	12.86 lbs	
IFD @65%:	43 lbs	21.37 lbs
Flammability:	CAL 117	CAL 117

t-3 task & stool

BASE:

- reinforced nylon plastic
 - 26" base
-

CASTERS/GLIDES:

- 60mm (2-1/3") hard (carpet casters) are reinforced nylon
 - optional soft casters for hard floors are polyurethane coated nylon
 - twin-wheeled
 - 2-1/8" hard plastic glides
 - soft glides have soft felt pads
-

PNEUMATIC CYLINDER: (GAS LIFT)

- gas-assisted pneumatic cylinder
-

MECHANISMS:

Synchro-Tilt:

- stamped steel construction

Swivel (Stool):

- stamped steel construction
 - epoxy powder coat paint
-

FOOTRING (STOOL):

- made of aluminum, steel tube and plastic spacer
-

SEAT:

- plywood seat pan
-

BACK:

- constructed of polypropylene
-

J-BAR:

- 1/4" solid steel
 - epoxy powder coated
-

ARMS:

Width & Height-Adjustable T-Arms:

- reinforced nylon armrest structure
 - self-skinned urethane arm pads
-

FOAM:

- block polyurethane foam for seat and back
 - HCFC and CFC free
 - 0 Global warming factor
 - "bumpered" as covered sides to protect furniture
-

construction notes

tone chair

BASE:

- glass-reinforced nylon
- 26" diameter 5-star base

CASTERS/GLIDES:

- 60mm (2-1/3") hard (carpet casters) are glass-reinforced nylon plastic
- optional soft casters for hard floors are glass-reinforced nylon plastic with polyurethane soft band
- twin-wheeled casters
- glass filled nylon glides
- soft glides for hard floors have soft felt pads

PNEUMATIC CYLINDER:

- gas-assisted pneumatic cylinder lift

MECHANISMS:

- weight Activated Synchro-Tilt. Mechanism.
- glass-reinforced nylon plastic and steel construction
- powder coated paint

SEAT:

- features seat slider

Seat Structure:

- glass-reinforced nylon plastic seat pan structure

BACK:

Structural Back Frame:

- glass-reinforced nylon plastic frame structure
- glass-reinforced polypropylene
- lumbar constructed of polypropylene

ARMS:

Height Adjustable:

- thermoplastic Polyurethane (TPU) armpad covers with flexible polyurethane foam padding
- glass-reinforced nylon plastic

SEAT FOAM:

- molded, colored, polyurethane foam for seat
- HCFC and CFC free
- 0 Global warming factor
- "bumpered" as covered sides to protect furniture

	Seat:
Density:	3.0-4.1 lbs./ft ³
IFD @25%:	25 - 40 lbs
IFD @65%:	60 - 95 lbs
Recovery Strength @ 25%:	45 lbs
Recovery Ratio:	85.4%*
Tensile Strength:	22 - 25 lbs./sq. in.
Resiliency:	61%
Flammability:	CAL 117

* exceeds ASTM F 3770 - 91

variable multi-use swivel work chair & stool

BASE:

- ebony glass-reinforced nylon or polished diecast aluminum
- 26" diameter 5-star base

CASTERS/GLIDES:

- 60 mm (2-1/3") hard (carpet casters) are glass-reinforced nylon plastic
- optional soft casters for hard floors are glass-reinforced nylon plastic with polyurethane soft band
- twin-wheeled casters
- glass filled nylon glides
- soft glides have soft felt pads

MECHANISMS:

Swivel:

- constructed of aluminum, steel and plastic
- polished diecast aluminum case
- chrome-plated steel wire lever and ebony plastic handle

CANTILEVERED FRAME:

- 3/4" (19mm) durable round steel tube, 12 gauge
- powder coating or chrome finish

FOOTRING (STOOL):

- constructed of aluminum, steel tube and ebony plastic spacer

SEAT & BACK SHELL:

- engineered, injection-molded, lightly textured 100% nylon with patented , integrated back-flex
- non-corrosive steel mechanical fasteners

FIXED ARMS:

- 3/4" (19mm) durable round steel tube, 12 gauge, arm stanchion
- powder coating or chrome-plating finish on stanchion
- ABS plastic arm pad

TABLET:

- compact laminate
- chrome plated 3/4" (19mm) durable round steel tube, 12 gauge
- steel pivot-mechanism in glass-reinforced nylon plastic case allows worksurface to pivot-up 90°

SEAT & BACK PADS:

- polypropylene and ABS plastic
- extra-strength adhesive fasteners

SEAT FOAM:

- molded, colored, polyurethane foam for seat and back
- HCFC and CFC free
- 0 Global warming factor

	Seat:	Back:
Density:	3.2-3.6 lbs./ft ³	3.2-3.6 lbs./ft. ³
IFD @ 25%:	10.77 lbs.	
IFD @ 65%:	40 lbs.	
Flammability:	CAL 117	CAL 117

construction notes

visio

BASE:

- reinforced nylon, scuff resistant plastic
 - diameter of 27"
-

CASTERS:

- 60 mm (2-1/3") soft casters glass-reinforced nylon plastic with polyurethane soft band
-

MECHANISMS:

Weight-Activated Synchro-Tilt:

- steel & plastic
 - powder coating
 - plastic levers on left and right of seat control adjust
-

PNEUMATIC CYLINDER: (GAS LIFT)

- gas-assisted pneumatic cylinder lift
-

SEAT:

- plywood seat plate
 - polypropylene cover
-

BACK:

Back Structural:

- glass-reinforced nylon plastic

Lumbar:

- constructed of polypropylene
-

ARMS:

T-Arms:

- polyurethane pads
 - glass-reinforced nylon plastic
-

MESH:

- composition: 100% Polyester
 - weight: Approx. 350 g/lm
 - flammability CAL 117
 - fastness to Light: DIN EN ISO 105-B02: 2014 3-4
 - fastness to Rubbing: DIN EN ISO 105-X12: 2014 3-4 dry and wet
 - fastness to perspiration: DIN EN ISO 105-E04: 2009 3-4
 - cleaning: fixed covers: vacuum cleaning
-

FOAM:

- molded, colored, polyurethane foam for seat
- HCFC and CFC free
- 0 global warming factor
- hardness 55
- flammability CAL 117

Density: 3.2 - 3.6 min.lbs./cu.ft

IFD @ 25%: 206 N

IFD @ 65%: 529 N

Recovery Strength @ 25%: 200 N

Recovery Ratio: 85.4 %*

Tensile Strength: 35.3lbs./sq. in.*

Resiliency: 61%

Flammability: CAL 117

* exceeds ASTM P – 3770 – 91

construction notes

ability spinner stool

BASE:

- reinforced nylon scuff-resistant plastic
- 22" diameter

CASTERS/GLIDES:

- 60mm (2-1/3") hard (carpet casters) reinforced nylon
- optional soft casters for hard floors are polyurethane coated nylon
- twin-wheeled and hooded
- 2-1/8" hard plastic glides
- soft glides have soft insert pads

MECHANISMS:

- 360° swivel
- seat height adjustment lever

PNEUMATIC CYLINDER: (GAS LIFT)

- gas-assisted pneumatic cylinder
- pneumatic cylinder provides height adjustment of 6"

SEAT:

- available in triangular (NACSPT) and round (NASCPR)
- seat slider option not available
- 2" polyurethane slab foam for support

FOAM:

- molded, colored, polyurethane foam for seat
- HCFC and CFC free
- 0 global warming factor
- "bumpered" as covered sides to protect furniture
- exceeds ASTM D - 3574 -91
- dynamic fatigue test by constant force pounding: thickness loss = 5% (specification calls for not more than 25%)

Density:	2.4 - 2.5 min.lbs./cu.ft
IFD @ 25%:	48 - 57 lbs.
IFD @ 65%:	125 lbs
Tensile Strength:	17 lbs./sq.in.
@ 25%:	157 N
Elongation:	120 min. 95.5% min.
Tensile Strength:	35.3lbs./sq. in.*
Resiliency:	55%
Flammability:	CAL 117
Compression Seat at 90% Max:	10%
Compression Modulus:	2.2 min.

construction notes

around guest

CASTERS/GLIDES/CASTERS INSERTS:

- 50mm (2") hard (carpet casters) are glass-reinforced nylon plastic
- optional soft casters for hard floors are glass-reinforced nylon plastic with polyurethane soft band
- twin-wheeled casters
- glass filled nylon glides and caster inserts
- soft glides for hard floors have soft felt pads

FRAME:

- welded steel tube
- Ebony or Gris powder coat finish

ARM:

- Glass filled nylon

SEAT:

- polypropylene plastic integrated FlexAround Seat Pan offers an advanced degree of comfort, support and ventilation

BACK:

Structural back frame:

- glass-reinforced nylon plastic frame structure designed to create a light, sculptural form with an open volume or space. Fabric-wrapped from front to back for a soft, tactile edge experience at the sides, bottom and top edge surfaces

MESH BACK:

- cushioned Mesh, featuring a dual-textured weave with coordinating colors on front and back. The mesh is breathable and provides user back support
 - elastic piece-dyed to prevent nylon fade
 - composition: 100% Polyester
 - weight: Approx.. 300 g/sq.. m
 - flammability: CAL 117
 - fastness to Light: AATCC 16..3-2014 class 5
 - abrasion Resistance: ASTM D- 4157-13, 30,000 cycles
 - piling Resistance: ASTM D-3511/D, class 5
 - cleaning: fixed covers: vacuum cleaning

UPHOLSTERED BACK:

- deep pocket in the back plate filled with molded foam to provide comfort and support

FOAM:

- molded, colored, polyurethane foam
- HCFC and CFC free
- 0 Global warming factor

Seat:

Density:	3..2-3..6 lbs./ft ³
IFD @ 25%:	206 N
IFD @ 65%:	529 lbs.
Recovery Strength @ 25%:	200 N
Recovery Ratio:	85..4%*
Tensile Strength:	35..3 lbs../sq.. in..*
Resiliency:	61%
Flammability:	CAL 117

* exceeds ASTM P – 3770 – 91

just-us chair

BASE:

- 26" diameter base of reinforced nylon, scuff resistant plastic in Ebony or Gris as specified in finish palette

CASTERS/GLIDES:

- 60 mm (2-1/3") hard (carpet casters) are glass-reinforced nylon plastic
- optional soft casters for hard floors are glass-reinforced nylon plastic with polyurethane soft band.
- twin-wheeled casters in Ebony (black) or Medium Grey (coordinated with Gris finish palette), as specified
- glass filled nylon glides
- soft glides have soft felt pads

PNEUMATIC CYLINDER (GAS LIFT):

- gas-assisted pneumatic cylinder in Ebony or Gris powder coated paint finish, as specified in finish palette

MECHANISM:

Swivel-Tilt Height-Adjustable:

- constructed of aluminum, steel and plastic
- polished diecast aluminum case
- Ebony or Gris painted steel wire lever and coordinating plastic handle

ARMS:

- glass filled nylon

BACK:

Structural back outer frame:

- constructed of glass reinforced nylon

Inner Frame:

- constructed of glass reinforced nylon

SEAT:

- glass filled nylon structural seat
- polypropylene upholstery plate (upholstered seat model only)

MESH:

Around & Just-Us Mesh:

(mesh is standard in back; optional in seat construction):

- cushioned mesh, featuring a dual-textured weave with coordinating colors & finishes on front and back. The mesh is breathable and provides user back support
 - elastic piece-dyed to prevent nylon fade
 - composition: 100% Polyester
 - weight: approx. 300 g/sq. m
 - flammability: CAL 117
 - fastness to light: AATCC 16.3-2014 class 5
 - abrasion resistance: ASTM D- 4157-13, 30,000 cycles
 - piling resistance: ASTM D-3511/D, class 5
 - cleaning: fixed covers: vacuum cleaning

SEAT FOAM (UPHOLSTERED SEAT MODEL ONLY):

- molded, colored, polyurethane foam for seat
- HCFC and CFC free
- 0 Global warming factor
- “bumpered” as covered sides to protect furniture

Seat:

Density:	3.2-3.6 lbs./ft ³
IFD @ 25%:	206N
IFD @ 65%:	529N
Recovery Strength @ 25%:	200N
Recovery Ratio:	85.4%*
Tensile Strength:	35.3 lbs./sq. in.*
Resiliency:	61%
Flammability:	CAL 117

* exceeds ASTM P – 3770 – 91

construction notes

kupp

FRAME:

- diecast aluminum left and right legs with powder coated finish
-

CASTERS/GLIDES:

- 60 mm (2-1/3") hard casters for carpet are glass-reinforced nylon plastic
 - optional soft casters for hard floors are glass-reinforced nylon plastic with polyurethane soft band
 - twin-wheeled casters
-

SEAT/BACK:

- engineered, injection-molded, lightly textured glass filled polypropylene
 - non-corrosive steel mechanical fasteners
-

ARMS:

- injection-molded glass filled nylon with over molded steel bar
 - non-corrosive steel mechanical fasteners
-

CROSS STRETCHER:

- rounded steel tube, powder coated
 - extra-strength adhesive fasteners
-

FOAM:

- block polyurethane foam for seat and back
 - HCFC and CFC free
 - 0 Global warming factor
-

FRAME/BASE:

- Welded steel tubing
-

CASTERS/GLIDES:

- 60 mm (2-1/3") hard casters for carpet are glass-reinforced nylon plastic
 - optional soft casters for hard floors are glass-reinforced nylon plastic with polyurethane soft band
 - twin-wheeled casters
 - glass filled nylon glides
 - soft glides have soft felt pads
-

MECHANISM:**Swivel:**

- constructed of welded steel and plastic
-

SEAT & BACK SHELL:

- engineered, injection-molded, lightly textured 100% nylon
 - non-corrosive steel mechanical fasteners
-

UNDERPAN:

- material polypropylene
-

SEAT PLATE:

- plywood with t-nuts
 - non-corrosive steel mechanical fasteners
-

SEAT FOAM:

- block polyurethane foam for seat and back
 - HCFC and CFC free
 - 0 Global warming factor
-

construction notes

sitara

GLIDES:

- multi-surface glides are nylon
-

FRAME:

- welded steel tubing
-

STRUCTURAL SEAT & BACK:

- engineered, injection-molded, lightly textured polypropylene
 - recyclable materials
-

INTEGRATED ARMS WITH CAP:

- arms are integrated with the frame
 - arms are available in polished aluminum or black fiberglass reinforced nylon plastic options
-

STANDARD SHIPPING CARTONS:

- double wall cardboard
 - recycled and recyclable
 - 3" reinforced gum tape (recycled)
-

FOAM:

Back:

- Upholstered back section is high-density molded foam

Seat:

- Upholstered seat section is made of colored block-foam
- seat is 1/2" thick
- foam seat grade: 2550 ultracel

Seat:

Density: 2.4-2.5 lbs./ft.3

IFD: 47-54 psi

Flammability: CAL 117

Modulus: 2.20 min @65%

construction notes

sprout stools

BASE (STOOLS & TABLES):

- 1/8" thick spun aluminum trumpet base
- optional epoxy powder coat paint finish in any standard Teknion color

GLIDES (STOOLS & TABLES):

- glass filled nylon glides with felt pads

FRAME:

- 2" diameter steel tube vertical
- welded 7/8" diameter steel tube footrest (counter and bar height models only)
- optional epoxy powder coat paint finish in any standard Teknion color

MECHANISM:

- POM plastic bushing provides 360 Degree Swivel
- footrest (on counter & bar height models) rotates with seat
- fixed height for safer use in public spaces and consistency across multiple models within a floor plate

SEAT:

- cast aluminum under pan with optional epoxy powder coat paint finish in any standard Teknion color
- Polypropylene mushroom-clip seat fastening
- plywood structure
- upholstery

SEAT FOAM:

- molded, colored, polyurethane foam for seat
- HCFC and CFC free
- 0 Global warming factor
- "bumpered" as covered sides to protect furniture

	Seat:
Density:	3.2-3.6 lbs./ft ³
IFD @ 25%:	206N
IFD @ 65%:	529N
Recovery Strength @ 25%:	200N
Recovery Ratio:	85.4%*
Tensile Strength:	35.3 lbs./sq. in.*
Resiliency:	61%
Flammability:	CAL 117

* exceeds ASTM F 3770 – 91

construction notes

synapse

FRAME:

- beech wood
-

SEAT:

- engineered, injection- molded, lightly textured polypropylene
 - aluminum
 - recyclable materials
-

GLIDES:

- polyethylene
-

FOAM:

- Upholstered section of the guest chair is made of colored block-form foam (seat only)
 - polyurethane
 - Density: 4.0 lbs./ft.3
 - IFD @25%: 42 lbf.
 - IFD @65%: 86 lbf.
 - CAL117: Pass
-

STANDARD SHIPPING CARTONS:

- double wall cardboard
 - recycled and recyclable
 - 3" reinforced gum tape (recycled)
-

FRAME:

- solid "A" grade maple
 - connections are secured with screws, glue and dowels
-

FOAM:

- molded, colored, polyurethane foam for seat
 - HCFC and CFC free
 - 0 global warming factor
-

STANDARD SHIPPING CARTONS:

- recycled foam used to protect product in box
 - double wall cardboard
 - recycled and recyclable
 - 3" reinforced gum tape (recycled)
-

construction notes

variable conference

BASE:

- diecast aluminum with polished finish
- 26" diameter 5-prong spider base

CASTERS/GLIDES:

- 60 mm (2-1/3") hard casters for carpet are glass-reinforced nylon plastic
- optional soft casters for hard floors are glass-reinforced nylon plastic with polyurethane soft band
- twin-wheeled casters
- glass filled nylon glides
- soft glides have soft felt pads

MECHANISMS:

Swivel:

- constructed of aluminum, steel and plastic
- polished diecast aluminum case
- chrome-plated steel wire lever and ebony plastic handle

CANTILEVERED FRAME:

- 3/4" (19mm) durable round steel tube, 12 gauge
- powder coating or chrome finish

SEAT & BACK SHELL:

- engineered, injection-molded, lightly textured 100% nylon with patented, integrated back-flex
- non-corrosive steel mechanical fasteners

FIXED ARMS:

- 3/4" (19mm) durable round steel tube, 12 gauge, arm stanchion
- powder coating or chrome-plating finish on stanchion
- ABS plastic arm pad

TABLET:

- compact laminate
- chrome plated SAE1010 3/4" (19mm) durable round steel tube, 12 gauge
- steel pivot-mechanism in glass-filled nylon plastic case allows worksurface to pivot-up 90°

SEAT & BACK PADS:

- polypropylene and ABS plastic
 - extra-strength adhesive fasteners
-

SEAT FOAM:

- molded, colored, polyurethane foam for seat and back
- HCFC and CFC free
- 0 Global warming factor

	Seat:	Back:
Density:	3.2-3.6 lbs./ft ³	3.2-3.6 lbs./ft. ³
IFD @ 25%:	10.77 lbs.	
IFD @ 65%:	40 lbs.	
Flammability:	CAL 117	CAL 117

construction notes

variable hybrED chair

BASE:

Storage Tray Base:

- Polypropylene, scuff resistant plastic (ebony/platinum), 27-1/2" base
- non-corrosive steel mechanical fasteners

Swivel-Height Adjustable with 5-Star Base:

- reinforced nylon, scuff resistant plastic (ebony), 27-1/2" base
- diecast aluminum 26" base (premium)

CASTERS/GLIDES:

- 60 mm (2-1/3") hard (carpet casters) are glass-reinforced nylon plastic
- optional soft casters for hard floors are glass-reinforced nylon plastic with polyurethane soft band
- twin-wheeled casters in Ebony (black) and Silver/Ebony finish.
- glass filled nylon glides
- soft glides have soft felt pads

CANTILEVERED FRAME:

- cantilevered frame & base to maximize storage capacity & allow
- 1" (25 mm) durable round steel tube, 12 gauge
- powder coating

PNEUMATIC CYLINDER (GAS LIFT):

Swivel Height Adjustable with 5-Star Base:

- gas-assisted pneumatic cylinder

MECHANISM:

Storage Tray Base:

- custom swivel mechanism constructed of aluminum, steel and plastic
- polished diecast aluminum case
- swivel range from -45° to +45°

Swivel Height Adjustable with 5-Star Base:

- constructed of aluminum, steel and plastic
- polished diecast aluminum case
- chrome-plated steel wire lever and ebony plastic handle
- 360° Swivel

WORKSURFACE:

- PC-ASA scuff-resistant plastic tablet with integrated edge barriers
- powder coated 1" (25mm) durable round steel tube, 12 gauge
- steel pivot-mechanism in glass-reinforced nylon plastic case allows worksurface to pivot 360° to provide un-handed usage

SEAT & BACK SHELL:

- engineered, injection-molded, lightly textured 100% nylon with patented, integrated back-flex
- non-corrosive steel mechanical fasteners
- 11 gauge steel reinforcement plate for seat pan

SEAT & BACK PADS:

- polypropylene and ABS plastic
- extra-strength adhesive fasteners
- options for no upholstery, upholstered pad on seat only or upholstered pads on seat & back; with single or dual upholstery options

FOAM:

- molded, colored, polyurethane foam for seat and back
- HCFC and CFC free
- 0 Global warming factor
- "bumpered" as covered sides to protect furniture

	Seat:	Back:
Density:	4.8 lbs./ft.3	5.10 lbs./ft.3
IFD @ 25%:	206N	206N
IFD @ 65%:	529N	529N
Recovery Strength @ 25%:	200N	129N
Recovery Ratio:	85.4%*	85.4%
Tensile Strength:	35.3 lbs./sq. in.*	13.83 lbs./sq. in.*
Resiliency:	61%	61%
Flammability:	CAL 117	CAL 117

* exceeds ASTM F 3770 – 91

construction notes

nami

FRAME:

- uni 7947 18 mm round steel tube
 - epoxy powder coating or chrome finish
-

SEAT AND BACK:

Plastic:

- engineered, injection- molded, lightly textured polypropylene
- recyclable materials

3D Wood:

- engineered, heat and pressure molded beech Veneer 3D Sheets form one-piece Shell
 - semi-open pore finish
-

ARMS:

- polyethylene
-

GLIDES:

- polyethylene
-

DOLLY:

- 14 gauge tubing, 7/8" diameter
 - welded steel construction
 - hard casters are dual nylon
-

BOOKRACK:

- 6 mm steel wire
 - epoxy powder coating
-

TABLET:

- compact laminate
-

GANGING CONNECTORS:

- polyethylene
-

STANDARD SHIPPING CARTONS:

- double wall cardboard
 - recycled and recyclable
 - 3" reinforced gum tape (recycled)
 - 2 chairs shipped per box
 - 1 stool shipped per box
-

variable 4-leg stacking guest chair & stool

FRAME:

- 3/4" (19mm) durable round steel tube, 14 gauge
- powder coating or chrome-plated finish
- wall saver leg
- integrated fixed arm option
- ebony nylon plastic bumpers
- non-corrosive metal mechanical fasteners

CASTERS/GLIDES:

- 60 mm (2-1/3") hard (carpet casters) are glass-reinforced nylon plastic
- optional soft casters for hard floors are glass-reinforced nylon plastic with polyurethane soft band
- twin-wheeled casters
- glass filled nylon glides
- soft glides have soft felt pads

SEAT & BACK SHELL:

- engineered, injection-molded, lightly textured 100% nylon with patented, integrated back-flex
- non-corrosive steel mechanical fasteners

FIXED ARMS:

- ABS plastic arm pad

TABLET:

- compact laminate
- chrome plated 3/4" (19mm) durable round steel tube, 12 gauge
- steel pivot-mechanism in glass-filled nylon plastic case allows worksurface to pivot-up 90°

BOOKRACK:

- chrome plated 3/16" (4.76 mm) & 1/4" (6.35 mm) round steel wire

SEAT & BACK PADS:

- polypropylene and ABS plastic
- extra-strength adhesive fasteners

SEAT FOAM:

- molded, colored, polyurethane foam for seat and back
- HCFC and CFC free
- 0 Global warming factor

	Seat:	Back:
Density:	3.2-3.6 lbs./ft ³	3.2-3.6 lbs./ft. ³
IFD @ 25%:	10.77 lbs.	
IFD @ 65%:	40 lbs.	
Flammability:	CAL 117	CAL 117

construction notes

volume

FRAME:

- SAE 1010 12mm round steel wire
 - chrome plated
-

SEAT AND BACK:

- engineered, injection- molded, lightly textured polypropylene
 - recyclable materials
 - o.s plyurethane foam (upholstered seat version)
-

ARMS:

- n/a
-

GLIDES:

- polycarbonate
-

DOLLY:

- 14 gauge tubing, 1" diameter
 - welded steel construction
 - hard casters are dual nylon. 2 lockable casters & 2 casters without locks
-

BOOKRACK:

- engineered, injection- molded, lightly textured polypropylene tray
 - recyclable materials
 - 6mm SAE 1010 steel wire
 - chrome plated
-

TABLET:

- compact laminate
 - 12 mm SAE 1010 chrome plated steel wire arm
-

GANGING CONNECTORS:

- polycarbonate
-

STANDARD SHIPPING CARTONS:

- double wall cardboard
 - recycled and recyclable
 - 3" reinforced gum tape (recycled)
-

FRAME:

- 1-1/2" x 7/8" oval tube, 16 gauge
 - 7/8" round tube, 16 gauge
 - epoxy powder coating
-

SEAT AND BACK:

- engineered, injection- molded, lightly textured polypropylene
 - recyclable materials
-

ARMS:

- 30% glass-filled nylon
-

GLIDES:

- virgin polypropylene
-

DOLLY:

- 7/8" gauge tubing
 - welded steel construction
 - hard casters are dual nylon
-

BOOKRACK:

- 18 gauge steel
 - epoxy powder coating
-

GANGING CONNECTORS:

- nylon
-

STANDARD SHIPPING CARTONS:

- double wall cardboard
 - recycled and recyclable
 - 3" reinforced gum tape (recycled)
 - 2 chairs shipped per box
-

construction notes

aegis

FRAME:

- standard modular frame made of 16 gauge welded tubing
-

WEBBING:

- made of elasbelt "Green Line" type 450/S
 - latex rubber 47%, polypropylene 53%
 - total section mmq. 94.96
 - tensile strength: 815 lbs.
-

FOAM:

VC grade foam is used. Colored block-form foam is used for seat and back.

Seat:

Density:	2.4 - 2.5 min.lbs./cu.ft
IFD @ 25%:	47 - 57 lbs
Tensile Strength:	17 lbs./sq. in
Elongation:	120 min
Resiliency:	55% min
Flammability:	CAL 117
Compression set at 90% max:	10%
Compression Modulus:	2.2 min

SIDE TABLE:

- surface is MDF, router-cut and shaped
-

STANDARD SHIPPING CARTONS:

- recycled foam used to protect product in box
 - double wall cardboard
 - recycled and recyclable
 - 3" reinforced gum tape (recycled)
-

SEAT & BOLSTER

- Robust 5/8" plywood frame construction
- 5 3/8" thick polyurethane foam wrapped with compressed fiber & upholstered
- water-based adhesive for foam attachment. Glue is not used in the upholstery process.
- nylon cable manager
- non-corrosive steel threaded inserts
- non-corrosive steel mechanical fasteners

SCREENS:

- 3/4" thick solid plywood panel
- panel is foam wrapped (1 1/4" thick) for cushioning then upholstered on front & back face
- non-corrosive steel threaded inserts
- masonite spacers

LEGS:

- (2x) powder coat die-cast aluminum leg sub-assemblies with cross-bracing between front and back legs for structure & aesthetic. All metal-to-metal fastenings. Fastenings are concealed
- all Teknion Foundation, Mica, Accent & Zones paint finishes are offered as a standard
- on-corrosive steel threaded inserts to accept metal Ganging Plate. Metal to metal fastenings are provided
- standard Ganging Plate attachment across all modules provides linear alignment & allows reconfiguration of units in the field

OPTIONAL POWER CUBE:

- one Simplex & (2x) USB mounted below seat surface per sofa
- provides fixed-location factory installed or flexible field-installed options
- allows more than one Power Cube (Simplex & (2x) USB) to be provided

GLIDES:

- multi-surface, non-marking, steel, self-leveling glides with 1/2" height adjustment

FOAM:

seat-contoured 5 3/8" max thick enhanced comfort PU blockform foam with crowned surface for enhanced comfort

Bolster-colored 2 1/4" max thick enhanced comfort PU blockform foam body with molded polyurethane back endcaps.

Screen-1/4" thick PU blockform foam.

	Seat:	Bolster:	Screen:
Density	3.2 min. lbs./cu. ft	3.2 min lbs./cu. ft	3.2 min lbs./cu. ft
IFD @ 25%:	45 - 55 lbs.	16 - 22 lbs.	16 - 22 lbs
Tensile Strength:	15 lbs./sq. in	10 lbs./sq. in	10 lbs./sq. in
Elongation:	120% min.	75% min.	75% min.
Recovery Ratio:	40% min.	45% min.	45% min.
Flammability:	CAL 117	CAL 117	CAL 117
Compression Set:	10% max @ 75%	8% max @ 90%	8% max @ 90%
Modulus:	1.90 min.	2.25 min.	2.25 min.
Hysteresis Loss:	35% max.	25% max.	25% max.

HIGH SPANNING SCREEN:

- 3/4" plywood core with HPL laminate on both sides
- 1/4" thick foam cushioning on edges, and front and back side of substrate, covered on all sides with upholstery
- non-corrosive steel threaded inserts
- masonite spacers
- powder coated, die-cast aluminum corner brackets with concealed mechanical fasteners to adjacent screens
- optional A/V mounting & wire management sub-assembly:
 - powder coated, formed steel channels & other components
 - steel mechanical fasteners

FOAM:

	Spanning Screen:
Density	3.2 min lbs./cu. ft
IFD @ 25%:	16 - 22 lbs
Tensile Strength:	10 lbs./sq. in
Elongation:	75% min.
Recovery Ratio:	45% min.
Flammability:	CAL 117

BANQS TABLES:

Surface:

- formed-natural veneer plywood with flat exposed edge follows profile of seating surface
- veneered or HPL top surface on baltic-birch plywood substrate or MDF with self-edge with straight or knife-edge profile
- optional cut-outs to accommodate power, data & lighting accessories. Light is mounted justified towards one end of the table
- powder coated metal shroud & tether sub-assembly is provided for optional wall mounting, Power Pill & A/V models. Metal shroud includes door & provides cable management

construction notes

banqs (continued)

BANQS TABLES (CONTINUED):

Post:

- Powder coat extruded aluminum channels and formed metal panels & welded steel plate flange construction to accept mechanical fasteners
- All metal-to-metal fastenings
- 72" wide table provides (2x) posts & bases for stability

Bases:

- Powder-coated x gauge flat steel base or cast-aluminum 4-prong base
- 72" wide table provides (2x) posts & flat steel bases for stability

Bases:

- Powder-coated x gauge flat steel base or cast-aluminum 4-prong base
- 72" wide table provides (2x) posts & flat steel bases for stability

Glides:

- multi-surface, non-marking, steel stacking-micro-leveling glides
- Injection-moulded stackable shims. Each table will be shipped with 4 - stackable to a max height of 1/4"

BANQS ACCESSORIES:

Zones Table Lamps:

- spun metal shade
- more to come...

Zones Pillow:

- pillow insert: Material: 585 grams 50/50 feather/THS with DPT Cover
- removable, zippered, LUUM upholstered cover

FRAME:

Seat

- 12 gauge steel frame with dymetrol flexible membrane

Back and Arms

- 12 gauge steel tubing

STORAGE SHELF:

- black polyester mesh

TABLET:

- diecast aluminum base
- surface as specified, see Fabrics & Finishes Program guide for details

CUP HOLDER:

- diecast aluminum base
- black rubber non-slip surface

CASTERS/GLIDES:

- 70 mm nylon hard casters for use on carpet
- optional soft casters for hard floors are polyurethane coated

SIDE PANELS:

- constructed of steel
- surface as specified, see Fabrics & Finishes Program guide for details

FOAM:

VC grade foam is used. Both molded polyurethane and colored block-form foam are used for seat and back

	Seat:	Back:
Density:	2.60 min.lbs./cu.ft	2.00 - 2.15 lbs./cu.ft
IFD @ 25%:	41 - 47 lbs	33 - 38 lbs
Tensile strength	10 lbs./sq. in	10 lbs./sq. in
Elongation:	75% min	75% min
Recovery ratio:	45% min	45% min
Flammability:	CAL 117	CAL 117
Compression:		
Set at 90% max:	8%	8%
Compression		
Modulus:		2.25 min. 2.25 min.
Hysteresis Loss:	25% max.	25% max.

construction notes

bonds

FRAME:

- plywood construction
 - connections are secured with screws, glue and dowels
-

CASTERS /GLIDES:

- 37 mm (1-1/2") hard casters for carpet are glass-reinforced nylon plastic
 - optional soft casters for hard floors are glass-reinforced nylon plastic with polyurethane soft band
 - twin-wheeled casters
 - glass filled nylon glides
 - soft glides have soft felt pads
 - multisurface glides
-

TABLET:

- diecast powder coated aluminum
-

FOAM:

- molded, colored, polyurethane foam for seat
 - polyurethane slab foam for sides
 - HCFC and CFC free
 - 0 global warming factor
-

AUXILIARY TABLE:

Surface:

- 0.800" THICK (3/4" MDF core) , knife edge only. laminated with balanced backer on opposite side, wood inserts for machine screws on the bottom, exposed edges are sealed with sealant

Glides:

- all surface teflon glide

Base:

- 3/8" thick CRS metal base

Column:

- 16 gauge (0.060") wall thickness CRS metal round tube

Fin:

- 10 gauge (0.134") thick CRS metal Fin

Ws Mounting Plate:

- 11 gauge (0.120") thick CRS metal plate
-

BUILDING BLOCK TABLE:

Wood Structure:

- 11/16" thick particle board core, HPL laminate /flintwood/V2 or V3

Leveller:

- all surface levelling/glide, fastened on a 14 gauge (0.075") thick CSR sheet metal plate

Inlay Material:

- duotex Panel Inlay, 6.4 mm thick

Metal Magazine Holder:

- 14 gauge and 18 gauge thick CSR sheet metal assembly, assembled with rivets and welding

Ganging Kit:

- 11 gauge (0.120") thick CSR sheet metal plate with two pieces of stick on rubber bumper
-

construction notes

collaborative ottoman

MODULAR SEATING:

Seat:

- plywood construction
- available in round or square

Base:

- reinforced nylon scuff-resistant plastic
- 22" diameter

CASTERS/GLIDES:

- 37mm (1.5") hard (carpet casters) reinforced nylon
- optional soft casters for hard floors are polyurethane coated nylon
- twin-wheeled and hooded
- 2" hard plastic glides
- soft glides have soft insert pads

FOAM:

VC grade foam is used. Colored block form foam is used for seat.

	Seat:	Back:
Density:	2.6 min. lbs./cu.ft	1.6 - 1.75 lbs./cu.ft
IFD @ 25%:	41 - 47 lbs.	16 - 22 lbs.
Tensile Strength:	10 lbs./sq. in	10 lbs./sq. in
Elongation	75% min.	75% min.
Recovery Ratio:	45% min.	45% min.
Flammability:	CAL 117	CAL 117
Set at 90% max:	8%	8%
Compression:		
Modulus:	2.25 min.	2.25 min.
Hysteresis Loss:	25% max.	25% max.

construction notes

dna

MODULAR SEATING:

Seat:

- plywood construction

Back:

- constructed of 14 gauge steel
- welded and powder coated

Glides:

- black plastic with steel thread

Foam:

VC grade foam is used. Both molded polyurethane and colored blockform foam are used for seat and back

	Seat:	Back:
Density:	2.6 min. lbs./cu.ft	1.6 - 1.75 lbs./cu.ft
IFD @ 25%:	41 - 47 lbs.	16 - 22 lbs.
Tensile Strength:	10 lbs./sq. in	10 lbs./sq. in
Elongation	75% min.	75% min.
Recovery Ratio:	45% min.	45% min.
Flammability:	CAL 117	CAL 117
Set at 90% max:	8%	8%
Compression:		
Modulus:	2.25 min.	2.25 min.
Hysteresis Loss:	25% max.	25% max.

MODULAR TABLES:

Surface:

as specified, compact laminate or baltic birch plywood substrate with natural veneer or flintwood

Base:

- plywood construction

Base Frame:

- standard modular frame constructed of steel
- welded and powder coated

Glides:

- black plastic with steel thread

Foam:

VC grade foam is used. Both molded polyurethane and colored blockform foam are used for seat and back

Density:	2.60 min. lbs./cu.ft	
IFD @ 25%:	41 - 47 lbs.	
Tensile Strength:	10 lbs./sq. in	
Elongation	75% min.	
Recovery Ratio:	45% min.	
Flammability:	CAL 117	
Compression:		
Set at 90% max:	8%	
Modulus:	2.25 min.	
Hysteresis Loss:	25% max.	25% max.

FREESTANDING TABLES:

Surface:

As specified, compact laminate or baltic birch plywood substrate with natural veneer or flintwood

Base:

- diecast aluminum base and latch (laptop table only)
- extruded aluminum post

FRAME:

- solid hardwood doweled construction
 - Ferrarra arms are made of molded maple
 - all other exposed wood is solid maple
 - rubber webbing seat
-

FOAM:

- terylene covered high density block foam
-

construction notes

tux

FRAME:

- solid hardwood, doweled construction
-

WEBBING:

- made of elasbelt "Green Line" type 450/S
 - latex rubber 47%, polypropylene 53%
 - tensile strength: 815 lbs.
-

BASE:

- standard modular frame made of 14 gauge welded square steel tubing
 - - welded & chrome plated
-

FOAM:

VC grade foam is used for seat and back

		Seat:	Back:
Density:	2.60 min. lbs./cu.ft	2.00 - 2.15 min.	lbs./cu.ft
IFD @ 25%:	41 - 47 lbs.	33 - 38 lbs.	
Tensile Strength:	10 lbs./sq. in	10 lbs./sq. in	
Elongation	75% min.	75% min.	
Recovery Ratio:	45% min.	45% min.	
Flammability:	CAL 117	CAL 117	
Compression:	CAL 117	CAL 117	
Set at 90% max:	8%	8%	
Modulus:	2.25 min.	2.25 min.	
Hysteresis Loss:	25% max.	25% max.	

FRAME:

- standard modular frame made of 16 gauge welded square tubing
- subframe assembly for seats is 1/8" metal angle iron and 1-1/2" x 1/2" 16 gauge tubing, welded and epoxy powder coated
- seat frame made from 3/4" 16 gauge square tubing

WEBBING:

- made of elabelt "Green Line" type 450/S
- latex rubber 47%, polypropylene 53%
- tensile strength: 815 lbs.

FOAM:

VC grade foam is used. Both molded polyurethane and colored block-form foam are used for seat and back.

	Seat:	Back:
Density:	2.60 min.lbs./cu.ft	2.00 - 2.15 lbs./cu.ft
IFD @ 25%:	41 - 47 lbs	33 - 38 lbs
Tensile strength	10 lbs./sq. in	10 lbs./sq. in
Elongation:	75% min	75% min
Recovery ratio:	45% min	45% min
Flammability:	CAL 117	CAL 117
Compression:	CAL 117	CAL 117
set at 90% max:	8%	8%
Compression		
Modulus:	2.25 min	2.25 min
Hysteresis Loss:	25% max	25% max

TRAY:

- surface is MDF, router cut and shaped
- frame is cold rolled steel tube with plate, epoxy powder coated

STANDARD SHIPPING CARTONS:

- recycled foam used to protect chair in box
 - double wall cardboard
 - recycled and recyclable
 - 3" reinforced gum tape (recycled)
-

construction notes

vignette swivel and lounge

FORFEITED SWIVEL:

Frame:

- molded plywood construction

Base:

- satin-chromed steel
- steel column
- glides are made of nylon and steel

Foam:

- high density block foam
-

COFFEE TABLES:

Surface:

- as specified, MDF, flintwood, natural veneer, marble, or corian

Base:

- satin-chromed steel
 - glides are made of nylon and steel
-

LOUNGE:

Frame:

- plywood construction
- rubber webbing seat

Base:

- chromed steel
- glides are made of polypropylene

Foam:

- high density block foam
-