



BEAN Specification Sheet

MATERIALS BREAKDOWN



SEAT/TOP CONSTRUCTION

SEAT/TOP LAMINATE

Constructed of 1" Nu-Green 2, ULEF (Ultra Low Emission Formaldehyde) raw particleboard core, covered and bonded with a water-based glue to a 1/16" high-pressure plastic laminate sheet on top and a plastic laminate backing sheet below for a sandwich top thickness of approximately 1-1/8". The core is made using 100% pre-consumer recycled or recovered wood fiber, and is manufactured inside a FSC Certified manufacturing facility. The top density is 39 pounds per sq. in. The top edge is routed to accept our PVC molding (Flat or Bullnose) to match or accent the top, and further bonded in place with a water based white glue. All our laminate, PVC edge tables pass BIFMA Air Quality Testing.

FRAME CONSTRUCTION

LEGS

Legs are one piece constructed on 3/16" thick cold rolled sheet metal with no welds. Legs are fastened to the inserts on the underside of the table with 1/4 -20 bolts.

CERTIFICATIONS

ANSI/BIFMA X5.4 Public & Lounge Seating
ANSI/BIFMA X5.5 Desk/Table Products

STATEMENT OF LINE - SPECIFICATIONS



1420 - Stool



BN BEAN - Table



SQ BEAN - Table

Seat Height (in)	12		
Total Height (in)	12	20.50	20.50
Seat Width (in)	18		
Total Width (in)	18	32	30
Depth (in)	18	32	30
Product Weight (lbs)	14	35	38
Qty (pcs)/Volume (cu ft)			