



# ENDZONE BENCH Specification Sheet

## MATERIALS BREAKDOWN



## FRAME CONSTRUCTION

### LAMINATE TOP

Constructed of 1" NAUF (no added urea-formaldehyde) particle board (Phase 2 CARB compliant) core with a 2" built-up edge, covered and bonded with a water-based glue to a 1/16" high-pressure plastic laminate sheet on top and a plastic laminate backing sheet below for a sandwich top thickness of 1 1/8". The core is manufactured with 100% recycled material and is manufactured inside a FSC Certified manufacturing facility. The top density is 39 pounds per sq. in.

### 2" END PANEL

The 2" thick End Panel is made using two 1" thick 9 ply particle board, covered and bonded with a water-based glue to a 1/16" high-pressure laminate sheet on top. End Panels are secured to the table top using 3/4" turn mechanical fasteners. End Panels also come with adjustable glides.

### SUPPORT BEAM

The 2" thick support beam is made using two 1" thick NAUF (no added urea-formaldehyde) particle board (Phase 2 CARB compliant) core, covered and bonded with a water-based glue to a 1/16" high-pressure plastic laminate sheet.

## SEAT CONSTRUCTION

### CUSHION

The upholstered seat cushion is made with upholstery covers form-fitted and stapled over 1 inch thick hi-resiliency polyurethane slab foam.

### FOAM

Open cell cut foam is formulated displacing 25% of the existing non-renewable petroleum material with a sustainable plant based substitute. The foam performs as regular based cut foam and provides a 1.8 PCF density with no changes to the physical properties, comfort, and longevity of the foam.

### FLAME RETARDANTS

Foam provided is compounded to meet specifications of the Federal Motor Vehicle Standard MVSS302 and California Bulletin No. 117 (TB117-2013).

## EDGE CONSTRUCTION

### 2MM BIO EDGE

2MM Bio edges are PVC-free. Made with 88% bio-based resin blend, this proprietary edge product is the leading green solution. The edge is adhered to the core material and trimmed using our "state-of-the art" edge banding process to give you a virtually pick proof edge. 2MM Bio edge has the impact durability of PVC without added chemicals. Available in 38 solid colors. 2MM Bio edge is applied to the table core using a water-based glue.

## CERTIFICATIONS

ANSI/BIFMA X5.4 Public & Lounge Seating

## OPTIONS

Power and a wire manager available. Please refer to the price list for more information.



## ENDZONE BENCH Specification Sheet

### STATEMENT OF LINE - SPECIFICATIONS



**ENDB2**



**ENDB2-CC**



**ENDB3**



**ENDB3-CCC**



**ENDB3-CCT**

Total Height (in)	17	18	17	18	18
Total Width (in)	48	48	48	72	72
Depth (in)	20	20	20	20	20
Weight Rating /Seat (lbs)	250	250	250	250	250
Product Weight (lbs)	74	80	96	105	102
Qty (pcs)/Volume (cu ft)					



**ENDB3-CTC**



**ENDB3-TCC**



**ENDB3-TCCT**



**ENDB4**



**ENDB4-CCCC**

Total Height (in)	18	18	17	17	18
Total Width (in)	72	72	72	96	96
Depth (in)	20	20	20	20	20
Weight Rating /Seat (lbs)	250	250	250	250	250
Product Weight (lbs)	102	102	102	96	130
Qty (pcs)/Volume (cu ft)					



**ENDB4-CCCT**



**ENDB4-CCTC**



**ENDB4-CTCC**



**ENDB4-TCCC**



**ENDB4-TCCCT**

Total Height (in)	18	18	18	18	18
Total Width (in)	96	96	96	96	96
Depth (in)	20	20	20	20	20
Weight Rating /Seat (lbs)	250	250	250	250	250
Product Weight (lbs)	127	127	127	127	127
Qty (pcs)/Volume (cu ft)					