



URBAN Specification Sheet

MATERIALS BREAKDOWN



FRAME CONSTRUCTION

FRAME

Constructed of high carbon content cold rolled seam welded flash controlled steel tubing free of crimping on all bends. Offered in 7/8" O.D. 14 Gauge tube. Stretcher bars are welded to the frame to provide seat support. All connections are metal to metal.

SLED BASE FRAME

The back to back sled is made of cast aluminum and is attached to the chair leg ends using a 5/16 in. threaded glide. Braze welding is used on all exposed welds.

SEAT AND BACK CONSTRUCTION

SEAT

The DuraSpec poly seat consists of over-molded polyurethane on an innovative shell made with 100% recycled materials.

BACK

Urban's back is made from polypropylene plastic and mechanically fastened to the frame.

FLAME RETARDANTS

Foam provided is compounded to meet specifications of the Federal Motor Vehicle Standard MVSS302 and California Bulletin No. 117 (TB117-2013).

OPTIONAL WOOD BACK

The maple back is comprised of a minimum of 7 layers of plywood, pressed into a 0.5 inch thick tapered back, with an outer layer of maple veneer front and back. The back can be machined with one of the standard 3 designs or with a custom logo

ARM CONSTRUCTION

The arm is constructed from molded nylon.

FEET CONSTRUCTION

GLIDES

Frame feet are finished with durable injection molded plastic glides.

CASTERS (MODEL 1402)

The caster is non-locking, twin wheel and made of a durable nylon pneumatically attached to a 5/16"- 18 threaded steel insert which is threaded through a 1/4" steel tab welded into the frame at the floor.

FOOTREST (MODELS 1421, 1426E)

Constructed of 1" NAUF (no added urea-formaldehyde) particle board (Phase 2 CARB compliant) covered and bonded to a rubber tread mat with a PVC edge.

DOLLY CONSTRUCTION

FRAME

Constructed of high carbon content cold rolled seam welded flash controlled steel tubing free of crimping on all bends. The handle is 3/4" 11 gauge tube. Stretchers that form the dolly tray are constructed from 1.5" angle bar and welded into position. The handle to dolly tray connection is friction fit and all other connections are metal to metal.

STACKING

Four point, standard width: 6 high on floor, 8 high with dolly.

Four point, midsize width: 6 high on floor, 4 high with dolly.

CERTIFICATIONS

ANSI/BIFMA X5.4 Public & Lounge Seating

OPTIONS

Wall saving, connected, casters, and stacking are available on select models. Please refer to the price list for more information.

STATEMENT OF LINE - DIMENSIONS



1401



1411



1431



1441



1404

Seat Height (in)	18	18	18	18	18
Total Height (in)	32.5	32.5	32.5	32.5	32.5
Seat Width (in)	18	18	18	18	22
Total Width (in)	24	20.1	24	20.1	27.8
Depth (in)	22	22	22	22	22
Arm Height (in)	27		27		27
Weight Rating (lbs)	500	500	500	500	500
Product Weight (lbs)	19	18	20	19	22
Qty (pcs)/Volume (cu ft)	1/11 or 2-4/22	1/11 or 2-4/22	1/11	1/11	1-3/21.25



1414



1434



1444



1402



1421

Seat Height (in)	18	18	18	18	18
Total Height (in)	32.5	32.5	32.5	32.5	43.5
Seat Width (in)	22	22	22	18	18
Total Width (in)	24	27.8	24	24	24
Depth (in)	22	22	22	22	22
Arm Height (in)		27		27	37
Weight Rating (lbs)	500	500	500	500	500
Product Weight (lbs)	21	22	23	19	25
Qty (pcs)/Volume (cu ft)	1-3/21.25	1/11	1/11	1/11 or 2-4/22	1/17



1425



1424



1426



1421E



1424E

Seat Height (in)	28	28	28	24	24
Total Height (in)	43.5	43.5	43.5	38.5	38.5
Seat Width (in)	18	22	22	18	22
Total Width (in)	20.1	27.8	27.8	24	27.8
Depth (in)	22	22	22	32	32
Arm Height (in)		37		33	33
Weight Rating (lbs)	500	500	500	500	500
Product Weight (lbs)	24	27	26	31	33
Qty (pcs)/Volume (cu ft)	1/17	1/17	1/17	1/19	1/19