



HARDI Tables & Desks - Specification Sheet

MATERIALS BREAKDOWN



BASE & TOP CONSTRUCTION

8850

Two-piece rotationally-molded highly durable Polyethylene (LDPE) infused with antimicrobial compound. Use tamper-resistant screws for assembly. Hardi is CAL 133 compliant as standard.

Sand Ballasting Capacity: 250 lbs of play sand. Ballast with bag inserted prior to pouring sand. Call Factory for more information.



BASE & TOP CONSTRUCTION

8851

Three-piece rotationally-molded highly durable Polyethylene (LDPE) infused with antimicrobial compound. Use tamper-resistant screws for assembly. Hardi is CAL 133 compliant as standard.

Sand Ballasting Capacity: 100 lbs of play sand per leg; there are two legs. Ballast with bag inserted prior to pouring sand. Call Factory for more information.



BASE & TOP CONSTRUCTION

8852

One-piece rotationally-molded highly durable Polyethylene (LDPE) infused with antimicrobial compound. No steel or wood components. Use tamper-resistant screws for assembly. Floor mount only. Hardi is CAL 133 compliant as standard.



BASE & TOP CONSTRUCTION

8853

One-piece rotationally-molded highly durable Polyethylene (LDPE) infused with antimicrobial compound. No steel or wood components. Use tamper-resistant screws for assembly. Floor and wall mount. Hardi is CAL 133 compliant as standard.



BASE & TOP CONSTRUCTION

8854

One-piece rotationally-molded highly durable Polyethylene (LDPE) infused with antimicrobial compound. No steel or wood components. Use tamper-resistant screws for assembly. Wall mount only. Hardi is CAL 133 compliant as standard.