

Model: TORTONA 1L PALAZZO

Codes: 100238602

Group: G-242


Format: 47 31/128"X5 181/256"X141/256" approx.



### ADDITIONAL NOTES

This material can show some pieces with whitening. Due to better usage of the wood, any order of this reference may contain mean percentage boards of between 10% and 15%.

### COMPOSITION



	Size	Material	Type of material
Layer 1	0.060-0.070	Varnish	Apresto Mate treatment
Layer 2	3	Hardwood Layer	Oak wood
Layer 3	9	Intermediate Layer	Wood or HDF slats
Layer 4	2	Backside	Coniferous wood

### TOLERANCES

Curvature	0.1% of length.	
-----------	-----------------	--

### LABORATORY TESTS

Resistance to abrasion	≥500	UNE-EN 13696:2009*
Mass per surface	10.95 KG/M2	EN 14342*
Thermal conductivity	0.18 W/M*K	UNE-EN 12667:2002*
Heat resistance	0.08 M2*K/W	UNE-EN 12667:2002*
Formaldehyde emissions	E1	EN 717*
Moisture content	7.00%	UNE-EN 13183-1/AC:2004*
Flammability	Dfl-s1	EN 13501*
Bulk density	782 Kg/m3	UNE-EN 323:1994*
Biological durability	Clase 1	UNE EN 335 -1 ; UNE EN 335-2*
Slip resistance (pendulum-wet)	CL 1 (30)	UNE 41901*
Slip resistance (pendulum-dry)	CL 3 (50)	UNE 41902*
Slip resistance (dcof)	0.51	ANSI A137.1*



## FEATURES

-  Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.
-  Slight smoothing of the wood using a brush to achieve a surface with a slight relief.
-  L'ANTIC COLONIAL's varnishing, in two finishes, APRESTO (gloss) and APRESTO MATE (matte), provides a unique surface quality that satisfies the most demanding requirements. Advantages: It achieves the highest cleanliness because, since the pores are sealed, dirt and dust remain on the surface and can be easily cleaned.
-  Is suitable for installing on water radiant heating
-  Material with few knots on its surface that can have different sizes depending on the type of wood. These, along with any cracks that may appear, are covered with putty.
-  It is necessary to apply adhesive for installing it.
-  There are consistent color changes between pieces.
-  Material from a European country.
-  3 mm
-  It is necessary to apply adhesive for installing it.
-  Applying a color oil or varnish on the wood surface in order to get different color ranges.
-  Beveled cut on the long sides of the board in order to create a continuity effect
-  30 Quality product made with selected raw materials, guaranteeing its full residential use for 30 years as provided by L' Antic Colonial.
-  Format where only one board has been used to finish the entire base surface
-  Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.
-  OAK Made with oak wood.
-  Material from a North American country.
-  PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests
-  Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.

## PACKING

Sales units per box	13.11 SQF/CS
Sales units per pallet	367.09 SQF/PAL
Sales units per square meter	1 M2
Sale unit	M2
Base unit	ST
Net weight	287.22 LB/SQF
Gross weight	302.49 LB/SQF

## SPECIAL PIECES

SAP	Description	Group	Boxes	Pallet	Units	SKU	Basic Unit	Net Weight	Gross weight
100153232	IGUALACION TORTONA PALAZZO 4,5X270X1,3	G-161	10 PIECES/BOX	1000 PIECES/PAL	8.23 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES
100176605	MAMPERLAN TORTONA 1L PALAZZO 7X120X3	G-163	2 PIECES/BOX	200 PIECES/PAL	11.9 PIECES/M2	-	-	1.58 KG/PIECES	1.64 KG/PIECES
100153236	TRANSICION TORTONA PALAZZO 4X270X1,3	G-161	10 PIECES/BOX	1000 PIECES/PAL	9.26 PIECES/M2	-	-	1 KG/PIECES	1.02 KG/PIECES
100153240	ZOCALO TORTONA PALAZZO 8X220X1,4	G-128	12 PIECES/BOX	600 PIECES/PAL	5.68 PIECES/M2	-	-	1.33 KG/PIECES	1.38 KG/PIECES

