


Model: AC4 STYLE 1L QUIET
Codes: 100297861
Group: G-204
Format: 7 143/256"X49 165/256"X71/256" approx.



COMPOSITION




| | Size | Material | Type of material |
|---------|------|------------------|--------------------------------------------------------|
| Layer 1 | 0.2 | Melamine | Aminoplastic thermosetting resins |
| Layer 2 | 0.1 | Decorative paper | |
| Layer 3 | 6.6 | HDF | High-density Fiber Board and water-repellent glues |
| Layer 4 | 0.1 | Backside | Sheets of kraft paper impregnated with phenolic resins |

CERTIFICATIONS


Carb certification

CARB: Phase II compliant


FEATURES




Imitates the surface of wood




20 year warranty for domestic use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.




Format where only one board has been used to finish the entire base surface




PanEuropean Forest Certification that guarantees to consumers the origin of the products from sustainably managed forests




23. Intensive residential




Abrasion-resistance level as per Standard UNE-EN 13329




Installation system where gluing the boards to the floor is not necessary. They are placed on a foam, joined together, as long as the product does not already have a foil on the back of the piece.




5 year warranty for commercial use valid for laminate floors that have been installed in rooms where they are exposed to normal wear and tear for their recommended End Use Category in accordance with EN 13329.



Is suitable for installing on water radiant heating



Safety and joint durability are the main features of this easy installation system that guarantees the elimination of gaps between boards throughout the floor's lifetime. The pressure exerted between boards reinforces the union and prevents it from being carried out incorrectly.



32. General commercial

DIMENSIONAL FEATURES

| | | |
|----------------------------------|-------------|-------------------|
| Squareness of the item (q) | ≤0.20 mm | EN 13329* |
| Difference in height among items | ≤0.15 mm | EN 13329* |
| Uv light fastness | 7 | EN 438-2,16* |
| Surface stripping | ≥1.00 N/mm2 | EN 13329 Anexo D* |



| LABORATORY TESTS | | |
|-------------------------------------------------------------------|-----------------------------------|--------------------|
| Resistance to abrasion | AC4 | UNE EN 13329:2000* |
| Impact resistance | IC2 | UNE EN 13329* |
| Resistance to staining | Grado 5 (G 1 y 2) y Grado 4 (G 3) | EN 438* |
| Resistance to cigarette burns | 4 | EN 438* |
| Furniture leg effect | No damage | EN 424* |
| Castor chair effect | No damage | EN 425* |
| Swelling in thickness | ≤18% | UNE-EN 13329* |
| Dimensional stability | Max≤0.15 mm | EN 13329* |
| Formaldehyde emissions | E1 | EN 717* |
| Slip resistance (pendulum-wet) | CL 1 (29) | UNE 41901* |
| Tensile strength of joints | >1.0 N/mm2 | EN 13329* |
| Fire resistance | Cfl-s1 | EN 13501* |
| Evaluation of propensity to accumulation of electrostatic charges | ≤2 kV | EN 14041* |
| Heat resistance | R=0.056 m2 K/W | ISO 8302-1991* |
| Swelling in thickness | ≤18% | ASTM D 1037* |
| Slip resistance (dcof) | 0.56 | ANSI A137.1* |
| Critical radiant flux | Cfl | EN ISO 9239-1* |
| Smoke density (burning) | s1 | EN 13501-1* |
| Density of the board | 890 ±5 KG/M3 | UNE EN 323* |
| Slip resistance (pendulum-dry) | CL 3 (55) | UNE 41902* |

| PACKING | | |
|------------------------------|-----------------|--|
| Sales units per box | 26.06 SQF/CS | |
| Sales units per pallet | 1355.16 SQF/PAL | |
| Sales units per unit | 2.61 SQF/ST | |
| Sale unit | M2 | |
| Base unit | ST | |
| Sales units per square meter | 1 M2 | |
| Net weight | 158.49 LB/SQF | |
| Gross weight | 162.61 LB/SQF | |

| SPECIAL PIECES | | | | | | | | | |
|----------------|--------------------------------------|-------|---------------|-----------------|----------------|-----|------------|----------------|----------------|
| SAP | Description | Group | Boxes | Pallet | Units | SKU | Basic Unit | Net Weight | Gross weight |
| 100115891 | IGUALACION STYLE QUIET 4X270X1 | G-155 | 20 PIECES/BOX | 1000 PIECES/PAL | 9.26 PIECES/M2 | - | - | 0.77 KG/PIECES | 0.77 KG/PIECES |
| 100176737 | MAMPERLAN AC4 STYLE 1L QUIET 7X120X3 | G-163 | 2 PIECES/BOX | 200 PIECES/PAL | 11.9 PIECES/M2 | - | - | 1.58 KG/PIECES | 1.64 KG/PIECES |
| 100115902 | TRANSICION STYLE QUIET 4X270X1 | G-155 | 20 PIECES/BOX | 1000 PIECES/PAL | 9.26 PIECES/M2 | - | - | 0.77 KG/PIECES | 0.8 KG/PIECES |
| 100114229 | ZOCALO STYLE QUIET 8X225X1,4 | G-107 | 12 PIECES/BOX | 648 PIECES/PAL | 5.56 PIECES/M2 | - | - | 1.57 KG/PIECES | 1.62 KG/PIECES |

