

Model: VANCOUV.BROWN ANT(24C/P) 25X150(A)

Codes: 100297087

Water absorption: Bla - Porcelanico (E<=0.1%)



## DIMENSIONAL FEATURES

Thickness	7/16" approx	+/-5%*
Width	9 13/16" approx	
Length	59 1/16" approx	
Length and width deviation	Below 0.15%	+/-0.3%*
Side straightness deviation	Below 0.15%	+/-0.3%*
Squareness deviation	Below 0.15%	+/-0.3%*
Surface flatness deviation	Below 0.15%	+/-0.4%*

\*ASTM C485/C499/C502

## MECHANICAL FEATURES

Breaking strength	812.11 LBF	>292LBF*
Modulus of rupture	11.92 LBF	>=8LBF*
Abrasion resistance	PEI 2 / 150v	
Crazing resistance	Resists 3 cycles	

\*ASTM C648

## HYGIENIC FEATURES

Chemical resistance	Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases	B Min.*
Stain resistance	Class 5. Easy cleaning with water	3 Min.*

\*ASTM C650/C1378

## SCOPE OF USE

Technical code-1	Use on medium traffic floors	
------------------	------------------------------	--

## ANTI-SLIP VALUE

Slip resistance (pendulum-wet)	CL3	
Slip resistance (ramp)	R-10	16773*
Slip resistance (bare feet)	C	16772*

\*ANSI A137.1

## PACKING

Sales units per box	20.18 SQF/CS	
Sales units per pallet	484.37 SQF/PAL	
Sales units per unit	4.04 SQF/ST	

### System Certification



Do not use cleaning agents containing hydrofluoric acid.

It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint.

For big sizes, it is recommended to fix with mortars containing polymeric additives and to use the double gluing technique.

Mosaic tiles must be grouted.

This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.