

Model: IMAGE CREAM 40X80(A)

Codes: 100202078

Water absorption: Bla - Porcelánico (E<=0.1%)



DIMENSIONAL FEATURES

Thickness	7/16" approx	+/-5%*
Width	15 11/16" approx	
Length	31 1/2" approx	
Length and width deviation	Below 0.15%	+/-0.3%*
Side straightness deviation	Below 0.15%	+/-0.3%*
Squareness deviation	Below 0.15%	+/-0.3%*
Surface flatness deviation	Below 0.15%	+/-0.4%*

*ASTM C485/C499/C502

MECHANICAL FEATURES

Breaking strength	623.87 LBF	>292LBF*
Modulus of rupture	10.8 LBF	>=8LBF*
Abrasion resistance	PEI 4 / 1500v	
Crazing resistance	Resists 3 cycles	

*ASTM C648

HYGIENIC FEATURES

Chemical resistance	Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases	B Min.*
Stain resistance	Class 5. Easy cleaning with water	3 Min.*

*ASTM C650/C1378

SCOPE OF USE

Technical code-1	Use on medium traffic floors	
------------------	------------------------------	--

ANTI-SLIP VALUE

Dynamic coefficient of friction	0.28	
Slip resistance (pendulum-wet)	CL1	
Slip resistance (ramp)	R-9	14413*
Slip resistance (bare feet)	A	
4s	34	

*ANSI A137.1

System Certification



PACKING

Sales units per box	13.78 SQF/CS	
Sales units per pallet	661.33 SQF/PAL	
Sales units per unit	3.44 SQF/ST	

System Certification



Do not use cleaning agents containing hydrofluoric acid.
It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint.
For big sizes, it is recommended to fix with mortars containing polymeric additives and to use the double glueing technique.
Mosaic tiles must be grouted.

This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.