

Model: MINNESOTA CREAM ANT(24C/P) 25X150(A)

Codes: 100297055

Water absorption: Bla - Porcelánico (E<=0.1%)



DIMENSIONAL FEATURES

Thickness	7/16" approx	+/-5%*
Width	9 13/16" approx	
Length	59 1/16" approx	
Length and width deviation	Below 0.15%	+/-0.3%*
Side straightness deviation	Below 0.15%	+/-0.3%*
Squareness deviation	Below 0.15%	+/-0.3%*
Surface flatness deviation	Below 0.15%	+/-0.4%*

*ASTM C485/C499/C502

MECHANICAL FEATURES

Breaking strength	864.07 LBF	>292LBF*
Modulus of rupture	12.37 LBF	>=8LBF*
Abrasion resistance	PEI 4 / 1500v	
Crazing resistance	Resists 3 cycles	

*ASTM C648

HYGIENIC FEATURES

Chemical resistance	Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases	B Min.*
Stain resistance	Class 5. Easy cleaning with water	3 Min.*

*ASTM C650/C1378

SCOPE OF USE

Technical code-1	Use on medium traffic floors	
------------------	------------------------------	--

ANTI-SLIP VALUE

Dynamic coefficient of friction	0.71	
Slip resistance (pendulum-wet)	CL3	

*ANSI A137.1

PACKING

Sales units per box	20.18 SQF/CS	
Sales units per pallet	484.37 SQF/PAL	
Sales units per unit	4.04 SQF/ST	

System Certification

