

Model: AIRSLATE KOTAH

Codes: 100311502

Group: G-238

Format: 250X120X0.2-0.4 approx.

Thickness range: "-5/32" approx.



RECOMMENDATIONS

Recommended adhesive	100217753 POLITECH PREMIUM COMPUESTO A + B 10KG	
Recommended joint	100236481 COLORSTUK RAPID ANTRACITA N 5KG	
Recommended joint (wet area)	100236481 COLORSTUK RAPID ANTRACITA N 5KG	100086920 FILA FOB XTREME 1L
Recommended adhesive (wet area)	100217753 POLITECH PREMIUM COMPUESTO A + B 10KG	

LABORATORY TESTS

Bulk density	1450 Kg/m3	UNE EN 1936:2007*
Water absorption at atmospheric pressure	1.00%	UNE-EN 13755:2008*
Flammability	C-S2, d0	UNE-EN 13501-1:2007+A1:2010*
Frost resistance	93.1 MPa	UNE-EN 12371:2010*
Resistance to thermal shock	T2	UNE -EN 16140:2011*
Flame-spread or surface characteristics	CLASE II	ASTM E 84*
Coefficient of linear thermal expansion	23 1/(10E6*K)	UNE-EN 10545-8*
Flexural strength	102.2 MPA	EN 12372*

FEATURES



Protection that reduces the appearance of the most common domestic bacteria.



There are considerable color changes between pieces.



Material from an Asian country.



Material suitable for use on indoor walls.



Gloss-free



Material suitable for use on outdoor walls.



Material suitable for use on shower walls.



Material that stands out for having an asymmetrical surface.

PACKING

Sales units per box	161.46 SQF/CS	
Sales units per pallet	4036.47 SQF/PAL	
Sales units per unit	32.29 SQF/ST	
Sale unit	M2	
Base unit	ST	
Net weight	107.1 LB/SQF	
Gross weight	110.27 LB/SQF	

