

Model: DELHI NATURAL HOME

Codes: 100078650

Group: G-242

Format: 15 191/256"X31 127/256"X151/256" approx.



RECOMMENDATIONS

Recommended adhesive	100031189 SUPER-ONE N GRIS 25KG	
Recommended joint	100236449 COLORSTUK RAPID CEMENTO N 5KG	
Recommended joint (wet area)	100236449 COLORSTUK RAPID CEMENTO N 5KG	100086920 FILA FOB XTREME 1L
Recommended adhesive (wet area)	100031189 SUPER-ONE N GRIS 25KG	

ADDITIONAL NOTES

Due to the texture of the slates, it is important that when they are grouted we try to cover the least amount of the pieces so as to make subsequent cleaning easier and prevent the joint from staying between the different textures.

TOLERANCES

Indoor tolerance	±4 mm (ancho), ±4 mm (largo), ±3 mm (espesor)	UNE-EN 1341:2013*
Outdoor tolerance	±4 mm (ancho), ±4 mm (largo), ±3 mm (espesor)	UNE-EN 1341:2013*

LABORATORY TESTS

Bulk density	2320 Kg/m ³	UNE EN 1936:2007*
Water absorption at atmospheric pressure	0.96 %	UNE-EN 13755:2002*
Flammability	A1f l/A1	UNE-EN 13501-1:2007+A1:2010*
Frost resistance	3.2 %	UNE-EN 12371:2011*
Resistance to abrasion (except g.7-8)	19.5 mm	UNE-EN 14157:2005*
Uniaxial compressive strength	89.04 MPA	EN 1926*
Slip resistance (dcof)	0.36	ANSI A137.1*
Flexural strength	13.7 MPA	EN 12372*
Slip resistance (pendulum-wet)	CL 3 (47)	
Slip resistance (pendulum-dry)	CL 3 (60)	

FEATURES

- Protection that reduces the appearance of the most common domestic bacteria.
- There are considerable color changes between pieces.
- Material from an Asian country.
- Material suitable for use on indoor walls.
- Gloss-free
- Material suitable for use on outdoor walls.
- Material suitable for use on shower walls.
- Material suitable for use on indoor floors.
- Material suitable for use on outdoor floors.
- Material that stands out for having an asymmetrical surface.



PACKING

Sales units per box	3.44 SQF/CS	
Sales units per pallet	268.67 SQF/PAL	
Sales units per unit	3.44 SQF/ST	
Sale unit	M2	
Base unit	ST	
Net weight	1047.55 LB/SQF	
Gross weight	1068.46 LB/SQF	

