

Elemental Edges STAIR TREADS

Specifications

Elemental Edges Stair Treads

DESIGN

Size

Treads Length: 48" (1.219m) / 72" (1.829m)

Width: 12.5" (317.5mm)

Nosing Depth: 2" (50.8mm) ADA compliant Nosing Radius: 1/4" (6mm) ADA compliant

Length: 48" (1.219m) / 72" (1.829m) Width: 20" (508mm)

Nosing Depth: 2" (50.8mm) ADA compliant

Nosing Radius: 1/4" (6mm) ADA compliant

.125" (1/8")

Overall Gauge Colors Available

Treads with Risers

Quickship 14 Made to Order 56

PERFORMANCE

Classification ASTM F2169 Resilient Stair Treads Type TP, Class 2 Group 1 & 2

(Visually Impaired Safety Strip)

Resistance to Chemicals ASTM F925 - Passes, No More Than Slight Changes

Resistance to Light ASTM F1515 - Passes, $\Delta E = 4.2$ Resistance to Heat ASTM F1514 - Passes, $\Delta E = 4.8$

Critical Radiant Flux ASTM E648 - > 0.45 Smoke Density ASTM E662 - < 450 Slip Resistance ASTM D2047 SCOF \geq 0.64 Hardness ASTM D2240 95 Shore A

SUSTAINABILITY

Certification FloorScore® Certified

Country of Origin

SERVICE

Warranties Limited 10 Year Warranty

For detailed warranty, installation and adhesive information visit mohawkgroup.com