







ColorBeat

Solid, all loop textured tile available in 48 colors as 24x24 tile with select colors available as 12x36 plank. Install as a border, inset or accent tile.



Named for the Filipino word meaning "to learn," Matuto is a high-performance LVT that offers a stylish, cost-effective alternative to VCT and allows for design creativity in the toughest commercial environments.



CONSTRUCTION The contemporary design and 12" x 24" tile size of Matuto offers creativity and flexibility for a wide variety of installation methods.

PERFORMANCE The 20 mil commercial wear layer coated with M-Force™ enhanced urethane finish provides durability and cleanability with a no-polish option that allows for cost-effective maintenance.

COLOR Specifically designed to coordinate with Mohawk Group's color bank, Matuto's full range of neutrals and brights works perfectly with many of our carpet collections.

Colorways 646 Green Grass 555 Blue Night 453 Vivid Violet 353 Red Hot 252 Outrageous Orange 121 Unmellow Yellow 123 Barely Beige 133 Totally Tan 858 Bronze Blast 378 Chocolate Bar 976 Blackout 959 Grey Granite

EcoFlex[™] ICT carpet tile backing





PERFORMANCE

- Unsurpassed dimensional stability - no growing or shrinking
- Constructed with an ultra dense five layer cushion backing system
- Main body of tile provides an effective moisture barrier (not applicable at the seams)
- Tiles are impervious to moisture damage from spills and water extraction cleaning
- Construction features superior tuft bind that is highly resistant to edge ravel
- Proven performance for over 15 years



BUDGET

 Superior construction offers reliability for the life of your installation



SUSTAINABILITY

- EcoFlex ICT contains 35% minimum pre consumer recycled content by total weight*
- Recyclable through Mohawk's ReCover program
- EcoFlex ICT may contribute to or comply with LEED® credits MR 4.0, IEQ 4.3 and Innovation credit for NSF 140
- CRI Green Label Plus certified
- Free of EPA phthalates of concern

- Certified at the Gold Level in accordance with NSF/ANSI 140 the Sustainability Assessment for Carpet
- NSF/ ANSI 140 Platinum level version available with a minimum of 10% post-consumer recycled content



SERVICE


• Engineered performance for an overall better after sales service experience


^{*} Recycled content claim third party verified by UL (Underwriters Laboratory)

Style Name / Number	Hyper Earth / BT405
Construction	Tufted
Surface Appearance	Textured Patterned Loop
Gauge	1/12" (47.00 rows per 10 cm)
Dye Method	Solution Dyed
Fiber Type	ColorStrand® SD Nylon
Stain Release Technology	Sentry Plus Stain Protection
Soil Release Technology	Sentry Soil Protection
Backing Material	EcoFlex ICT
Indoor Air Quality	Green Label Plus Certified # 1098
NSF 140	Gold
Size	12" x 36" (.3048 m x .9144 m)
Installation Method	Monolithic / Half-Lap / Brick Ashlar /
	BasketWeave / Plank Half-Lap /
	Monolithic Stepping / Random /
	Herringbone
Flammability	ASTM E 648 Class 1 (Glue Down)
Smoke Density	ASTM E 662 Less than 450
Static Propensity	AATCC - 134 Under 3.5 KV
Warranties: Lifetime Limited Carpet Tile Warranty, Lifetime Limited	

Duracolor Stain Warranty, Lifetime Static

For Iconic Earth, ColorBeat and Matuto spec information, visit our website at www.mohawkgroup.com





Mohawk Industries, Inc. warrants its adhesives for the life of the original installation only when a Mohawk Industries style (product) is installed. Mohawk's floor preparation procedures must be followed to ensure that the substrate has been prepared properly. Failure to use Mohawk Industries adhesives or to follow Mohawk's floor preparation procedures will void all lifetime adhesive warranties. Please contact your local Sales Representative for installation guidelines.

your local Sales Representative for installation guidelines.

These paterns contain inherent characteristics which may result in pattern run off and/or pattern appearance variations at the seams or tile edges (darker or lighter pattern lines). These characteristics are inherent in the patterns and are not manufacturing defects. Consideration to these characteristics should be given when selecting an installation method.

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to prevent premature or accelerated wear. Walk-off tiles from the Tuff Stuff II Collection are recommended at entryways to reduce soiling.

Mohawk Group is providing this architect folder for the purpose of promoting our commercial business. This folder and its samples shall remain the property of Mohawk Group. Color may vary from dye lot to dye lot. Substitution of material may be made due to improved technology, supply limitations or other factors. The performance of this product is not affected by such variations.

For current and complete specifications please visit www.mohawkgroup.com









