Denim



















The performance standard for every application, Duracolor fiber is forever stain free, forever sustainable and forever beautiful, guaranteed*. Carpet is easy to maintain with inherent stain resistance and water-only stain removal.

FOREVER STAIN FREE

- Permanent built in protection
- Resists 99% of all stains
- Passes the GSA Test Method for stain resistance:
 AATCC Test Method 175
- Duracolor Warranty: We guarantee it

FOREVER SUSTAINABLE

- Made with 30% recycled content: 25% pre-consumer
 5% post-consumer
- No Chemicals required:
 96% of all common stains clean with just water
- Declare Red List Free:
 Duracolor fiber is Declare red
 list free in accordance with the
 Living Building Challenge

- Lasts Longer: Product life is extended, reducing the impact to your bottom line and to the environment
- Recyclable through Mohawk's ReCover Program

FOREVER BEAUTIFUL

- Available in more than 300 colors
- Unsurpassed colorfastness to light and atmospheric contaminants so colors won't fade
- Unmatched design flexibility without compromising color retention or stain resistance
- Proven track record of success over the past 20 years



Duracolor



Competitor Solution Dyed / Yarn Dyed Blend

^{*} See Mohawk Group official warranty documents for further details at www.mohawkgroup.com

ColorBeat

Solid, all loop textured tile available in 48 colors. Select colors also available as 12x36 plank. Install as a border, inset or accent tile.



ı	Brand	Lees
	Style Name / Number	Hem 24x24 / GT178
	Construction	Tufted
	Surface Appearance	Textured Patterned Loop
	Gauge	1/12" (47.00 rows per 10 cm)
	Dye Method	Solution Dyed / Yarn Dyed
	Fiber Type	duracolor. Premium Nylon
	Stain Release Technology	Permanent, Built into the Fiber
	Soil Release Technology	Sentry Soil Protection
	GSA Stain Release Rating	Passes
	Backing Material	EcoFlex ICT
	Indoor Air Quality	Green Label Plus Certified # 1098
	NSF 140	Gold
	Size	24" x 24" (.6096 m x .6096 m)
	Installation Method	Quarter Turn / Brick Ashlar
	Flammability	ASTM E 648 Class 1 (Glue Down)
	Smoke Density	ASTM E 662 Less than 450
	Static Propensity	AATCC - 134 Under 3.5 KV
	Warranties: Lifetime Limited (Carpet Tile Warranty, Lifetime Limited
	Duracolor Stain Warranty, Life	etime Static

Style Name / Number	ľ	Brand	Lees
Surface Appearance	ı	Style Name / Number	Hem 12x36 / GT295
Gauge	1	Construction	Tufted
Dye Method	1	Surface Appearance	Textured Patterned Loop
Fiber Type	1	Gauge	1/12" (47.00 rows per 10 cm)
Stain Release Technology Permanent, Built into the Fiber Soil Release Technology Sentry Soil Protection GSA Stain Release Rating Passes Backing Material EcoFlex ICT Indoor Air Quality Green Label Plus Certified # 1098 NSF 140 Gold Size 12" x 36" (.3048 m x .9144 m) Installation Method Monolithic / Half-Lap / Brick Ashlar BasketWeave / Plank Half-Lap / Monolithic Stepping / Random / Herringbone Flammability ASTM E 648 Class 1 (Glue Down) Smoke Density ASTM E 662 Less than 450 Static Propensity AATCC - 134 Under 3.5 KV Warranties: Lifetime Limited Carpet Tile Warranty, Lifetime Limited	ı	Dye Method	Solution Dyed / Yarn Dyed
Soil Release Technology	ı	Fiber Type	duracolor. Premium Nylon
GSA Stain Release Rating Passes Backing Material	ı	Stain Release Technology	Permanent, Built into the Fiber
Backing Material	ı	Soil Release Technology	Sentry Soil Protection
Indoor Air Quality	ı	GSA Stain Release Rating	Passes
NSF 140	ı	Backing Material	EcoFlex ICT
Size	ı	Indoor Air Quality	Green Label Plus Certified # 1098
Installation Method	ı	NSF 140	Gold
BasketWeave / Plank Half-Lap / Monolithic Stepping / Random / Herringbone Flammability	ı	Size	12" x 36" (.3048 m x .9144 m)
Monolithic Stepping / Random / Herringbone Flammability	ı	Installation Method	Monolithic / Half-Lap / Brick Ashlar
Herringbone Flammability	ı		BasketWeave / Plank Half-Lap /
Flammability	ı		Monolithic Stepping / Random /
Smoke Density	ı		Herringbone
Static Propensity AATCC - 134 Under 3.5 KV Warranties: Lifetime Limited Carpet Tile Warranty, Lifetime Limited	ı	Flammability	ASTM E 648 Class 1 (Glue Down)
Warranties: Lifetime Limited Carpet Tile Warranty, Lifetime Limited	ı	Smoke Density	ASTM E 662 Less than 450
· · · · · · · · · · · · · · · · · · ·	ı	Static Propensity	AATCC - 134 Under 3.5 KV
Duracolor Stain Warranty, Lifetime Static	ı	Warranties: Lifetime Limited (Carpet Tile Warranty, Lifetime Limited
	ı	Duracolor Stain Warranty, Life	etime Static

Each order of Hem 12x36 will have about one half of the accent stripe in each box. We aren't able to guarantee the exact number of accent stripes in each box and suggest opening multiple boxes if your installation requires a more precise distribution of the accent stripe.


2BY36

]	Brand Style Name / Number	Lees Zip It / GT296
	Construction	•
2	Surface Appearance	
د	Gauge	1/12" (47.00 rows per 10 cm)
١,	Dye Method	Solution Dyed / Yarn Dyed
	Fiber Type	duracolor, Premium Nylon
	Stain Release Technology	Permanent, Built into the Fiber
	•,	
	Soil Release Technology	Sentry Soil Protection
	GSA Stain Release Rating	Passes
	Backing Material	
	Indoor Air Quality	Green Label Plus Certified # 1098
	NSF 140	Gold
	Size	12" x 36" (.3048 m x .9144 m)
	Installation Method	Monolithic / Half-Lap / Brick Ashlar /
		BasketWeave / Plank Half-Lap /
		Monolithic Stepping / Random /
		Herringbone
	Flammability	ASTM E 648 Class 1 (Glue Down)
	Smoke Density	ASTM E 662 Less than 450
	Static Propensity	
	· · · · · · · · · · · · · · · · · · ·	Carpet Tile Warranty, Lifetime Limited
	Duracolor Stain Warranty, Life	

Construction

For ColorBeat, Jean and Selvedge spec information, visit our website at www.mohawkgroup.com

Installation Instructions:



Mohawk Industries, Inc. warrants its adhesives for the life of the original installation only when a Mohawk Industries style (product) is installed. Mohawk's floor preparation procedures must be followed to ensure that the substrate has been prepared properly. Failure to use Mohawk Industries adhesives or to follow Mohawk's floor preparation procedures will void all lifetime adhesive warranties. Please contact your local Sales Representative for installation guidelines.

These patterns contain inherent characteristics which may result in pattern run off and/or pattern appearance variations at the seams or tile edges (darker or lighter pattern lines). These characteristics are inherent in the patterns and are not manufacturing defects. Consideration to these characteristics should be given when selecting an installation method.

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to prevent premature or accelerated wear. Walk-off tiles from the Tuff Stuff II Collection are recommended at entryways to reduce soiling.

Duracolor by Mohawk Stain Resistant System passes GSA requirements for permanent stain resistance. Under GSA requirements stain resistant carpets must score no less than 8.0 (10.0 is best) on the AATCC tested using AATCC test method 175.

Mohawk Group is providing this architect folder for the purpose of promoting our commercial business. This folder and its samples shall remain the property of Mohawk Group. Color may vary from dye lot to dye lot. Substitution of material may be made due to improved technology, supply limitations or other factors. The performance of this product is not affected by such variations.

For current and complete specifications please visit www.mohawkgroup.com









