

R | HIGHLAND FOREST PRODUCT SPECIFICATIONS



COLLECTION	Highland Forest
STYLE NUMBER	I200V
CONSTRUCTION	Commercial Luxury Vinyl Plank
WEAR LAYER THICKNESS	20 mil / 0.02 inches (0.508 mm)
OVERALL THICKNESS	0.098 inches (2.5 mm)
EDGE PROFILE	Squared Edge
REFERENCE SPECIFICATION	ASTM F1700 Class III printed film vinyl plank Type B (embossed)
FINISH	ExoGuard®
INSTALLATION TYPE	Dry Back
INSTALLATION	Glue Down
RECOMMENDED ADHESIVE	LOKWORX+ RESILI, LOKWORX+ RESILIENT, LOKWORX RESILIENT, 4151 or S150 SPRAY ADHS

Packaging

PLANK SIZE
PIECES /BOX
AREA /BOX
WEIGHT /BOX

US Units
 4 inches W x 36 inches L
 36
 35.95 sq ft
 30.6 lbs

Metric Units
 10.2 cm W x 91.4 cm L
 3.3 sq m
 13.9 kg

Performance Testing

STATIC LOAD / ASTM F970	Passes (Modified), *750 lbs
RESIDUAL INDENTATION / ASTM F1914	Passes
RESISTANCE TO CHEMICALS / ASTM F925	Passes
RADIANT PANEL / ASTM E648	Passes, Class I
SMOKE DENSITY / ASTM E662	Passes
SLIP RESISTANCE / ASTM D2047	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

*Results are based on a laboratory test and used for comparative purposes. Real life load limit may vary.
 Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

R | HIGHLAND FOREST


Warranty

15 Year Limited Commercial.


Commercial Limited Underbed Bond Warranty S150/4151/Lokworx+ Resilient.

Please visit patcraft.com for the most current warranty information.


Installation Methods



Brick



Herringbone



Stagger

[Installation Guidelines](#)

[Maintenance Guidelines](#)

Environmental

FLOORSCORE®

Certified