M | Speak In Design PRODUCT SPECIFICATIONS

COLLECTION	Speak Your Language
STYLE NUMBER	I0240
PRODUCT TYPE	Tile
CONSTRUCTION	Multi-Level Pattern Loop
FIBER TYPE	EcoSolution Q100™ Nylon
DYE METHOD	100% Solution Dyed
PRIMARY BACKING	Non-Woven Synthetic
SECONDARY BACKING	EcoWorx® Tile
TRAFFIC RATING	Severe
PROTECTIVE TREATMENTS	SSP® Shaw Soil Protection
GSA APPROVED PRODUCT	Yes

	US Units	Metric Units
PRODUCT SIZE	24 inches x 24 inches	60.96 cm x 60.96 cm
AREA PER BOX	48 ft²	4.46 m²
PIECES PER BOX	12	
GAUGE	1/12 inches	47.24 per 10 cm
STITCHES	10 per inches	40.03 per 10 cm
FINISHED PILE THICKNESS	0.09 inches	2.29 mm
AVERAGE DENSITY	7200 oz/yd³	0.27 g/cm³
TOTAL THICKNESS	0.216 inches	5.49 mm
TUFTED YARN WEIGHT	18 oz/yd²	610.30 g/m²
MERGEABLE DYE LOT	Yes	

Performance Testing

PILL TEST	Pass
RADIANT PANEL	Class I
NBS SMOKE	Less than 450
ELECTROSTATIC PROPENSITY	Less than 3.5 kv
CRI GREENLABEL PLUS	GLP9968
ADA COMPLIANCE	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranty

Lifetime Commercial Limited

Please visit patcraft.com for the most current warranty information.

patcraft®

M | Speak In Design

Installation Methods

Quarter Turn   Random   Monolithic   Brick   Ashlar

Installation Guidelines
Maintenance Guidelines

Environmental Specifications

RECYCLABILITY   100% recyclable

Materials

Ingredients
DOES NOT CONTAIN   does not contain PVC, phthalates or PBD/PBDE

Recycled Content
TOTAL RECYCLED CONTENT (BY WEIGHT)   59%
PRE-CONSUMER   59%
POST-CONSUMER   0%

Meets or exceeds all local and national regulations in country of manufacture. Manufactured in an ISO9001 & ISO14001 certified facility or equivalent. Recycled content is calculated using system allocation, mass balance, and direct insertion. The actual recycled content in this product will likely vary. For more information email info@patcraft.com.

Third Party Certifications

CRADLE TO CRADLE CERTIFIED®   Silver Level (Version 4.0)
HEALTH PRODUCT DECLARATION (HPD)   1,000 ppm Disclosure
ENVIRONMENTAL PRODUCT DECLARATION(EPD)   3rd Party Certified in Accordance with ISO14044, ISO14025 & EN15804
DECLARE   LBC Compliant
NSF 140   Gold
CRI GREEN LABEL PLUS (GLP)   GLP9968
ENVIRONMENTAL GUARANTEE   Free transport and recycling within the United States and Canada.
PRODUCT PACKAGING   100% Recyclable
USGBC LEED   contributes
BUILDING RESEARCH ESTABLISHMENT   certified
GOOD ENVIRONMENTAL CHOICE AUSTRALIA   certified