

'22

TILE & STONE
COLLECTIONS

TECHNICAL DATA 2022



TECHNICAL DATA												TILE APPLICATIONS						#WHYTILE					
Series	 Trim Available	 Wear Rating/PEI	 Shade/Texture Spectrum (STS) Rating	 Scratch Hardness	 Water Absorption	 Breaking Strength	 Frost Resistance	 Recycle Content Pre-Consumer	 Recycle Content Post-Consumer	 Tile Thickness	 Rec. Grout Joints*	 ID Floors (Level Interior, Dry)	 IW Floors (Level Interior, Wet)	 W+ Floors (Interior, Wet Plus)	 EW Floors (Exterior, Wet)	 OG Floors (Oils/Greases)	 WB Walls/ Backsplash	 Pet Friendly	 Absolute Waterproof	 Easy to Clean	 Family Friendly	 Scratch Proof	 Stain Proof
ANSI Designation				MOHS Scale	ASTM C373	ASTMC648	ASTM C1026					ANSI A326.3	ANSI A326.3	ANSI A326.3	ANSI A326.3	ANSI A326.3							
ANSI Standard				N/A	≤3%	≥250 lbs	Resistant		± 0.3 mm			≥0.42 Wet	≥0.42 Wet	≥0.50 Wet	≥0.55 Wet	≥0.55 Wet							
Adobe	Yes	IV/III/II	V2	8.0	<3.00%	>600 lbs	Resistant	8.93%	16.60%	12x24 = 10.8 mm 16x16 = 8.8 mm	3/16"	●	●	●	●	●	●	●	●	●	●	●	●
Amalfi Stone	Yes	IV/III	V4	8.0	<3.00%	>400 lbs	Resistant	19.40%	11.10%	12x24 = 10.8 mm 16x16 = 8.8 mm 13x13 = 8.2 mm	3/16"	●	●				●	●	●	●	●	●	●
Amazonia	No	IV	V3	8.0	<0.50%	>450 lbs	Resistant	N/A		11.3 mm	3/16"	●	●				●	●	●	●	●	●	●
Aria	Yes	IV/III	V2	5.5	<0.50%	>600 lbs	Resistant	3.00%	N/A	18x36 = 11.0 mm 12x24 = 9.5 mm	1/8"	●	●				●	●	●	●	●	●	●
Artisan Wood	No	IV/III	V3	6.5	<0.50%	>550 lbs	Resistant	N/A	N/A	9.0 mm	1/8"	●	●				●	●	●	●	●	●	●
Black Forest	No	IV/III	V3	6.5	<0.50%	>450 lbs	Resistant	12.50%	23.70%	7½x47 = 11.3 mm	1/8"	●	●	●			●	●	●	●	●	●	●
Burano	Yes	IV/III	V2	6.5	<3.00%	>450 lbs	Resistant	5.00%	16.00%	12x24 = 10.8 mm 16x16 = 8.8 mm	3/16"	●	●				●	●	●	●	●	●	●
Catalina	Yes	IV	V3	6.0	<0.50%	>500 lbs	Resistant	5.00%	16.00%	12x24 = 11.2 mm	3/16"	●	●				●	●	●	●	●	●	●
ColorTheory	Yes	130m³	V1	7.0	<0.50%	>540 lbf.	Resistant	10.00%	N/A	9.6-9.8 mm	1/8"	●	●				●	●	●	●	●	●	●
Concrete	Yes	IV/III	V2	8.0	<0.50%	>600 lbs	Resistant	3.00%	N/A	6x24 = 10.3 mm 12x24 = 10.3 mm 24x24 = 10.3 mm	1/8"	●	●	●	●	●	●	●	●	●	●	●	●
Construct	Yes	IV/III	V3	5.0	<0.50%	>500 lbs	Resistant	5.00%	16.00%	18x36 = 11.3 mm 12x24 = 11.2 mm	3/16"	●	●				●	●	●	●	●	●	●
Contessa	Yes	IV	V2	7.0	<0.50%	>450 lbs	Resistant	17%		11.0-11.3 mm	3/16"	●	●				●	●	●	●	●	●	●
Contour	Yes	IV	V3	6.0	<3.00%	>450 lbs	Resistant	19.20%	11.40%	12x24 = 10.8 mm	3/16"	●	●				●	●	●	●	●	●	●
Cortina	Yes	IV/III	V3	5.5	<0.50%	>600 lbs	Resistant	3.00%	N/A	18x36 = 11.0 mm 12x24 = 9.5 mm	1/8"	●	●				●	●	●	●	●	●	●
Crescent	Yes	IV/III	V3	5.0	<3.00%	>400 lbs	Resistant	19.20%	11.10%	12x24 = 10.8 mm 16x16 = 8.8 mm	3/16"	●	●				●	●	●	●	●	●	●
Crosswind	Yes	IV/III	V2	8.0	<3.00%	>600 lbs	Resistant	7.50%	14.30%	10.8 mm	3/16"	●	●	●			●	●	●	●	●	●	●
Dash	Yes	N/A	V1	6.0	<0.25%	>400 lbs	Resistant			8.7 mm	3/16"	●	●	●	●	●	●	●	●	●	●	●	●
Dossier	Yes	IV/III/II	V2	7.0	<0.50%	>475 lbs	Resistant	3.00%	N/A	24x24 = 9.5 mm 12x24 = 9.5 mm	1/8"	●	●				●	●	●	●	●	●	●
Elements	No	II	V1	5.0	<0.50%	>275 lbs	Resistant	21.44%	N/A	6.0 mm	3/16"	●	●				●	●	●	●	●	●	●
Elysium	Yes	IV/III	V2	6.5	<3.00%	>500 lbs	Resistant	18.20%	11.10%	12x24 = 10.8 mm 16x16 = 8.8 mm 13x13 = 8.2 mm	3/16"	●	●				●	●	●	●	●	●	●
Encierro	Yes	IV/III	V4	6.5	<3.00%	>450 lbs	Resistant	19.20%	11.40%	12x24 = 10.8 mm 16x16 = 8.8 mm	3/16"	●	●				●	●	●	●	●	●	●
Farmhouse	Yes	IV/III	V3	8.0	<3.00%	>600 lbs	Resistant	8.93%	16.60%	10.8 mm	3/16"	●	●	●			●	●	●	●	●	●	●
Forester	No	IV/III	V4	7.0	<3.00%	>550 lbs	Resistant	19.40%	11.10%	10.8 mm	3/16"	●	●				●	●	●	●	●	●	●
Form	No	IV/III/II	V2	6.5	<3.00%	>300 lbs	Resistant	18.20%	16.40%	8x8 = 7.6 mm	3/16"	●	●				●	●	●	●	●	●	●
Formation	Yes	IV/III	V2	8.0	<0.50%	>480 lbs	Resistant	3.00%	N/A	24x24 = 10.3 mm 12x24 = 10.3 mm	1/8"	●	●	●	●	●	●	●	●	●	●	●	●
FortyEight	No	IV/III	V3	5.0-7.0	<0.50%	>550 lbs	Resistant			24x48 = 11.3 mm	1/8"	●	●	●	●	●	●	●	●	●	●	●	●
Framework	Yes	IV/III	V2	8.0	<0.50%	>510 lbs	Resistant	3.00%	N/A	24x24 = 10.3 mm 12x24 = 10.3 mm	1/8"	●	●				●	●	●	●	●	●	●
Function	Yes	IV/III/II	V2	6.5	<3.00%	>500 lbs	Resistant	19.40%	5.00%	12x24 = 10.8 mm 16x16 = 8.8 mm 13x13 = 8.2 mm	3/16"	●	●				●	●	●	●	●	●	●
Gala	Yes	IV/III	V2	8.0	<0.50%	>450 lbs	Resistant	3.00%	N/A	24x24 = 9.5 mm 12x24 = 9.5 mm	1/8"	●	●				●	●	●	●	●	●	●
Gosford Park	No	IV/III	V3	8.0	<0.50%	>400 lbs	Resistant	5.00%	16.00%	8x40 = 9.0 mm	1/8"	●	●	●	●	●	●	●	●	●	●	●	●
Habitat	Yes	IV/III	V2	7.5	<3.00%	>300 lbs	Resistant	20%		16x16 = 8.8 mm 13x13 = 8.8 mm	3/16"	●	●				●	●	●	●	●	●	●
Lakemont	Yes	IV	V2	5.5	<3.00%	>500 lbs	Resistant	19.40%	11.90%	12x24 = 10.8 mm 16x16 = 8.8 mm 13x13 = 8.2 mm	3/16"	●	●	●			●	●	●	●	●	●	●

All tiles meet or exceed ASTM standards for chemical resistance (ASTM C650), crazing resistance (ASTM C424), and thermal shock (ASTM C484) unless otherwise noted.
NOTE: Due to the inherent nature of fired ceramic tile, it is important to note that the coefficient of friction may vary within and between product runs

*Minimum size and related allowances are provided in ANSI A108.02. Refer to "Grout Joint Size, Layouts, and Patterns" in the Tile Council of North America's "Handbook for Ceramic, Glass, and Stone Tile Installation."

TECHNICAL DATA												TILE APPLICATIONS						#WHYTILE					
Series	 Trim Available	 Wear Rating/PEI	 Shade/Texture Spectrum (STS) Rating	 Scratch Hardness	 Water Absorption	 Breaking Strength	 Frost Resistance	 Recycle Content	 Post-Consumer	 Tile Thickness	 Rec. Grout Joints*	 ID	 IW	 W+	 EW	 OG	 WB	 Pet Friendly	 Absolute Waterproof	 Easy to Clean	 Family Friendly	 Scratch Proof	 Stain Proof
ANSI Designation				MOHS Scale	ASTM C373	ASTMC648	ASTM C1026					ANSI A326.3	ANSI A326.3	ANSI A326.3	ANSI A326.3	ANSI A326.3							
ANSI Standard				N/A	≤3%	≥250 lbs	Resistant		± 0.3 mm			≥0.42 Wet	≥0.42 Wet	≥0.50 Wet	≥0.55 Wet	≥0.55 Wet							
Madison Square	Yes	IV	V3	7.0	<3.00%	>600 lbs	Resistant	8.93%	16.60%	10.8 mm	3/16"	●	●				●	●	●	●	●	●	●
Manitoba	No	IV/III	V3	9.0	<3.00%	>400 lbs	Resistant	31.70%	5.00%	10.8 mm	3/16"	●	●				●	●	●	●	●	●	●
Modulor	Yes	IV/III	V2	6.0	<0.50%	>600 lbs	Resistant	3.00%	N/A	18x36 = 11.0 mm 12x24 = 9.5 mm	1/8"	●	●	●			●	●	●	●	●	●	●
Montreaux	Yes	IV	V3	6.5	<3.00%	>350 lbs	Resistant	20%		13x13 = 8.2 mm	3/16"	●	●				●	●	●	●	●	●	●
Norway	No	IV/III	V3	7.5	<3.00%	>400 lbs	Resistant	19.20%	11.40%	10.8 mm	3/16"	●	●				●	●	●	●	●	●	●
Pulse	Yes	IV/III/II	V2	7.0	<0.50%	>475 lbs	Resistant	18.00%	N/A	24x24 = 9.5 mm 12x24 = 9.5 mm	1/8"	●	●	●			●	●	●	●	●	●	●
QuarryBasics	Yes	N/A	V2	7.0	<3.00%	400 lbs	Resistant	9.5%		12.7 mm	3/16"	●	●	●	●	●	●	●	●	●	●	●	●
Quartzite	Yes	IV/III	V3	9.0	<3.00%	>650 lbs	Resistant	19.20%	11.40%	18x36 = 11.3 mm 12x24 = 10.8 mm 16x16 = 8.8 mm	3/16"	●	●				●	●	●	●	●	●	●
Railwood	No	IV/II	V3	6.0	<3.00%	>600 lbs	Resistant	31.70%	5.00%	10.8 mm	3/16"	●	●				●	●	●	●	●	●	●
Rainforest	No	IV/III	V2	8.0	<3.00%	>600 lbs	Resistant	31.70%	5.00%	10.8 mm	3/16"	●	●				●	●	●	●	●	●	●
Retro	Yes	IV/III	V2	6.0-6.5	<3.00%	>450 lbs	Resistant	20%		8x8 = 7.6 mm	3/16"	●	●	●			●	●	●	●	●	●	●
Rock Island	Yes	IV/III	V2	8.0	<3.00%	>500 lbs	Resistant	19.40%	11.10%	12x24 = 10.8 mm 16x16 = 8.8 mm 13x13 = 8.2 mm	3/16"	●	●				●	●	●	●	●	●	●
Ruidoso	No	IV/III	V3	5.0	<3.00%	>550 lbs	Resistant	N/A	N/A	10.8 mm	3/16"	●	●				●	●	●	●	●	●	●
Rustica	Yes	IV/III/II	V2	8.0	<3.00%	>600 lbs	Resistant	8.93%	16.60%	24x24 = 10.5 mm 12x24 = 10.8 mm 8x8 = 7.3 mm	3/16"	●	●	●			●	●	●	●	●	●	●
San Giulio	Yes	IV	V2	7.5	<3.00%	>400 lbs	Resistant	19.40%	11.10%	12x24 = 10.8 mm 16x16 = 8.8 mm	3/16"	●	●	●			●	●	●	●	●	●	●
Spatial	Yes	130m³	V2	7.0	<0.50%	>540 lbs	Resistant	10.00%	N/A	9.6 - 9.8 mm	1/8"	●	●				●	●	●	●	●	●	●
Strata	Yes	IV/III	V2	6.0	<3.00%	>350 lbs	Resistant	19.40%	11.10%	12x24 = 10.8 mm 13x13 = 8.2 mm	3/16"	●	●				●	●	●	●	●	●	●
Sunwood Pro	No	IV	V3	7.5	<3.00%	>400 lbs	Resistant	19.20%	11.40%	10.8 mm	3/16"	●	●				●	●	●	●	●	●	●
Southerleigh	Yes	IV	V3	8.0	<3.00%	>350 lbs	Resistant	19.20%	11.40%	12x24 = 10.8 mm 16x16 = 8.8 mm 13x13 = 8.2 mm	3/16"	●	●				●	●	●	●	●	●	●
Sprint	No	N/A	V1	6.0	<0.25%	>400 lbs	Resistant			8.7 mm	1/8"	●	●	●	●	●	●	●	●	●	●	●	●
Sussex	Yes	IV/III/II	V2	7.5	<0.50%	>600 lbs	Resistant	18.00%	N/A	18x36 = 11.0 mm 12x24 = 9.5 mm	1/8"	●	●				●	●	●	●	●	●	●
Tartan	Yes	III/II/I	V3	7.0	<0.50%	>600 lbs	Resistant	31.00%		10.8 mm	1/8"	●	●	●	●	●	●	●	●	●	●	●	●
Timberwood	No	IV/III/II	V4	8.0	<3.00%	>600 lbs	Resistant	5.00%	16.00%	9.0 mm	1/8"	●	●	●	●	●	●	●	●	●	●	●	●
Trazzo	Yes	IV/III	V2	8.0	<0.50%	>480 lbs	Resistant	3.00%	N/A	24x24 = 9.5 mm 12x24 = 9.5 mm	1/8"	●	●				●	●	●	●	●	●	●
Union Square	No	IV	V2	5.0	<3.00%	>600 lbs	Resistant	19.40%	11.10%	7.4 mm	3/16"	●	●				●	●	●	●	●	●	●
Vintage Brick	No	IV	V4	6.5	<0.10%	>450 lbs	Resistant	20.00%	N/A	3x12 = 8.5 mm 8½x10 = 8.5 mm	3/16"	●	●	●	●	●	●	●	●	●	●	●	●
Vintage Cement	Yes	IV/III	V2	8.0	<0.50%	>600 lbs	Resistant	3.00%	N/A	24x24 = 10.3 mm 12x24 = 10.3 mm	1/8"	●	●	●	●	●	●	●	●	●	●	●	●
Walker	No	IV/III	V3	9.0	<0.50%	>700 lbs	Resistant	N/A	N/A	9.0 mm	1/8"	●	●	●			●	●	●	●	●	●	●
Wildwood	No	IV/III	V3	6.5	<0.50%	>650 lbs	Resistant	N/A	N/A	9.0 mm	1/8"	●	●				●	●	●	●	●	●	●
Wilshire	Yes	IV/III/II	V2	7.0	<0.50%	>475 lbs	Resistant	18.00%	N/A	24x24 = 9.5 mm 12x24 = 9.5 mm	1/8"	●	●				●	●	●	●	●	●	●
Windrose	Yes	IV/III	V2	7.0	<3.00%	>500 lbs	Resistant	18.20%	11.10%	12x24 = 10.8 mm 16x16 = 8.8 mm 13x13 = 8.2 mm	3/16"	●	●				●	●	●	●	●	●	●
Wisteria	Yes	IV/III	V2	8.0	<3.00%	>600 lbs	Resistant	8.93%	16.60%	12x24 = 10.8 mm 16x16 = 8.8 mm	3/16"	●	●	●			●	●	●	●	●	●	●

All tiles meet or exceed ASTM standards for chemical resistance (ASTM C650), crazing resistance (ASTM C424), and thermal shock (ASTM C484) unless otherwise noted.
NOTE: Due to the inherent nature of fired ceramic tile, it is important to note that the coefficient of friction may vary within and between product runs

*Minimum size and related allowances are provided in ANSI A108.02. Refer to “Grout Joint Size, Layouts, and Patterns” in the Tile Council of North America’s “Handbook for Ceramic, Glass, and Stone Tile Installation.”

WALL TILE TECHNICAL DATA

TECHNICAL DATA							TILE APPLICATIONS		#WHYTILE		
Series	 Trim Available	 Shade/Texture Spectrum (STS) Rating	 Water Absorption	 Breaking Strength	 Recycle Content	 Wall Tile Thickness	 Walls/Backsplash	 Exterior	 Easy to Clean	 Family Friendly	 Stain Proof
			Pre-Consumer								
ANSI Designation			ASTM C373		ASTM C648						
ANSI Standard			<20%	>140 lbf	± 0.3 mm						
Aquarelle	Yes	V2	<20%	>150 lbf	10%	8.15 mm	●	●	●	●	●
Brick	Yes	V1	<20%	>150 lbf	N/A	7.3-7.7 mm	●	●	●	●	●
Details	No	V1	<20%	>275 lbf	30.00%		●	●	●	●	●
Emma	Yes	V2	<20%	>150 lbf	21.44%	7.5 mm	●	●	●	●	●
Essentials	Yes	V1	<20%	>150 lbf	17%	9.1-9.3 mm	●	●	●	●	●
Impression	No	V1	<20%	>150 lbf	N/A	10.5 mm	●	●	●	●	●
Profile	No	V2	<20%	>140 lbf	18.00%	7.3 mm	●	●	●	●	●
Ripple	Yes	V1	<20%	>140 lbf	21.44%	8.6-8.9 mm	●	●	●	●	●
Seaside	Yes	V1	<20%	>140 lbf	21.44%	8.6-8.9 mm	●	●	●	●	●
Spa	Yes	V1	<20%	>150 lbf	10%	8.15 mm	●	●	●	●	●
Up & Down	Yes	V1	<20%	>150 lbf	N/A	Up= 9.9 mm Down = 7.1 mm	●	●	●	●	●
Wall Tile Collection	Yes	V1	<20%	>150 lbf	10%	7.45 mm	●	●	●	●	●



WALL TILE TRIM ILLUSTRATIONS

	STANDARD WALL TILE														
	Aquarelle	Brick	Emma	Essentials	Ripple	Seaside	Spa	Up & Down	Group 1 Wall Tile Collection Brite	Wall Tile Collection Matte	Group 2 Wall Tile Collection Brite	Wall Tile Collection Matte	Wall Tile Collection Bold Tones	Group 3 Wall Tile Collection Bold Tones	Wall Tile Collection Matte
	Field Tile Sizes														
	12" x 24"														
	10" x 20"														
	8" x 12"														
	6" x 6"														
	3"x12"														
	3" x 6"														
	4¼" x 4¼"														
4¼" x 12¾"															
4¼" x 8½"															
Surface Trim															
	2" x 6" S4269														
	2" x 2" SN4269														
	2" x 2" SM4269														
	2⅞" x 2⅞" SN4289														
	3" x 6" S4369														
	3" x 6" S4639														
	3" x 3" SN4369														
	3" x 24" Bullnose														
	4¼" x 8½" S4489														
	4¼" x 12¾" S4C49														
	4¼" x 12¾" S44C9 Bullnose														
	4¼" x 4¼" S4449														
	4¼" x 4¼" SN4449														
	6" x 6" S4669														
	6" x 6" SN4669														
	½"x12" Pencil														
Radius Trim															
	2" x 6" A4200														
	2" x 2" AN4200														
	2" x 2" AM4200														
	1" x 6" A106														
Cove Base Trim															
	4¼" x 4¼" A3401														
	4¼" x 4¼" SCL/SCR3401														
	4¼" x 6" S3419T														
	4¼" x 6" SCL/SCR3419T														
	6" x 6" A3601														
	6" x 6" SCL/SCR3601														
Counter & Decorative Trim															
	3"x6" Border Matte & Glossy														

X - Available in select colors

NATURAL STONE TECHNICAL DATA

FLOOR TILE

Product Description	Country of Origin	Shade Variation				Durability		F W S Suggested Application			Suitable for Exterior Applications	Rec. Grout Joints*	Tile Thickness
		Low	Moderate	High	Random	Commercial	Residential	Floor	Wall	Showers*			

Granite													
Absolute Black	India	●				●	●	●	●	●	●	1/8"	18x18 = 1/2" 12x12 = 3/8"
Absolute Black Flamed	India	●				●	●	●	●		●	1/8"	3/8"
Black Galaxy	India	●				●	●	●	●	●	●	1/8"	3/8"
Moon White	India		●			●	●	●	●	●	●	1/8"	3/8"
Tan Brown	India	●				●	●	●	●	●	●	1/8"	3/8"
Limestone													
Blue Lagos	Portugal		●			●	●	●	●			1/8" Suede: 3/16"	3/8"
Blue Lagos Blend	Portugal				●	●	●	●	●			1/8"	5/8"
Chihuahua	Mexico		●			●	●	●	●	●	●	1/8"	3/8"
Gascogne Blue	Portugal		●			●	●	●	●	●	●	1/8" Suede: 3/16"	3/8"
Gascogne Blue Blend	Portugal				●	●	●	●	●	●	●	1/8"	5/8"
Golden Beach	Portugal	●				●	●	●	●	●	●	1/8" Suede: 3/16"	3/8"
Golden Beach Blend	Portugal				●	●	●	●	●	●	●	1/8"	5/8"
Imun Cream	Egypt		●			●	●	●	●		●	1/8"	12x24 = 3/8" 18x18 = 1/2" 4x12 = 3/8" 6x18 = 3/8"
Mediterranean Blue	Egypt		●			●	●	●	●		●	1/8"	12x24 = 3/8" 18x18 = 1/2" 4x12 = 3/8" 6x18 = 3/8"
Thala Gray	Tunisia		●			●	●	●	●	●	●	1/8"	12x24 = 3/8" 18x18 = 1/2" 12x12 = 3/8" 4x12 = 3/8"
Tut Pond	Egypt			●		●	●	●	●	●	●	1/8"	3/8"
Marble													
African Arabescato	Namibia			●		●	●	●	●	●		1/8"	3/8"
Artemis White	Turkey		●			●	●	●	●	●		1/8"	24x24 = 1/2" 12x24 = 1/2" 18x18 = 1/2" 4x12 = 3/8"
Astoria Gray	Turkey	●				●	●	●	●	●	Tumbled & Vintage Leather	1/8" Tumbled: 3/16"	12x24 = 3/8" 4x12 = 3/8" 6x18 = 1/2"
Bardiglio Nuvolato	Italy			●		●	●	●	●	●		1/8"	3/8"
Calacatta Gold	Italy			●		●	●	●	●	●		1/8"	3/8"
Calacatta Select	Italy		●			●	●	●	●	●		1/8"	3/8"
Crema Light	Turkey	●				●	●	●	●	●		1/8"	18x36 = 1/2" 24x24 = 1/2" 18x18 = 1/2" 12x24 = 1/2" 4x12 = 1/2"
Crema Marfil Standard/Select	Spain	●				●	●	●	●	●		1/8"	24x24 = 5/8" 12x24 = 3/8" 18x18 = 5/8" 4x12 = 3/8"
Crema Marfil Classic	Spain		●			●	●	●	●	●	Tumbled & Vintage Leather	1/8" Tumbled: 3/16"	12x24 = 3/8" 18x18 = 5/8" 12x12 = 3/8" 4x12 = 3/8" 6x18 = 5/8"
Dark Emperador	Spain		●			●	●	●	●	●		1/8"	3/8"
Dolomite White	Turkey	●				●	●	●	●	●	Tumbled Only	1/8"	3/8"
Emperador Brown	Turkey			●		●	●	●	●	●	Tumbled Only	1/8"	3/8"
Empress Black	China		●			●	●	●	●	●		1/8"	12x24 = 3/8" 18x18 = 1/2" 12x12 = 3/8" 4x12 = 3/8"
Euro White	Portugal		●			●	●	●	●	●		1/8"	3/8"
Ice White	Turkey		●			●	●	●	●	●	Tumbled Only	Tumbled: 3/16"	3/8"
Iceberg	Turkey		●			●	●	●	●	●		1/8"	12x24 = 1/2" 12x12 = 3/8" 4x12 = 3/8"
Ivory Select	Turkey	●				●	●	●	●	●		1/8"	12x24 = 1/2" 18x18 = 1/2" 4x12 = 3/8"
Light Emperador Turkish	Turkey		●				●	●	●	●	Vintage Leather Only	1/8"	12x24 = 3/8" 12x12 = 3/8" 4x12 = 3/8" 6x18 = 1/2"
Madera Black	China		●			●	●	●	●	●		1/8"	3/8"

*Natural stone is generally not recommended for use in steam showers. There are many varieties of stone that will perform very well with the right installation conditions. Please contact your Interceramic Sales Representative if you have further questions.

Product Description	Country of Origin	Shade Variation				Durability		F W S Suggested Application			Suitable for Exterior Applications	Rec. Grout Joints*	Tile Thickness
		Low	Moderate	High	Random	Commercial	Residential	Floor	Wall	Showers			

Marble Cont.													
Madera White	China		●			●	●	●	●	●	Vintage Leather Only	1/8"	3/8"
Polar Gray	Turkey		●			●	●	●	●	●	Tumbled & Vintage Leather Only	1/8" Tumbled: 3/16"	24x24 = 5/8" 12x24 = 3/8" 18x18 = 1/2" 12x12 = 3/8" 4x12 = 3/8" 6x18 = 1/2"
Rain Cloud	Portugal			●		●	●	●	●	●	●	1/8"	5/8"
Shadow Gray	Turkey			●		●	●	●	●	●		1/8"	12x24 = 1/2" 18x18 = 1/2" 4x12 = 3/8"
Silver Waves	China			●		●	●	●	●	●	Vintage Leather Only	1/8"	3/8"
Snow Frost	China		●			●	●	●	●	●		1/8"	3/8"
Stargazing	Portugal			●		●	●	●	●	●	●	1/8"	5/8"
Trifecta Ice	Turkey			●		●	●	●	●	●		1/8"	3/8"
Trifecta Latte	Turkey			●		●	●	●	●	●		1/8"	3/8"
Trifecta Linen	Turkey			●		●	●	●	●	●		1/8"	3/8"
Trifecta Steel	Turkey			●		●	●	●	●	●		1/8"	3/8"
White Carrara	Italy		●			●	●	●	●	●		1/8"	3/8"
White Dawn	Portugal			●		●	●	●	●	●	●	1/8"	5/8"
White Thassos	Greece	●				●	●	●	●	●		1/8"	3/8"
Peruvian Travertine													
Andean Cream	Peru			●		●	●	●	●	●	●	1/8"	3/8"
Cusco Storm	Peru			●		●	●	●	●	●	●	1/8"	3/8"
Alpaca Fleece	Peru		●			●	●	●	●	●	●	1/8"	3/8"
Mexican Travertine													
Crema Imperial Classic	Mexico		●			●	●	●	●	●	●	1/8" Tumbled: 3/16"	3/8"
Crema Imperial Select	Mexico	●				●	●	●	●	●	●	1/8"	3/8"
Crema Venato Vein-Cut	Mexico		●			●	●	●	●	●	●	1/8"	3/8"
Travertino Caramel	Mexico		●			●	●	●	●	●	●	1/8" Tumbled: 3/16"	3/8"
Turkish Travertine													
Autumn Leaves	Turkey				●	●	●	●	●	●	●	1/8" Tumbled: 3/16"	18x18 = 1/2" Versailles Pattern = 1/2"
Classic	Turkey		●			●	●	●	●	●	●	1/8" Tumbled: 3/16"	24x24 = 1/2" 12x24 = 1/2" 18x18 = 1/2" 12x12 = 3/8" 4x12 = 3/8" Versailles Pattern = 1/2"
Desert Travonya	Turkey		●			●	●	●	●	●	●	1/8" Tumbled: 3/16"	12x24 = 1/2" 18x18 = 1/2" 12x12 = 3/8" 6x18 = 1/2" Versailles Pattern = 1/2"
La Travonya	Turkey			●		●	●	●	●	●	●	1/8" Tumbled: 3/16"	12x24 = 1/2" 18x18 = 1/2" Versailles Pattern = 1/2"
Noce Toros	Turkey		●			●	●	●	●	●	●	1/8" Tumbled: 3/16"	Versailles Pattern = 1/2"
Silver	Turkey			●		●	●	●	●	●	●	1/8" Tumbled: 3/16"	12x24 = 1/2" 18x18 = 1/2" 12x12 = 3/8" 4x12 = 3/8" 6x18 = 1/2" Versailles Pattern = 1/2"
Tuscany Ivory	Turkey		●			Tumbled & U/C/B Only	●	●	●	●	●	1/8" Tumbled: 3/16"	12x24 = 1/2" 18x18 = 1/2" 12x12 = 3/8" Versailles Pattern = 1/2"
Tuscany Walnut	Turkey		●			Tumbled & U/C/B Only	●	●	●	●	●	1/8" Tumbled: 3/16"	12x24 = 1/2" 18x18 = 1/2" Versailles Pattern = 1/2"
Natural Slate													
Autumn Mist	India				●	●	●	●	●			3/8"	3/8" - 1/2"
Indian Black	India		●			●	●	●	●	●	●	3/8"	3/8" - 1/2"
Kota Bluestone	India		●			●	●	●	●	●	●	3/8"	3/8" - 1/2"
Primrose	India				●	●	●	●	●	●	●	3/8"	3/8" - 1/2"
Rustic Gold	India			●		●	●	●	●		●	3/8"	3/8" - 1/2"

NATURAL STONE TECHNICAL DATA

FLOOR TILE

Product Description	Country of Origin	Shade Variation				Durability		F W S Suggested Application			Suitable for Exterior Applications	Rec. Grout Joints*	Tile Thickness
		Low	Moderate	High	Random	Commercial	Residential	Floor	Wall	Showers*			
Ledger Panels													
Marble Dolomite White 3D Honed	Turkey	●				●	●		●		●	None	1/2"-3/4"
Marble Ice White Hi/Lo	Turkey		●			●	●		●		●	None	1/2"-3/4"
Marble Ivory Select 3D Honed	Turkey	●				●	●		●		●	None	1/2"-3/4"
Marble Madera White 3D Honed	China		●			●	●		●		●	None	1/2"-3/4"
Marble Palissandro 3D Honed	Turkey			●		●	●		●		●	None	1/2"-3/4"
Marble Polar Gray Hi/Lo	Turkey		●			●	●		●		●	None	1/2"-3/4"
Natural Slate Alabaster Quartzite	China		●			●	●		●			None	1/2"-5/8"
Natural Slate Autumn Mist	India				●	●	●		●			None	1/2"-5/8"
Natural Slate Everest Quartzite	China			●		●	●		●			None	1/2"-5/8"
Natural Slate Harvest Quartzite	China			●		●	●		●			None	1/2"-5/8"
Natural Slate Indian Black	India		●			●	●		●		●	None	1/2"-5/8"
Natural Slate Ink Quartzite	China		●			●	●		●			None	1/2"-5/8"
Natural Slate Kota Bluestone	India		●			●	●		●		●	None	1/2"-5/8"
Natural Slate New California Gold	India				●	●	●		●		●	None	1/2"-1"
Natural Slate Petra Sand	India		●			●	●		●		●	None	1/2"-1"
Natural Slate Primrose	India				●	●	●		●			None	1/2"-5/8"
Natural Slate Rustic Blend	China				●	●	●		●		●	None	1/2"-5/8"
Natural Slate Rustic Gold	India			●		●	●		●			None	1/2"-5/8"
Natural Slate Timber Quartzite	China			●		●	●		●			None	1/2"-5/8"
Natural Slate White Quartzite	China		●			●	●		●		●	None	1/2"-3/4"
Travertine Autumn Leaves	Turkey				●	●	●		●		●	None	3/4"-1"
Travertine Autumn Leaves Brick	Turkey				●	●	●		●		●	None	3/4"-1"
Travertine Classic	Turkey		●			●	●		●		●	None	3/4"-1"
Travertine Classic Brick	Turkey		●			●	●		●		●	None	3/4"-1"
Travertine La Travonya	Turkey			●		●	●		●		●	None	3/4"-1"
Travertine La Travonya Brick	Turkey			●		●	●		●		●	None	3/4"-1"
Travertine Noce Toros	Turkey		●			●	●		●		●	None	3/4"-1"
Travertine Noce Toros Brick	Turkey		●			●	●		●		●	None	3/4"-1"
Travertine Silver	Turkey			●		●	●		●		●	None	3/4"-1"
Travertine Silver Brick	Turkey			●		●	●		●		●	None	3/4"-1"
River Rocks													
Charcoal Antique Pebbles	Indonesia		●			●	●	●	●	●	●	1/8"	3/8"
Ivory Antique Pebbles	Indonesia		●			●	●	●	●	●	●	1/8"	3/8"
Petrified Wood Antique Pebbles	Indonesia			●		●	●	●	●	●		1/8"	3/8"
Taupe Antiqe Pebbles	Indonesia		●			●	●	●	●	●	●	1/8"	3/8"
Taupe Blend Antique Pebbles	Indonesia				●	●	●	●	●	●	●	1/8"	3/8"
Contemporary Blend Sliced Pebbles	China				●	●	●	●	●	●		1/8"	5/16"
Crema Marfil Sliced Pebbles	Spain		●			●	●	●	●	●		1/8"	5/16"
Urban Blend Sliced Pebbles	China				●	●	●	●	●	●		1/8"	5/16"
White Carrara Sliced Pebbles	Italy		●			●	●	●	●	●		1/8"	5/16"
Hawksbill Gray Polygon Honed Pebbles	China				●	●	●	●	●	●		1/8"	3/8"
Hawksbill White Polygon Honed Pebbles	China				●	●	●	●	●	●		1/8"	3/8"
Lily White Polygon Honed Pebbles	China		●			●	●	●	●	●		1/8"	3/8"
Madera White Polygon Honed Pebbles	China		●			●	●	●	●	●		1/8"	3/8"
White Carrara Polygon Honed Pebbles	Italy		●			●	●	●	●	●		1/8"	3/8"
Birch Sliced Pebbles	China		●			●	●	●	●	●	●	1/8"	3/8"
Black Pearl Sliced Pebbles	China		●			●	●	●	●	●	●	1/8"	3/8"
Forest Sliced Pebbles	China				●	●	●	●	●	●	●	1/8"	3/8"
Snowball Sliced Pebbles	China		●			●	●	●	●	●	●	1/8"	3/8"
Asian Bardiglio Tumbled Pebbles	Vietnam		●			●	●	●	●	●	●	1/8"	5/16"
Asian Nero Tumbled Pebbles	Vietnam		●			●	●	●	●	●	●	1/8"	5/16"
Asian Thassos Tumbled Pebbles	Vietnam		●			●	●	●	●	●	●	1/8"	5/16"
Asian TriColor Blend Tumbled Pebbles	Vietnam				●	●	●	●	●	●	●	1/8"	5/16"

*Natural stone is generally not recommended for use in steam showers. There are many varieties of stone that will perform very well with the right installation conditions. Please contact your Inter ceramic Sales Representative if you have further questions.





interceramicusa.com

Headquarters

1950 Parker Rd.
Carrollton, TX 75010

1.800.688.5671
info@interceramic.com

