

SpraySmart™ 901

RESILIENT FLOORING SPRAY ADHESIVE



 **Tarkett**

SpraySmart™

SpraySmart 901 is a solvent-free adhesive specifically formulated for installing the following Tarkett VCT, VET, SVT, Vinyl Sheet, Rubber Tile products and Finishing Accessories::

VCT

- Tarkett VCT
- (Solids & Feature Strips)
- VCT Basketball Kit

Finishing Accessories

- Subfloor Leveler System®

VET-SVT

- Azterra™
- Color Essence™
- Color Essence SR™
- Cortina Grande™
- Cortina Grande SR™
- Karim Kolors
- Karim Shapes

Vinyl Sheet

- Acczent®
- Acczent® Flourish
- Acczent® Wood Acoustiflor®
- Aria™
- iQ™ Granit™
- iQ™ Granit™ Safe-T
- iQ™ Granit™ Micro
- Melodia™
- iQ™ Natural
- iQ™ Optima®
- iQ™ Optima® Acoustiflor®
- Standard Plus

Rubber Tile*

- Circulinity™ Collection
- Defiant™
- Inertia™
- Mesto™
- Mesto Configurations™
- MicroTone™
- Minerality™
- Prima® Marbleized & Olio®
- Triumph
- Replay® Tile & Sheet
- Organics

*Not approved for Eco-Shell™ with Cork, CorkTones™ or Metallurgy™ at this time

SpraySmart 901 uses an advanced spray adhesive technology that promotes improved productivity and indoor air quality, and provides occupational health and safety benefits. A unique water-based acrylic adhesive, SpraySmart 901 is available in easy-to-use, fully recyclable spray cans which utilize a safe, non-ozone depleting propellant.

SpraySmart 901 is an environmentally friendly, non-toxic, non-flammable intelligent adhesive option, enabling immediate occupancy; an important benefit for healthcare, education, retail and other environments where immediate foot and rolling traffic are required.

Technical Data	Standards	SpraySmart 901 Flooring Adhesive
Adhesive Type		Water-based Acrylic Blend
Appearance		Light Blue
Odor		Sweet Mild Odor
Flash Point		> 212°F
NFPA 704 Flammability Rating		0 - Non-flammable
Storage		Store Between 50°F & 120°F
Shelf Life		2 Years (If unopened)
Open Time		25-45 Minutes
Working Time		2 Hours
VOC Content		< 0.0 g/ml Calculated
Foot Traffic Permitted		Immediately After Installation
Heavy Rolling Traffic Permitted		Immediately After Installation
pH Tolerance	ASTM F710	11 pH
Substrate Moisture Tolerance	ASTM F2170 ASTM F1869	90% RH 8 lbs. per 1,000 ft.2/24 hrs.
Underfloor Heating Systems		Yes
Please visit www.tarkettna.com for the most updated specifications and installation, cleaning and maintenance instructions.		

Sustainability Facts	
To learn more, visit www.tarkettna.com .	
SpraySmart 901	LEED Credits Contribution
Construction Waste Management ReStart® Reclamation Program MR 2	1-2
Material Reuse Supports Reuse & Recycling of Flooring MR 3	1-2
Regional Materials Manufactured in Dalton, GA - an ISO 9001 Facility MR 5	1-2
People-Friendly Spaces Low-emitting Materials IEQ 4.1 Adhesives, FloorScore® Certified & Meets CA 01350	1
Return On Investment Requires fewer man hours to install.	
SpraySmart™ 901	
Immediate Traffic After Installation, Including Rolling Loads	✓
For Use Under Hospital Beds	✓
Eliminates Trowel Marks	✓
Heat Weld Immediately	✓
Increased Limits for Moisture and pH	✓
Reduces Adhesive Consumption	✓
Supports Reuse and Recycling of Flooring	✓
Cradle to Cradle - Silver Certification	✓

COVERAGE:

All flooring types listed porous & non-porous surfaces

VCT:

200 sq. ft./22 oz. can;
1,200 sq. ft./carton

VET-SVT:

160 sq. ft./22 oz. can;
960 sq. ft./carton

Vinyl Sheet:

150 sq. ft./22 oz. can;
900 sq. ft./carton

Rubber Tile:

80 sq. ft./22 oz. can;
4800 sq. ft./carton



COMPLYING WITH GREEN LEED Services



30000 Aurora Road
Solon, OH 44139
TARKETTNA.COM 800.899.8916

©2019 TARKETT USA, INC. 05/19

