

Bearing Point, Paris, France / Architect: STUDIOS Architecture Paris

HeartFelt is an innovative, patented, felt ceiling and wall system that turns every ceiling into a visual and acoustic playground.

FEATURES AND BENEFITS

- Standard Dimensions: 8' panel lengths
 - HeartFelt Linear:
 - 40HL55 (40mm x 55mm, 1-9/16" x 2-3/16")
 - 40HL80 (40mm x 80mm, 1-9/16" x 3-1/8")
 - 40HL105 (40mm x 105mm, 1-9/16" x 4-1/8")
 - HeartFelt Round:
 - 40HR64 (40mm x 64mm, 1-9/16" x 2-1/2")
- Modular system with both square and round profile design offering easy plenum access
- Compatible with industry standard lighting, HVAC, fire safety and security components in a ceiling application, as well as a simple and clean installation in a wall application
- Available with three standard carrier modules, 60mm (2-3/8"), 80mm (3-1/8"), 100mm (3-15/16"), for acoustical and aesthetic flexibility. 50mm (2"), 70mm (2-3/4"), 90mm (3-1/2"), and custom carrier modules are also available. An additional lead time will apply. Please contact your local sales representative for more information
- Red Dot Award 2017 Winner – Best of the Best

ATTRIBUTES



NRC
UP TO 0.80



CLASS A FIRE RATED
ASTM E84



SEISMIC RATING:
ZONE A, B, C, D, E, F



CUSTOMIZATION
AVAILABLE

LEED® v4


- ✓ MR: Building Product Disclosure
- ✓ EQ: Low-Emitting Materials
- ✓ EQ: Indoor Air Quality Assessment
- ✓ EQ: Acoustic Performance

LEED® is a registered trademark of the
U.S. Green Building Council.

CERTIFICATIONS



GREENGUARD
GOLD CERTIFIED



CRADLE-TO-CRADLE
BRONZE CERTIFIED



MATERIAL HEALTH:
BRONZE CERTIFIED

HeartFelt® is a registered trademark of Hunter Douglas, Inc. used with permission.



FINISHING AND CUSTOMIZATION OPTIONS

Face of Panel

HeartFelt products offer an array of grey and earth tone felt colors in a wide range of profiles, patterns and configurations.

COLORS

HeartFelt - Greys



White
7593F



Light Grey
7596F



Middle Grey
7597F



Dark Grey
7598F

HeartFelt - Earth Tones



Creme
7575F



Light Brown
7576F



Middle Brown
7577F



Dark Brown
7578F



Black
7594F



*40HL55, 40HL80, 40HL105, 40HR64
Available in HeartFelt Greys




Umber
7579F

*40HL55
Available in HeartFelt Earth Tones


STANDARD CONFIGURATION OPTIONS FOR HEARTFELT LINEAR SYSTEMS

STANDARD PROFILES AND DEPTHS




Profiles shown (left to right): 40HL55, 40HL80, 40HL105, 40HR64

OPTIONAL END CAP




End caps available for all profile options

STANDARD CARRIER OPTIONS FOR HEARTFELT LINEAR SYSTEMS



60mm (2-3/8") Spacing



80mm (3-1/8") Spacing




100mm (3-15/16") Spacing

STANDARD CONFIGURATION OPTIONS FOR HEARTFELT LEVELS SYSTEMS




WAVE



CHOPPY



STEP




SCATTER




Custom carrier modulations are available upon request. 50mm (2"), 70mm (2-3/4"), and 90mm (3-1/2") Spacings as well as Levels and custom carriers available. Please contact your local sales representative for more information.

INSTALLATION EXAMPLES

Typical Isometrics



Additional wall options available for design flexibility, contact your local sales representative to get started.





Hotel nhw RAI / Photo © Egbert de Boer

PHYSICAL DATA

MATERIAL

Non-Woven PES fibers (felt)

FIRE RATING

Class A Fire Rated per ASTM E84
Canada – per CAN/ULC S102.2-10

SEISMIC RATING

ZONES A,B,C,D,E,F

VISUAL CONSIDERATIONS

Given the unique and special nature of our HeartFelt® ceiling and wall product, steps should be taken (before and during installation, as well as over the lifetime of the ceiling) to avoid or minimize static and the accumulation of dust, lint, dirt or airborne particles on or around the felt. Manufacturer does not warrant against or take responsibility for any such static or accumulation.

LIGHT REFLECTANCE

Varies with color

WARRANTY

1-year Limited Warranty.
Full warranty information can be found at certainteed.com/warranty

ACOUSTICAL PERFORMANCE

PANEL PROFILE	PANEL SPACING (CARRIER)	OPEN AREA	REVEAL	ACOUSTICS (NRC)
HeartFelt Linear - 40HL55	60mm (2-3/8")	33%	13/16"	0.60
	80mm (3-1/8")	50%	1-9/16"	0.50
	100mm (3-15/16")	59%	2-3/8"	0.45
HeartFelt Linear - 40HL80	60mm (2-3/8")	33%	13/16"	0.75
	80mm (3-1/8")	50%	1-9/16"	0.65
	100mm (3-15/16")	59%	2-3/8"	0.55
HeartFelt Linear - 40HL105	60mm (2-3/8")	33%	13/16"	0.80
	80mm (3-1/8")	50%	1-9/16"	0.70
	100mm (3-15/16")	59%	2-3/8"	0.65
HeartFelt Round - 40HR64	60mm (2-3/8")	33%	13/16"	0.65
	80mm (3-1/8")	50%	1-9/16"	0.60
	100mm (3-15/16")	59%	2-3/8"	0.50

Acoustical tests performed in accordance with ASTM C423 in a type E400 mounting.



CertainTeed ARCHITECTURAL

METAL • WOOD • FELT • FIBERGLASS & MINERAL FIBER • GYPSUM • SUSPENSION & INTEGRATED SYSTEMS
20 Moores Road, Malvern, PA 19355 800-366-4327 certainteed.com/architectural

© 08/22 CertainTeed, Printed in the USA, Code No. 12-11-1406-US-EN

