

For versatility, creativity and economics in your ceiling, our Metalinx $^{\text{\tiny{TM}}}$ line of woven wire and expanded metals can provide adaptability with a variety of design choices.

FEATURES AND BENEFITS

- Woven Wire, Welded Wire & Expanded Metal options
- Steel and stainless steel material options
- Installs with our standard heavy duty CertainTeed 15/16" EZ Stab Classic T-grid suspension system
- Variety of sizes, applications and powder-coat finishes
- Easy plenum access
- Compatible with industry standard lighting, HVAC, speaker, fire safety, and security services

CERTIFICATIONS











COLORS AND FINISHES

A wide choice of colors and finishes as well as custom color matching are available upon request. See website for the most up to date information and to order samples. Colors are for illustration purposes only.

STANDARD PAINT COLORS




CUSTOM COLORS



WHITE FINISH OPTIONS

Powder-coat paint finish for Arctic White #1015P (Gloss 10-20), Crystalline White #1050P (Gloss 45-55), Supernova White #1085P (Gloss 80-90), Aviation White #1011P: Powder-coat paint finish offering – LRV 90 – 9% gloss finish.



BLACK FINISH OPTIONS


Powder-coat paint finish for Starless Black #5000P (Matte); Raven Black #5030P (Gloss 25-35); Sable Black #5060P (Gloss 65-75); Wet Glass Black #5095P (Gloss 90-95)






PATTERNS

Woven-Wire Mesh








W-01 Pattern 1" square opening Open area: 80%


W-02 Pattern 2" square opening Open area: 89%

Welded-Wire Mesh










W-03 Pattern 3" square opening Open area: 91%

W-04 Pattern 4" square opening Open area: 92%

W-05 Pattern 2" x 1" rectangular opening Open area: 84%

W-06 Pattern 3" x 1-1/2" rectangular opening Open area: 73%


Expanded Metal Mesh







E-02 Pattern 1/2 #16 Standard Open area: 66%



E-03 Pattern 3/16 #22 Standard Open area: 61%



^{*} includes T-grid hold down clips, 4 per panel



PHYSICAL DATA

MATERIAL

Steel

WEIGHT Varies

FIRE RATING

N/A

Material is non-combustible Melting point: 2800° SEISMIC RATING

Zones A,B,C,D,E,F

WIND LOAD

N/A

RECYCLED CONTENT

25%

LIGHT REFLECTANCE (LR) COEFFICIENT PER ASTM E1264 & ASTM E1477

- Cotton White: LR = 0.81

WARRANTY

1-year Limited Warranty. Full warranty information can be found at certainteed.com/warranty



