



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: January 31, 2023

1 Identification

- · Product identifier
- · Trade name: Mineral Board Formula 6S
- · Other means of identification:

Cashmere; Cashmere Customline; Cashmere High NRC; Cashmere Style Edge; Fine Fissured High NRC; Sereno Fine Fissured; Sky

- · Recommended use and restriction on use
- · Recommended use: Contact manufacturer/supplier
- · Restrictions on use: No relevant information available.
- Details of the supplier of the Safety Data Sheet
- Manufacturer/Supplier:

CertainTeed Ceilings
20 Moores Road
Malvern, PA 19355
800-233-8990
www.certainTeed.com/ceilings
CertainTeed-EHS@saint-gobain.com

Emergency telephone number:

ChemTel Inc. (800)255-3924 (North America) +1 (813)248-0585 (International) 1-300-954-583 (Australia) 0-800-591-6042 (Brazil) 400-120-0751 (China) 000-800-100-4086 (India) 800-099-0731 (Mexico)

2 Hazard(s) identification

· Classification of the substance or mixture

The product is not classified as hazardous according to the Globally Harmonized System (GHS).

- · Label elements
- · GHS label elements Not regulated.
- · Hazard pictograms: Not regulated.
- · Signal word: Not regulated.
- · Hazard statements: Not regulated.
- · Precautionary statements: Not regulated.
- Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components:		
65997-17-3 Fibrous glass	47.5-75%	
93763-70-3 Perlite	5-20%	
65996-61-4 Pulp (cellulose)	1-19%	
<u> </u>	(Cont'd, on page 2)	

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: January 31, 2023

Trade name: Mineral Board Formula 6S

		(Cont'd. of page 1)
	Amylodextrin	5-15%
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic	<3.75%
1317-65-3	Limestone	0.99-1%
9002-89-5	Polyvinyl alcohol	<1%
471-34-1	Calcium carbonate	<0.2%
14808-60-7	Quartz	0.011-0.11%

Additional information:

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. For the wording of the listed Hazard Statements, refer to section 16.

Non-classification as a carcinogen is based on non-inhalable form of product. IARC listings for quartz note that the substance must be respirable.

4 First-aid measures

- Description of first aid measures
- After inhalation:

Unlikely route of exposure.

Supply fresh air; consult doctor in case of complaints.

· After skin contact:

Brush off loose particles from skin.

Wash with soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

· After eye contact:

Remove contact lenses if worn, if possible.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Unlikely route of exposure.

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

- · Most important symptoms and effects, both acute and delayed: No relevant information available.
- Indication of any immediate medical attention and special treatment needed: Treat symptomatically.

5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

- · For safety reasons unsuitable extinguishing agents: None.
- · Hazardous Combustion Products: Upon decomposition, this product emits carbon monoxide, carbon dioxide and /or low molecular weight hydrocarbons.
- Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: January 31, 2023

Trade name: Mineral Board Formula 6S

(Cont'd. of page 2)

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid formation of dust.

Do not breathe dust.

- · Environmental precautions No special measures required.
- · Methods and material for containment and cleaning up

Pick up mechanically.

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- Handling
- · Precautions for safe handling:

Prevent formation of dust.

Handle with care.

- Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles:

Storage area should be dry and well-ventilated.

- Information about storage in one common storage facility: No relevant information available.
- · Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

· Control paran	· Control parameters				
· Components with limit values that require monitoring at the workplace:					
93763-70-3 Perlite					
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction				
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction				
TLV (USA)	TLV withdrawn				
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust;**respirable fraction				
LMPE (Mexico)	Long-term value: 10 mg/m³ (e), A4				
9005-25-8 Stard	9005-25-8 Starch				
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction				
REL (USA)	Long-term value: 10* 5** mg/m³				
	(Cont'd. on page 4)				

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: January 31, 2023

Trade name: Mineral Board Formula 6S

	(Cont'd. of page 3		
	*total dust **respirable fraction		
TLV (USA)	Long-term value: 10 mg/m³		
EL (Canada)	Long-term value: 10* 3** mg/m³ *total dust;**respirable fraction		
EV (Canada)	Long-term value: 10 mg/m³ total dust		
LMPE (Mexico)	Long-term value: 10 mg/m³ A4		
1317-65-3 Lime	estone		
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction		
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction		
TLV (USA)	TLV withdrawn		
471-34-1 Calciu	im carbonate		
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction		
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction		
TLV (USA)	TLV withdrawn		
14808-60-7 Qua	artz		
PEL (USA)	Long-term value: 0.05* mg/m³ *resp. dust; 30mg/m3/%SiO2+2		
REL (USA)			
TLV (USA)			
EL (Canada)	· ·		
EV (Canada)			
LMPE (Mexico)	Long-term value: 0.025* mg/m³ A2, *fracción respirable		
65997-17-3 Fib	rous glass		
PEL (USA)	15 mg/m³ TWA		
REL (USA)	3 fibers/cm³ TWA (fibers with diameter ≤ 3.5 μm & length ≥ 10 μm.) 5 mg/m³ TWA (total fibrous glass)		

- Exposure controls
- · General protective and hygienic measures: Avoid breathing dust.
- Engineering controls: Provide adequate ventilation.
- · Breathing equipment:

Not required under normal conditions of use.

A NIOSH approved dust respirator should be used for operations generating dust.

Protection of hands:

Wear gloves for the protection against mechanical hazards according to OSHA and NIOSH rules.

(Cont'd. on page 5)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: January 31, 2023

Trade name: Mineral Board Formula 6S

(Cont'd. of page 4)

- **Eye protection:** Follow relevant national guidelines concerning the use of protective eyewear.
- · Body protection: Protective work clothing
- Limitation and supervision of exposure into the environment

No relevant information available.

· Risk management measures No relevant information available.

9 Physical and chemical properties			
· Information on basic physical and chemical properties · Appearance:			
Form:	Solid		
Color:	According to product specification		
· Odor:	Not determined.		
· Odor threshold:	Not determined.		
· pH-value:	Not applicable.		
Melting point/Melting range:	Not determined.		
· Boiling point/Boiling range:	Not determined.		
· Flash point:	Not applicable.		
· Flammability (solid, gaseous):	Product is not flammable.		
· Auto-ignition temperature:	Not determined.		
· Decomposition temperature:	Not determined.		
· Danger of explosion:	Product does not present an explosion hazard.		
· Explosion limits			
Lower:	Not determined.		
Upper:	Not determined.		
· Oxidizing properties:	Non-oxidizing.		
· Vapor pressure:	Not applicable.		
· Density:			
Relative density:	2-2.5		
Vapor density:	Not applicable.		
Evaporation rate:	Not applicable.		
· Solubility in / Miscibility with			
Water:	Negligible		
· Partition coefficient (n-octanol/water): Not determined.			
· Viscosity			
Dynamic:	Not applicable.		
Kinematic:	Not applicable.		
· Other information	No relevant information available.		

10 Stability and reactivity

(Cont'd. on page 6)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: January 31, 2023

Trade name: Mineral Board Formula 6S

(Cont'd. of page 5)

- Reactivity: The product is non-reactive under normal conditions of use, storage and transport.
- · Chemical stability: Stable under normal temperatures and pressures.
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

· Possibility of hazardous reactions

Reacts with strong acids and alkali.

Reacts with strong oxidizing agents.

- · Conditions to avoid Prevent formation of dust.
- · Incompatible materials Oxidizers, strong bases, strong acids
- Hazardous decomposition products

Under fire conditions only:

Carbon monoxide and carbon dioxide

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity: Based on available data, the classification criteria are not met.
- LD/LC50 values that are relevant for classification: None.
- · Primary irritant effect:
- · On the skin: Based on available data, the classification criteria are not met.
- · On the eye: Based on available data, the classification criteria are not met.
- · Sensitization: Based on available data, the classification criteria are not met.
- · IARC (International Agency for Research on Cancer):

Reference to chemical component(s) listed below are based on unbound respirable particles and are not generally applicable to product as supplied.

14808-60-7 Quartz 1

NTP (National Toxicology Program):

14808-60-7 Quartz

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Eve contact.

Skin contact.

Repeated dose toxicity:

Long-term inhalation of silica dusts may cause obstructive pulmonary disease including silicosis.

- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity:

Contains known or suspect carcinogens when inhaled. Product is in non-inhalable form and is nonclassifiable as a carcinogen.

- Reproductive toxicity: Based on available data, the classification criteria are not met.
- STOT-single exposure: Based on available data, the classification criteria are not met.
- · STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

(Cont'd. on page 7)

Page: 7/9

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: January 31, 2023

Trade name: Mineral Board Formula 6S

(Cont'd. of page 6)

- · Toxicity
- · Aquatic toxicity No relevant information available.
- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- Mobility in soil: No relevant information available.
- · Other adverse effects No relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Smaller quantities can be disposed of with household waste.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- Uncleaned packagings
- · **Recommendation:** Disposal must be made according to official regulations.

14 Transport information		
· UN-Number · DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
· UN proper shipping name · DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
Transport hazard class(es)		
· DOT, ADR/RID/ADN, IMDG, IATA · Class	Not regulated.	
· Packing group · DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
· Environmental hazards · Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.		

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)

(Cont'd. on page 8)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: January 31, 2023

Trade name: Mineral Board Formula 6S

(Cont'd. of page 7)

·SARA

· Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act)

All ingredients are listed or exempt.

- · Proposition 65 (California)
- · Chemicals known to cause cancer:

Reference to Crystalline Silica and/or Quartz is based on unbound respirable particles and is not generally applicable to product as supplied.

14808-60-7 Quartz

· Chemicals known to cause developmental toxicity for females:

None of the ingredients are listed.

Chemicals known to cause developmental toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· EPA (Environmental Protection Agency):

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):

Reference to chemical component(s) listed below are based on unbound respirable particles and are not generally applicable to product as supplied.

14808-60-7 Quartz

|1

· Canadian Domestic Substances List (DSL):

All ingredients are listed or exempt.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

OSHA: Occupational Safety & Health Administration

Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/

(Cont'd. on page 9)

Page: 9/9

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: January 31, 2023

Trade name: Mineral Board Formula 6S

(Cont'd. of page 8)

overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org) Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by: ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com Revision- SGNA PS&C January 31, 2023