



Legato™ Collection

Mannington®
COMMERCIAL




Cover: Legato- W416, BL324, IdealBase - 244 Bluish White
Above: Legato - B413






Crafted to Coordinate



1. Legato, GR342
2. Cirro, Wood, Parisian Pine
3. Legato, G326
4. Legato, BL322
5. Cirro, Abstract, Linear Graphite
6. Teles, Dew Drop
7. Teles, Stalagmite



1. Legato, P304
2. Legato, T337
3. Teles, Ivory Coast
4. Cirro, Wood, Salted Oak
5. Cirro, Wood, Chalked Pine
6. Legato, BL324
7. Cirro, Stone, Exposed Concrete
8. Teles, Monterey Bluff



Available in a myriad of 54 colors, Legato boasts the benefits of Quantum Guard Elite®, including the promise of enhanced stain and scratch resistance. Unlike traditional linoleum, Legato Liquid Linoleum is poured in place seamlessly, harnessing both the benefits of traditional linoleum and sheet vinyl.

Many Segments, One Product


Mannington Commercial's Legato Liquid Linoleum can be installed across many segments that require the benefits of infection control, slip resistance, and sound dampening – traits that go above and beyond that of a traditional linoleum thanks to its seamless installation and Quantum Guard Elite® technology. These segments include healthcare, government, education, retail and assisted living applications.

Safe, Hygienic and Stain Resistant

Since Legato is a poured linoleum product, it eliminates the need for most transitions and can self-heal small scratches. This creates a hygienic floor, eliminating opportunities for bacteria growth and dirt collection at transitions, perfect for demanding medical environments. Legato also self-levels, creating a safer, easy to clean flooring solution for foot and rolling traffic. Leveraging the power of Quantum Guard Elite® technology, Legato leads the industry in its ability to resist scratching and staining.

Seamless Installation

Legato Liquid Linoleum is applied seamlessly on-site over the existing moisture treated subfloor with minimal preparation and no adhesives required. Setting overnight, with proper installation techniques, Legato self-levels for a smooth, natural looking matte finish floor with no joints or welding needed – an elegant installation for a beautiful floor.



Manufactured with Natural Ingredients


A progressive and sustainable flooring option that is certified by the USDA BioProcessed® Program, Legato is VOC free, and contains no plasticizers, PVC, formaldehyde, chlorine, or heavy metals. Legato is comprised of natural ingredients, including:

- vegetable oil
- cork
- limestone
- natural color pigments


Legato does not require adhesives so there are no additional ingredients outside of the composition of the Legato system itself.

54 Colors, Countless Design Options

Legato's 54 colors have five visible cork levels ranging from natural cork to a minimal trace.




Natural Cork	Medium	Low	Minimal
N339	BL322	B313	B312
	BR335	B413	BL327
High	GR417	B414	BR415
B343	O309	BL318	GR342
BL325	P305	BL324	GR344
BR333	P307	BL328	GR345
BR334	R310	BL329	GR346
G319	T336	BL331	GR347
N340	W302	G320	GR422
P304		G323	P303
P308		G326	W300
R311		GR330	W416
T337		GR348	Y315
T421		GR349	
		GR350	
		GR419	
		GR420	
		R306	
		W301	
		Y314	




Legato Liquid Linoleum




G320



G323



G326




GR330




GR342




GR344




GR345



GR346




GR347



GR348



GR349



GR350



GR417



GR419



GR420




GR422




N339




N340




O309




P303




P304



P305




P307




P308




R306




R310




R311



T336



T337



T421



W300




W301




W302



W416



Y314



Y315




QUANTUM GUARD®
elite

Success Is in the Science

Legato features Quantum Guard Elite® providing a complete performance package for this seamless resilient flooring solution.


- Self leveling, achieved through our installation process, helps to produce a smooth and natural looking floor delivering an easy to clean surface
- Superior stain resistance outperforms competing products
- Seamless installations eliminating transitions and the related hygienic concerns that come with those transitions
- Self-healing properties where small scratches disappear without scratch whitening

Seamless Installations



Transitions provide opportunity for the growth of bacteria. Legato eliminates the need for most transitions. At the same time, this eliminates barriers within the space and provides for safer and simpler foot and rolling traffic.

Self-Healing Surface Properties



The liquid properties of the flooring and wear layer allow it to self-heal during and after installation. This property will actually repair small scratches that occur at the surface of the product. If deeper scratches or other damage occurs, the product can be repaired seamlessly at the site of the damage.

A Sustainable Flooring Solution

Legato Liquid Linoleum with Quantum Guard Elite® will perform in high traffic spaces while meeting the top industry standards for sustainability. Top accolades include:

- Declare Red List Free
- EPD
- HPD
- FloorScore® Certified
- USDA BioPreferred® Program Certified

Legato is also VOC free, and contains no plasticizers, PVC, formaldehyde, chlorine or heavy metals.

Warranted to Work

Products with Quantum Guard Elite feature our Limited Quantum Guard Elite® Wear Warranty and Limited Commercial Warranty.

Legato™ Collection

Construction	Liquid Linoleum Homogeneous Poured in Place		
Classification	ASTM F2034**		
Total Thickness	0.085" (2.2 mm)		
Wear Layer Thickness	0.085" (2.2 mm)		
Wear Layer	Quantum Guard Elite®		
Size	Continuous		
Colors	54		
Packaging	Standard Kit	Quantum Guard Elite®	Repair Kit
Coverage	73 ft² (6.782 m²)	350 ft² (32.52 m²)	5 ft² (0.4645 m²)
Weight			
Component A	24.2 lbs (10.98 kg)	9.48 lbs (4.30 kg)	1.62 lbs (0.7348 kg)
Component B	8.8 lbs (3.992 kg)	1.54 lbs (0.70 kg)	0.58 lbs (0.2631 kg)
Color Paste	1lb (0.4536 kg)	N/A	<0.1 lb (0.05 kg)
Primer - Required	Porous & Non-Porous Substrates:		
Coverage per Gallon	347 ft² (32.24 m²)		
Weight	22 lbs (9.979 kg)		
Adhesive	No adhesive required		
Installation	Installation must be performed by certified installers trained to install the Legato product		
Testing			
Composition, % (ASTM F2034)	Passes - Min 30%		
Total Thickness, mils (ASTM F386)	Nom 85 mils (2.2 mm)**		
Wear Layer Thickness, mils (ASTM F410)	Nom 85 mils (2.2 mm)		
HUD/FHA	Meets or exceeds		
ADAG (American Disability Act Guidelines)	Passes		
Flexibility (ASTM F137)	Passes - 1" Mandrel - No Crack/Break		
Static Load (ASTM F970)	Passes - Residual Indent ≤ 0.005"		
Static Load (ASTM F970 mod.)	Passes - 2,000 PSI; Residual Indent ≤ 0.005"		
Rolling Resistance/Caster Chair (ISO 4918)	25,000 Cycles, No Significant Change		
Short Term Residual Indentation (ASTM F970 / F2034)	Passes - Must Be ≤ 0.005"		
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm²		
Smoke Density (ASTM E662)	Passes - ≤ 450		
SCOF (UL410)	Passes - ≥ 0.5		
Acoustic IIC (ASTM E492)	50 - 6" Concrete with Drop Ceiling		
Acoustic STC (ASTM E90)	61 - 6" Concrete with Drop Ceiling		
Resistance to Light (ASTM F1515)	Passes - < 8 Delta E Color Change		
Chemical Resistance (ASTM F925)	Passes - No More Than Slight Change		
Resistance to Heat (ASTM F1514)	Passes - < 8 Delta E Color Change		
Environmental Data			
Indoor Air Quality	FloorScore Certified; CDPH v1.1-2010		
Product Declarations	EPD, HPD, Declare Red List Free		
Carbon Offsets	Carbon Offset 105% (Cradle to Gate (A1-A3); 2.33kg CO2e/yd²)		
USDA BioPreferred® Program	Certified		
LEED Scoreboard	May contribute to LEED Credits LEED 2009: IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials		
Manufacturing	Visit mM Origin website, mindfulmaterials.origin.build, for current transparency information		
mindful Materials	Netherlands		
Warranty			
	Limited 10-Year Commercial Warranty		
	Limited 10-Year Quantum Guard Elite® Wear Warranty		

** Meets the composition and durability requirements of ASTM F2034 but as a poured in place homogeneous linoleum product