
## PRODUCT SPECIFICATIONS

Elkay ezH2O® Liv Pro™ In-Wall Commercial Filtered Water Dispenser Non-refrigerated. Features shall include Ambient Water, Automatic Filter Status Reset, Filtered, Green Ticker™, Hands Free, Laminar Flow, Visual Filter Monitor. Electronic Bottle Filler Sensor activation. Product shall be Wall Mount (Inwall Frame/Plate), for Indoor applications, serving 1 station(s). Unit shall be certified to UL 399 and CAN/CSA C22.2 No. 120.

Special Features:	Ambient Water, Automatic Filter Status Reset, Filtered, Green Ticker™, Hands Free, Laminar Flow, Visual Filter Monitor	
Finish:	Aspen White (WH), Midnight (BK)	
Power:	115V/60Hz	
Activation by:	Electronic Bottle Filler Sensor	
Mounting Type:	Wall Mount (Inwall Frame/Plate)	
Chilling Capacity:	Non-refrigerated	
Rated Watts:	25	
Dimensions (L x W x H):	5-1/8" x 18" x 28"	
Approx. Shipping Weight:	41 lbs.	
Installation Location:	Indoor	
No. of Stations Served:	1	

Special Note: For remote chiller installations, install filter near chiller. If chiller is not installed, install filter remotely or with included filter box.

- Visual Filter Monitor: LED Filter Status Indicator for when filter change is necessary.
- Filter is certified to NSF 42 and 53 for lead, cyst, particulate, chlorine, taste and odor reduction. 3,000 gal. capacity.
- Green Ticker: Informs user of number of 20 oz. plastic water bottles saved from waste.
- Laminar flow provides clean fill with minimal splash.









Included with Product:

Water Dispenser, SS Filter Box, Remote Filter Cable, 3000 Gal Filter

### Ships in one box.

A Century of Tradition and Quality.
For more than 100 years, Elkay has been making innovative products and providing exceptional customer care. We take pride in offering plumbing products that make life easier, inspire change and leave the world a better place.



## PRODUCT COMPLIANCE

ADA & ICC A117.1 CAN/CSA C22.2 No. 120 NSF/ANSI 42, 53, 61 (Q≤1), & 372 (lead free) UL 399







Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards. Installation may require additional components and/or construction features to be fully compliant. Consult the local Authority Having Jurisdiction if necessary.

Installation Instructions (PDF) - 1000005449
Installation Instructions (PDF) - ezH2O Liv Installation Checklist

Electrical components and water system are warranted for 12 months from date of installation. Warranty pertains to drinking water applications only. Non-drinking water applications are not covered under warranty.

Warranty (PDF)

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.



## Elkay ezH2O Liv Pro In-Wall Commercial Filtered Water Dispenser Non-refrigerated

Model LBWDC00

Optional Accessories		
<u>AP99</u>	Elkay Access Panel 9" x 9" x 6"  Spec Sheet (PDF)	NI SER
<u>51300C</u>	Elkay WaterSentry Replacement Filter (Bottle Fillers & Liv Pro)  Spec Sheet (PDF)	NO IMAGE AVAILABLE
ER51Y	Elkay Remote Chiller Non-Filtered Refrigerated 5 GPH  Spec Sheet (PDF)	
ER101Y	Elkay Remote Chiller Non-Filtered Refrigerated 10 GPH  Spec Sheet (PDF)	

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.



# IMPORTANT! INSTALLER PLEASE NOTE:


This water cooler has been designed and built to provide water to the user which has not been altered by materials in the cooler waterways. The grounding of electrical equipment such as telephone, computer, etc. to water lines is a common procedure. The grounding may be in the building but may also occur away from the building. This grounding can cause electrical feedback into a water cooler creating an electrolysis which creates a metallic taste or causes an increase in the metal content of the water. This condition is avoidable by installing the cooler using the proper materials as shown below.

#### NOTICE


This built in water dispenser must be connected to the water supply using a dielectric coupling. The filter is furnished with a non-metallic ball valve which meets this requirement. The drain trap which is provided by the installer should also be plastic to completely isolate the cooler from the building plumbing system.

These products are designed to operate on 40 psi to 105 psi supply line pressure.

## OPERATION OF QUICK CONNECT FITTINGS



Pushing tube in before pulling it out helps to release tube



## LEGEND:

- A = Recommended location for waste outlet (optional), 1-1/4" (32mm) trap not furnished.
- B = Recommended location for 3/8" (10mm) water inlet, to connect with 3/8" (10mm) shut off valve in filter box.
- C = Recommended location for electrical supply. It is recommended that the supply be on dedicated 15a Hospital Grade GFCI breaker.

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.