Stargaze®



72" x 36-1/4" freestanding Heated BubbleMassage™ air bath with Bask® heated surface and straight shroud **K-1958-GHW**

Features

- Bask® heated surface creates spa-like relaxation with soothing warmth on your back, shoulders, and neck
- Three heat settings allow you to customize the surface temperature
- 118 to 122 airjets release thousands of heated bubbles that surround and support the body in a warm massage
- Automatic and manual purge cycles remove residual water from air channels after use
- Variable-speed blower lets you adjust massage intensity to 18 levels
- Freestanding design creates a striking focal point in your bathing area
- 16" (406 mm) depth offers a deep soaking experience
- Integral lumbar support on both ends
- Textured bottom surface
- Wide ledge on one side is ideal for deck-mount faucet and/or ASTM E162 handshower

 ASTM E662
- Straight shroud
- Built-in 600W BubbleMassage™ heater warms humidified air before it enters the bath
- Automatic and manual purge cycles remove residual water from air channels after use
- Built-in 60W electric heater included to keep bath surface warm

Material

Acrylic

Technology

- Auto-shutoff timer on blower allows users to enjoy Heated BubbleMassage™ experience for 60 minutes before turning off
- User interface: two separate electronic keypad controls for Heated BubbleMassage™ and Bask®

Installation

- Center drain
- Freestanding
- PureFlo drains are not recommended for a deck-mount faucet installation
- Remote blower motor installation required (relocation kit is included)

Recommended Products/Accessories

K-7265 Brass toe tap bath drain K-23726 Drain treatment K-23732 Tub & shower cleaner



Codes/Standards

ASME A112.19.7/CSA B45.10 CSA B45.5/IAPMO Z124 ASTM E162 ASTM E662 UL 1795 CSA C22.2 No. 218.2 IAPMO Certification cUL Listed UL Listed

KOHLER® Plastic Baths and Shower Bases Lifetime Limited WarrantyKOHLER® Hydrotherapy Components Five-Year Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color Code Description

0 White



Stargaze®

1/2" (13 mm)



72" x 36-1/4" freestanding Heated BubbleMassage™ air bath with Bask® heated surface and straight shroud K-1958-GHW

No change in measurements if connected with drain illustrated. (K-37386) 9-5/16" Recommended Faucet Location (102 mm) (102 mm) (237 mm) 36" (914 mm) (76 mm) 19-1/4" Recommended Faucet Hole Location (489 mm) 4-1/4" (108 mm)_ 72" (1829 mm) Lumbar 3-3/4" 35-7/8" (911 mm) (95 mm) Angle 21° 17-3/8" 25"

1-1/2" Bath Drain

Required Electrical Service

Two dedicated circuits required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI). Outside North America, this device may be known as a Residual Current Device (RCD).

66-7/8" (1699 mm)

Blower, Heated 120 V, 15 A, 60 Hz

Surface:

(635 mm)

3-1/2"

(89 mm)

Heater: 120 V, 15 A, 60 Hz

Technical Information

All product dimensions are nominal.

Drain location: Center

Basin area, bottom: 50-3/4" x 24-7/8" (1289 mm x 632 mm)

67-9/16" x 29-3/16" (1717 mm x Basin area, top:

741 mm)

Weight: 91 lbs (41.3 kg)

Minimum floor load: 45 lbs/ft² (219.7 kg/m²) Water depth: 15-11/16" (399 mm) Water capacity: 90 gal (340.7 L)

Template: Footprint, 1245664, not required, not

included

<u>Flectrical component</u> <u>Blower: 120 V 10 A 60 Hz</u> 1-800-4KOHLER (1-800-456-4537)

Notes

(441 mm)

15-15/16"

(405 mm)

Measure your actual product for rough-in details.

Install this product according to the installation instructions.

29-7/16" (748 mm)

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

This bath is designed for freestanding installation only.

If installing a rim-mount faucet, make sure there is no interference above or below the deck before drilling any holes.



Kohler Co. reserves the right to make revisions without notice to product specifications. For the most current Specification Sheet, go to www.kohler.com. 12-26-2023 21:48 - US/CA