DORN BRACHT

# TARA Wall-mounted valve cold water without pop-up waste - Brushed Chrome



30 010 892



- 140mm projection
- fixed spout
- circular, air-enriched flow
- adapter with male thread 3/4"
- hole diameter 32 mm
- rosette Ø 55 mm
- max. flow 5.7 l/min
- lead-free
- This product can help a building to meet requirements of Green Building Rating Systems, e.g. LEED®, BREEAM®, DGNB

| | |
|---|---|
| Brushed Chrome | 30 010 892-93 |
| Chrome | 30 010 892-00 |
| Brushed Platinum | 30 010 892-06 |
| Platinum | 30 010 892-08 |
| Dark Chrome | 30 010 892-19 |
| Brushed Durabrass (23kt Gold) | 30 010 892-28 |
| Matte Black | 30 010 892-33 |
| Brushed Champagne (22kt Gold) | 30 010 892-46 |
| Champagne (22kt Gold) | 30 010 892-47 |
| Brushed Dark Platinum | 30 010 892-99 |

We reserve the right to change designs, product range and technical specifications without prior notice.
More information can be found at: www.dornbracht.com +49 (0) 2371 8899 900 mail@dornbracht.com


DORN BRACHT

# TARA Wall-mounted valve cold water without pop-up waste - Brushed Chrome


TARA

30 010 892

mm [inches]




## Flow rate chart




## Certificates

LGA_18902.

DORN BRACHT

# TARA Wall-mounted valve cold water without pop-up waste - Brushed Chrome



30 010 892

