



Rubber floor coverings and accessories 2023

nora[®]
by Interface[®]



CONTENTS

Interface + nora ➡	4
Why nora rubber? ➡	5–7
Flooring Selector ➡	8–9
norament flooring ➡	10–25
noraplan flooring ➡	26–42
nora special floorings ➡	43–54
nora QuickShip program ➡	55–60
nora stairwell solutions ➡	61–70
norament stairtreads	63–67
nora stair accessories	68–70
nora installation & care ➡	71–84
nora nTx	72–76
nora nTx installation materials	77–78
nora adhesives	79–80
nora accessories	81–82
nora pro clean system	83
nora pro steamer	84
nora services ➡	85–88
Room Designer	87
Building Information Modeling (BIM)	88
Warranty ➡	89–92
nora Limited Warranty - Americas	89–90
nora nTx Warranty	91
nora pro steamer Warranty	92
Technical Data ➡	93–96

Your single source provider

Interface Inc. is a global flooring solutions company based in Atlanta, USA. It specializes in CO2-neutral modular carpet tiles and resilient flooring, including luxury vinyl tile (LVT) and, since 2018, nora rubber flooring.

Together, Interface and nora by Interface offer an unrivaled capacity to cover every single area of your building – from a single source. The coherent blend of design and functionality works for any interior, from the classroom to the conference room, to retail spaces and public areas, all the way through stairwells to laboratories and operating rooms. Whatever the space, whatever the requirement, you'll find the perfect solution.

Interface and nora can help you to create beautiful, functional interiors that have a positive impact on people's lives and the planet.



A recipe for quality

nora floor coverings are made of high-quality natural and industrial rubber combined with naturally sourced minerals and environmentally compatible color pigments. They don't contain phthalate plasticizers and, once pressed and vulcanized under heat and high pressure, they are dimensionally stable. Their dense, non-porous surface ensures that they maintain their unrivaled functionality and visual appearance for decades.



Durable Surface
Withstand extreme stress from heavy rolling loads and wheeled traffic.



Superior Slip Resistance
Help to create safer spaces.



Ergonomic Design
Add comfort underfoot, reducing foot and leg pain.



Reduced Maintenance
Little more than water needed - no finishes, coatings or harsh chemicals necessary.



Quiet Acoustical Performance
Attenuate noise pollution.



Supports Infection Control
Disinfect completely due to a dense, non-porous surface.




© Elmar Witt



© nora



© Sebastian Singer




© Elmar Witt

Carbon Neutral Enterprise


Interface® is a third-party certified Carbon Neutral Enterprise, meaning we neutralized our carbon impact across our entire business, including all operations and our full value chain. This significant milestone establishes Interface as the first and only carbon neutral flooring manufacturer across all scopes of business.

Our journey to eliminate our environmental impact and ultimately become a restorative business began with the prompting of our leader, Ray C. Anderson in 1994. The Carbon Neutral Enterprise certification builds on our history as a purpose-driven flooring company and sets the stage for our future, guiding everything we do.


Additional Certifications & transparency documentation




Carbon Neutral Floors™
Like all of the flooring products we sell, nora rubber floor coverings are third party verified carbon neutral throughout their entire life cycle as part of Interface's Carbon Neutral Floors program. Learn more at interface.com/carbonneutral.




Cradle to Cradle Certified® Silver
An industry recognized proof point of nora's commitment to producing floor coverings that are safe, circular and responsibly made. Applies to nora 926 and 913 compound floor coverings and stair treads.




GREENGUARD Gold
All nora floor coverings and adhesives are certified for low VOC emissions.



GREENHEALTH
All nora 926 and 913 compound floor coverings and stair treads carry the Greenhealth Approved seal, meeting sustainability criteria established by Health Care Without Harm and Practice Greenhealth.



Health Product Declarations (HPDs)
LEED v4 compliant Material Ingredient Reporting for all nora 926 and 913 compound floor coverings and stair treads, and ESD floor coverings.



Environmental Product Declarations (EPDs)
Product-specific, type III, 3rd party verified disclosure of the flooring's carbon footprint and other potential environmental impacts. Applies to nora 926 and 913 compound floor coverings and stair treads, and ESD and acoustic floor coverings.



© Elmar Witt

Innovative floor coverings made in Germany

At nora, we aim to help our customers achieve their goals – whether that is seeing a creative vision come to life or finding the perfect solution to withstand high performance demands.

Our norament® and noraplan® product lines, together with our special floorings, offer a balance of design and functionality to answer your creative ideas and performance needs.



Science World Vancouver, BC, Canada

norament®
Our classic rubber floor covering with outstanding quality and ultra-functionality. Thanks to its highly dense surface, it withstands even the highest loads, for example in the industrial sector.

Including various designs from classic chip compositions and round pastilles to innovative marbled and stone looks.



noraplan®
Outstanding technical and functional properties make noraplan roll and tile floor coverings suitable for a diverse set of demands and environments, from elementary schools to hospitals.

Consisting of granular to linear designs in a wide array of colors.



Adler Mannheim, SAP Arena, Mannheim, Germany
© Elmar Witt

Special Floorings
These highly specialized solutions are designed for special technical standards and requirements, including highly fire-retardant, acoustic and electrostatically dissipative floor coverings as well as constructions for ice rinks, golf facilities, laboratories and more.

Learn how to create better spaces with nora floor coverings and system solutions.

Choose the flooring solutions to meet your needs.

	norament® tiles							
	825 round, hammered	arago, castello, kivo, pado	grano, satura	grano ed	xp	xp trac	920	992, 992 grano
HEALTHCARE								
Cafeteria/Visitor Area/Staff Area	—	√	√	—	√	—	—	—
Corridors (excluding first floor)	—	√	√	—	√	—	—	—
Dialysis	—	√ 3	√	—	√	—	—	—
Emergency Departments (excluding trauma)	—	√	√	—	√	—	—	—
Entrance Areas/Lobbies	√	√	√	—	√	—	—	—
Exam Rooms	—	√	√	—	√	—	—	—
Main Floor Corridors	—	√	√	—	√	—	—	—
Imaging Suites/MRI/Radiology	√ 1	√	√	√ ■	√	—	—	—
ICU/ PICU	—	√ 3	√	—	√	—	—	—
Laboratories/Pharmacy	—	√	√	√ ■	√	—	—	—
LDR	—	√	√	—	√	—	—	—
NICU/Neonatal	—	√ 3	√	—	√	—	—	—
Nurses Stations	—	√ 3	√	—	√	—	—	—
Office Areas	—	√	√	—	—	—	—	—
Patient Rooms	—	√	√	—	√	—	—	—
Physical Therapy/Rehabilitation/Gyms	√ 1	√	√	—	√	—	—	√
Ramps (public/not for areas with standing water)	√	√	√	√	√	√	√	√
Service Areas, Corridors, and Elevators	√	√ 3	√	—	√	√	√	√
Stairwells	√ 2	√	√	—	—	—	√	—
Sterile Care Corridors/Sterile Processing	—	—	√	—	√	√	—	—
Surgical Suites (ORs, PACUs)/Cath Labs	—	—	√	√ ■	√	—	—	—
Waiting Areas	—	√	√	—	√	—	—	—

The Recommended Application Chart* is based on industry best-practices and intended to be used in conjunction with local building codes/requirements and FGI guidelines. This chart is a working document and will be updated periodically. Specialized site conditions or goals can affect recommendations. Please contact your Healthcare Account Director with questions or additional information.								
	825 round/hammered	arago, castello, kivo, pado	grano, satura	grano ed	xp	xp trac	920	992, 992 grano

EDUCATION								
Cafeterias/Auditoriums	—	√	√	—	√	—	—	—
Classrooms	—	√	√	—	√	—	—	—
Computer Rooms	—	√	√	√ ■	√	—	—	—
Corridors	—	√	√	—	√	—	—	—
Entrance Areas	—	√	√	—	√	—	—	—
Gyms/Multipurpose	—	√ 3	√	—	√	—	—	√
Laboratories	—	—	√	√ ■	√	—	—	—
Library/Music/Assembly Halls	—	√	√	—	—	—	—	—
Ramps (public/not for areas with standing water)	√	√	√	√	√	√	√	√
Shops	—	—	√	—	√	—	—	—
Staff Areas	—	√	√	—	—	—	—	—
Stairwells	√ 2	√	√	—	—	—	√	—
Student Housing	—	√	√	—	—	—	—	—

Updated: November 2023

KEY

√ = Yes (recommended)

— = No (not recommended)

1 = Hammered surface is recommended

2 = Possible color variation when pairing norament 825 round/hammered tiles with norament round/hammered stairtreads

3 = Two-tone surface is recommended

4 = Striated profile surface is recommended

■ = Use conductive adhesive and copper tape with ed products

*Not inclusive of all potential space applications

noraplan® tiles/sheet/plank				
convia, dariva, environcare, sentica (2.0 mm)	dariva, environcare, sentica (3.0 mm)	environcare acoustic, sentica acoustic	environcare ed, sentica ed	unita (2.0 mm) valua (2.0 mm/ 3.0 mm)
√	√	—	—	√
√	√	—	—	√
√	√	—	—	√
√	√	—	—	√ 4
—	√	—	—	√
√	√	—	—	√
√	√	—	—	√
√	√	—	√ ■	√
√	√	√	—	√
√	√	√	√ ■	—
√	√	—	—	√ 4
√	√	√	—	√
√	√	—	—	√
√	√	—	—	√
√	√	—	—	√
√	√	√	√	√
—	—	—	—	—
—	—	—	—	—
—	√	—	—	—
—	√	—	√ ■	—
√	√	—	—	√
convia, dariva, environcare, sentica (2.0 mm)	dariva, environcare, sentica (3.0 mm)	environcare acoustic, sentica acoustic	environcare ed/ sentica ed	unita (2.0 mm) valua (2.0 mm/ 3.0 mm)
√	√	—	—	√
√	√	—	—	√
√	√	—	√ ■	√
√	√	—	—	√
√	√	—	—	—
√	√	—	√ ■	—
√	√	—	—	√
√	√	√	√	√
√	√	—	—	—
√	√	—	—	√
—	—	—	—	—
√	√	—	—	√

Choose the flooring solutions to meet your needs.

The Recommended Application Chart* is based on industry best-practices and intended to be used in conjunction with local building codes/requirements and FGI guidelines. This chart is a working document and will be updated periodically. Specialized site conditions or goals can affect recommendations. Please contact your Healthcare Account Director with questions or additional information.

INDUSTRY/ LIFE SCIENCES

norament® tiles								
	825 round, hammered	arago, castello, kivo, pado	grano, satura	grano ed	xp	xp trac	920	992, 992 grano
Assembly	—	—	✓	✓ ■	✓	✓	—	—
Atrium	—	✓	✓	—	✓	—	—	—
Cafeteria	✓	✓	✓	—	✓	—	—	—
cGMP Production Areas (including production stairwells)	—	—	—	✓ ■	✓	✓	—	—
Cleanroom	—	—	✓	✓ ■	✓	✓	—	—
Corridors	✓	✓	✓	✓ ■	✓	—	—	—
Dressing/ Locker Rooms	✓	✓	✓	—	✓	✓	—	—
Entrance Areas	—	✓	✓	—	✓	—	—	—
ESD Areas	—	—	—	✓ ■	—	—	—	—
Laboratories/Research	—	✓	✓	✓ ■	✓	—	—	✓ ◇
Machine Shop (oil)	—	—	✓	✓ ■	—	—	✓	—
Manufacturing	✓	—	✓	✓ ■	✓	✓	✓	—
Office Areas/Conference Rooms	—	✓	✓	—	—	—	—	—
Processing Areas	—	—	✓	✓ ■	✓	✓	—	—
Stairwells (excluding production stairwells)	✓ 2	✓	✓	—	—	—	✓	—
Warehouse (forklift)	—	—	✓ †	✓	✓ †	—	✓	✓

Updated: November 2023

KEY

- ✓ = Yes (recommended)
- = No (not recommended)
- 1 = Hammered surface is recommended
- 2 = Possible color variation when pairing norament 825 round/hammered tiles with norament round/hammered stairtreads
- 3 = Two-tone surface is recommended
- 4 = Striated profile surface is recommended
- Δ = Not suitable for forklift traffic
- ◇ = Large animal spaces and LN2 resistance
- = Use conductive adhesive and copper tape with ed products
- † = Must use nora® 2-part adhesive
- *Not inclusive of all potential space applications

noraplan® tiles/sheet/plank				
convia, dariva, environcare, sentica (2.0 mm)	dariva, environcare, sentica (3.0 mm)	environcare acoustic, sentica acoustic	environcare ed, sentica ed	unita (2.0 mm) valua (2.0 mm/ 3.0 mm)
—	—	—	✓ ■	—
✓	✓	—	—	✓
✓	✓	—	—	✓
—	—	—	—	—
✓	✓	—	✓ ■	—
✓	✓	—	✓ ■	✓
✓	✓	—	—	✓
✓	✓	—	—	✓
—	—	—	✓ ■	—
✓	✓	—	✓ ■	—
—	—	—	—	—
—	—	—	✓ ■ Δ	—
✓	✓	—	—	✓
—	✓	—	✓ ■	—
✓	✓	—	—	✓
—	—	—	—	—




norament product range

norament®


The classic among rubber floor coverings, norament represents absolute top quality and functionality and is available in a wide range of color and surface designs.

norament® 825 round


Monochrome with a classic round pastille surface for use in heavy traffic areas.




5336
Rhino




0884
Dust Grey




5337
Ash




0702
Black




0007
Aluminum




0882
Platinum Grey




0749
Stone Grey




0716
Slate Grey




2070
Sage




5343
Evergreen




0319
Slate Blue



0733
Steel Blue




5338
Biscuit



5341
Maize

norament 825 round

 14

Art. 1902

□ ~19.72" x 19.72" (501 mm x 501 mm)



~1.08" (27.5 mm)

~0.5 mm

~2.7 mm

~3.2 mm


These colors can also be delivered as:

-  Stairtread norament round
-  nora QuickShip Program



norament[®] arago[™]

Flat, direction-oriented relief structure with fine granules and modern marbling design for maximum demands. No two tiles are the same – each tile is totally unique.



norament arago

12
Art. 3118
~39.53" x 19.76" (1004 mm x 502 mm)

~3.5 mm

norament arago with beveled edges

12
Art. 3119
~39.23" x 19.57" (998 mm x 497 mm)

~3.5 mm

Upon request; call for lead times.

Variations in color and design, even within one production batch, define the product's aesthetic character.

These colors can also be delivered as:

Stairtread norament arago


norament[®] arago[™] nTx[™]




Viroqua Food Co+op, Viroqua, WI

norament castello™


Lightly marbled pattern with movement and variation that mimic nature and a two-tone surface for maximum demands. No two tiles are the same – each tile is totally unique.




5351
Chateau




5352
Citadel




5353
Cortege




5354
Manor




5355
Palazzo



5356
Domus



5357
Palais



5358
Cathedral



norament castello
8

Art. 3167
□ ~39.53" x 39.53" (1004 mm x 1004 mm)

 ~3.5 mm

Variations in color and design, even within one production batch, define the product's aesthetic character.


These colors can also be delivered as:

-  norament castello™ nTx™
-  nora QuickShip Program




norament® grano™


Rich, contrasting granular design with a hammered surface for use in extremely heavy traffic areas.




5301
White Fir




5302
Angelica Root




5303
Frankincense




5304
Black Pepper




5305
Agar




5306
Camphor




5307
Fenugreek




5308
Myrrh




5309
Jasmine




5310
Helichrysum




5311
Copaiba




5312
Vetiver




5313
Marjoram



5314
Henna



5315
Cedarwood




5316
Siberian Fir

norament grano

32

Art. 1880

□ ~39.53" x 39.53" (1004 mm x 1004 mm)

 ~3.5 mm


norament grano


For raised access floors

5


Art. 1912

□ ~24.6" x 24.6" (625 mm x 625 mm)


 ~3.5 mm




5317
Agapanthus




5318
Blue Tansy




5319
Spikenard




5320
Sassafras




5321
Wintergreen




5322
Ylang-ylang




5323
Plumeria




5324
Patchouli




5325
Balsam




5326
Fennel Seed




5327
Tea Tree




5328
Arborvitae




5329
Bergamot



5330
Cassia





5331
Neroli





5332
Geranium


These colors can also be delivered as:


- 


Special flooring norament grano ed electrostatically dissipative
- 

Special flooring norament grano ed electrostatically dissipative for raised access floors
- 

Special flooring norament® 992 grano™
- 

Stairtread norament grano
- 


norament® grano™ nTx™
- 

nora QuickShip program
- 

norament grano for raised access floors

norament® **hammered**

Monochrome with a hammered surface for use in heavy traffic areas.




norament hammered
14
Art. 1910
~19.76" x 19.76" (502 mm x 502 mm)
~2.7 mm

These colors can also be delivered as:
└─ Stairtread norament hammered

norament **kivo™**

Contemporary look of concrete with irregular grain design and a slightly structured two-tone surface for use in heavy traffic areas.




norament kivo
8
Art. 3166
~39.53" x 39.53" (1004 mm x 1004 mm)
~2.7 mm

Variations in granulate scattering, even within one production batch, define the product's aesthetic character.



norament **pado™**

Variegated granular design inspired by ancient terrazzo with a slightly structured two-tone surface for maximum demands.



norament pado
16

Art. 3167
□ ~39.53" x 39.53" (1004 mm x 1004 mm)


~3.5 mm

NOTE: Also available as norament pado™ nTx".
Minimum quantities required; contact your sales representative.




norament® satura™


Tone-on-tone granular design with a hammered surface for use in extremely heavy traffic areas.




5101
Andromeda




5102
Grus




5103
Mercury




5104
Centaurus




5105
Cygnus




5106
Vulpecula




5107
Callisto




5108
Indus




5109
Orion




5110
Ara




5111
Castor




5112
Titan




5113
Sagitta



5114
Circinus



5115
Hercules




5116
Arcturus

norament satura


32

Art. 1880
~39.53" x 39.53" (1004 mm x 1004 mm)


~3.5 mm




5117
Draco




5118
Pavo




5119
Mars




5120
Jupiter




5121
Hydra




5122
Earth




5123
Venus




5124
Aquila




5125
Cetus




5126
Saturn




5127
Vela




5128
Delphinus




5129
Neptune



5130
Aquarius



5131
Cassiopeia



5132
Monoceros

These colors can also be delivered as:

- Stairtread norament satura
- norament® satura™ nTx™
- nora QuickShip program





noraplan product range

noraplan®

noraplan floor coverings are available as sheets or tiles in a variety of designs and colors for extensive design possibilities.

noraplan **convia™**

The simple, smart flooring solution. Streamlined, purposeful design and the performance of nora flooring, all at our best value. A solid base color and dirt-concealing neutral granules with a smooth surface for use in heavy traffic areas.



noraplan convia
28

Art. 170F
~49.21' x 48" (15.0 m x 1.22 m)

Art. 270F
~24.015" x 24.015" (610 mm x 610 mm)

~2.0 mm

These colors can also be delivered as:
nora QuickShip program

NOTE: Sheet available as noraplan convia™ nTx™



noraplan darivia™

Organic, nature inspired design with varying degrees of contrast in a smooth surface for heavy traffic areas.



7161
Pine Nut



6716
Almond



6714
Mushroom



6713
Birch



7164
Hickory



6718
Walnut



6721
Sandbar



6709
Smoke



7168
Argan



6715
Pecan



6722
Pinecone



7169
River Birch



7173
Red Maple



6719
Cocoa Bean



6723
Bark



6710
Charcoal

noraplan dariva 2 mm
28


Art. 160F
~49.21' x 48" (15.0 m x 1.22 m)


~2 mm

noraplan dariva 3 mm
28


Art. 161F
~39.37' x 48" (12.0 m x 1.22 m)

~3 mm


 NOTE: Available as noraplan dariva™ nTx™. Minimum quantities may be required




7162
Cottonwood




6708
Beach Wood




7163
Plantain




7165
Pepperwood




7166
Palmetto




7167
Juniper




7170
Acai Berry




7171
Blue Spruce




7172
Sycamore



7174
Bluebell



7175
Wisteria




7176
Hemlock




noraplan **environcare™**


A changing base color consisting of three harmoniously matched color components and characteristic granules in a smooth surface for heavy traffic areas.




7031
Baseball Game




7032
Sleigh Ride




7033
Tail Gating




7034
Fireworks




7035
Snow Shoeing




7036
Clam Bake




7037
Fun Run




7038
Hide-n-Seek




7039
Baby Shower




7040
Bike Ride




7041
Whale Watch




7042
Star Gazing




7043
Ice Fishing



7044
Egg Hunt




7045
Ice Skating




7046
Drive-In

noraplan environcare 2.0 mm
48
Art. 1462
~49.21' x 48" (15.0 m x 1.22 m)
Art. 2462
~24.015" x 24.015" (610 mm x 610 mm)
~2.0 mm


noraplan environcare 3.0 mm
48
Art. 1463
~39.37' x 48" (12.0 m x 1.22 m)
Art. 2463
~24.015" x 24.015" (610 mm x 610 mm)
~3.0 mm




7047
Skiing




7048
Pie Contest




7049
Summer Camp




7050
Petting Zoo




7051
Snowball Fight




7052
Sledding




7053
Pot Luck




7054
Book Club




7055
Champagne Toast




7056
Antiquing




7057
Cookie Swap




7058
Beach Day




7059
Candlelight Dinner




7060
Garden Party




7061
Farmers Market




7062
Football




7063
Car Wash




7064
Water Park




7065
Pool Party




7066
Parade




7067
Yard Games




7068
Mini Golf




7069
Leap Frog




7070
Tennis Match




7071
Corn Maze




7072
Leaf Peeping




7073
Apple Picking




7074
Music Festival




7075
Food Coma



7076
County Fair



7077
Graduation



7078
Haunted House

These colors can also be delivered as:

- Special flooring noraplan environcare ed electrostatically dissipative
- Special flooring noraplan environcare acoustic footfall-sound-absorbing
- noraplan environcare™ nTx™
- nora QuickShip program

noraplan® sentica™

Tone-on-tone design with harmoniously matching color components in a smooth surface for heavy traffic areas.

6500
Cotton Candy

6501
Prom

6502
Vacation

6503
Indulgence

6504
Down Feathers

6505
Silk

6506
Cashmere

6507
Old Oak

6508
Wool

6509
Sand Box

6510
Dinner Rolls

6511
Clydesdale

6512
Sunrise

6513
Hayride

6514
Heat Wave

6515
Barbeque

6516
Aloe

6517
Cut Grass

6518
First Day

6519
Picnic

6520
Snow Day

6521
Sunday Paper

6522
Expedition

6523
Road Trip

6524
Frost Bite

6525
Ocean Mist

6526
Mountain Air

6527
Deep Sea

6528
Ice Cube

6529
Surf

6530
Waterfall

6531
Regatta

6532
Zest

6533
Valentine

6534
Carnival

6535
Destination

6536
Wheat Fields

6537
Camp Fire

noraplan sentica 2.0 mm

38

Art. 1700

~49.21' x 48" (15.0 m x 1.22 m)

Art. 2700

~24.015" x 24.015" (610 mm x 610 mm)

± ~2.0 mm

noraplan sentica 3.0 mm

38

Art. 1701

~39.37' x 48" (12.0 m x 1.22 m)

Art. 2701

~24.015" x 24.015" (610 mm x 610 mm)

± ~3.0 mm





















These colors can also be delivered as:

- Special flooring noraplan sentica ed electrostatically dissipative
- Special flooring noraplan sentica acoustic footfall-sound-absorbing
- noraplan® sentica™ nTx™
- nora QuickShip program

noraplan flooring

noraplan® unita™

The perfect combination of resilient rubber and randomly dispersed granite chips.

			
7105 Push-N-Pull	7106 Right-N-Left	7107 High-N-Low	7108 Near-N-Far
			
7113 Ask-N-Tell	7117 Open-N-Shut	7115 Hot-N-Cold	7119 Wet-N-Dry
			
7101 Here-N-There	7102 Up-N-Down	7103 Come-N-Go	7104 Bitter-N-Sweet
			
7114 All-N-None	7118 Dusk-N-Dawn	7120 Night-N-Day	7116 Fire-N-Ice
			
7112 Now-N-Then	7111 Back-N-Front	7109 North-N-South	7110 East-N-West

noraplan unita
20
Art. 1640
~49.21' x 48" (15.0 m x 1.22 m)
~2.0 mm






Rotterdam Business School, Rotterdam, Netherlands © CR-BEELDWERKEN


noraplan® **valua™**

A linear surface structure and nature inspired marbled detail for heavy traffic areas.




			
6708 Beach Wood	 6709 Smoke	 6710 Charcoal	6711 Ebony
			
6712 Sea Foam	6713 Birch	6714 Mushroom	6715 Pecan
			
6716 Almond	6717 Maple	6718 Walnut	6719 Cocoa Bean
			
6720 Macadamia	 6721 Sandbar	 6722 Pine Cone	 6723 Bark


noraplan valua 2.0 mm

 16
Art. 174A
 ~49.21' x 48" (15.0 m x 1.22 m)
 ~2.0 mm

These colors can also be delivered as:
 noraplan valua planks

noraplan valua 3.0 mm

 16
Art. 175A
 ~39.37' x 48" (12.0 m x 1.22 m)
 ~3.0 mm

 NOTE: Available as noraplan® valua™ nTx™.
Minimum quantities may be required




noraplan® **valua™ plank**

Exercise your creativity with the ultimate flexibility of noraplan valua plank. Standard in 5 colors and 3 sizes, you can create a myriad of effects.



6709
Smoke



6710
Charcoal



6721
Sandbar



6722
Pine Cone



6723
Bark




Boerhof showroom

Beveled plank edges enhance the tiled, individual look while being easy to clean and maintain. Heat welding is not required, allowing for ease of installation while providing a hygienic seal.


Planks (with beveled edges)




~24.015" x 6"
(610 mm x 152.5 mm)




~24.015" x 8.07"
(610 mm x 205 mm)



~24.015" x 12"
(610 mm x 305 mm)









~48.03" x 7.97"
(1220 mm x 202.5 mm)



~48.03" x 15.94"
(1220 mm x 405 mm)

Example installations



noraplan valua plank 2.0 mm



Art. 272A

~24.015" x 8.07" (610 mm x 205 mm)



Art. 273A

~24.015" x 12" (610 mm x 305 mm)



Art. 274A

~48.03" x 15.94" (1220 mm x 405 mm)

~2.0 mm

noraplan valua plank 3.0 mm



Art. 275A

~24.015" x 8.07" (610 mm x 205 mm)



Art. 276A

~24.015" x 12" (610 mm x 305 mm)



Art. 277A

~48.03" x 15.94" (1220 mm x 405 mm)

~3.0 mm



NOTE: Available as noraplan valua nTx.
Minimum quantities may be required



nora special floorings

nora special floorings

We developed our special floorings for areas subject to special technical standards and requirements, including increased footfall sound absorption, special fire protection and electrostatically dissipative requirements. We also have specialized solutions that withstand the stresses of extreme weights, harsh chemicals, ice blades and more.

norament® 920 🔥

Monochrome with a classic round pastille surface for use in extra heavy traffic areas subject to special fire protection requirements.



0884
Dust Grey



0749
Stone Grey




0702
Black



0862
Azure Blue

norament 920
4

Art. 354
~39.61" x 39.61" (1006 mm x 1006 mm)



- Increased safety thanks to high fire-retardant properties
- Ideal flooring for emergency exits and stairways
- IMO Certified floor covering
- Meets Class A (ASTM E84 Tunnel Test) with a flame spread rate of 15 and smoke development of 300
- For use in egress areas above 75 feet according to International Building Code (IBC)
- Passes ISO 26987 for oil and grease resistance

These colors can also be delivered as:

Stairtread norament 920



Nazareth College, Rochester, NY

norament® 992 norament® 992 grano

Designed to meet the extreme wear-resistant requirements of ice blades, spikes, cleats and free weights. norament 992 contains at least 11% recycled content.



norament 992



0702
Black


norament 992
1

Art. 1955
~39.45" x 39.45" (1002 mm x 1002 mm)




Kent State University, Kent, OH


norament 992 grano



5302
Angelica Root




5303
Frankincense




5304
Black Pepper



5308
Myrrh



5317
Agapanthus



5319
Spikenard


norament 992 grano
6

Art. 1955
~39.45" x 39.45" (1002 mm x 1002 mm)



norament® xp™

A granular design for use in high-performance workspaces. Its high-impact, dense structure resists the stresses of extreme weight and harsh chemicals.




norament xp
Art. 1880
~39.53" x 39.53" (1004 mm x 1004 mm)
~3.5 mm

These colors can also be delivered as:
norament® xp™ nTx™

norament® xp trac™

A granular design with an enhanced surface profile for use in facilities and applications challenged with recurrent wet areas, requiring enhanced slip resistance.



norament xp trac
Art. 325
~39.53" x 39.53" (1004 mm x 1004 mm)
~3.5 mm

These colors can also be delivered as:
norament® xp trac™ nTx™




Biopharmaceutical Manufacturing Facility, USA


norament ed ⚡


Electrostatically dissipative “ed” flooring for optimum ESD protection of electronic devices and equipment and resists most oils and greases and is suitable for forklift truck areas.





norament grano ed





 5301
White Fir





 5306
Camphor




 5317
Agapanthus




 5318
Blue Tansy




5329
Bergamot




5325
Balsam



5321
Wintergreen





 5304
Black Pepper

norament grano ed
Static-dissipative
 8


Art. 1880
□ ~39.45" x 39.45" (1002 mm x 1002 mm)



norament grano ed 
Static-dissipative for raised access floors
 5

Art. 1912
□ ~24.6" x 24.6" (625 mm x 625 mm)



These colors can also be delivered as:
 nora QuickShip program

Quick-Installation of nora® ESD Floor Coverings


nora ESD floor coverings can be quickly and easily installed using nora dryfix ed. It accelerates the installation and allows for immediate trafficking. See nora Installation & Care section for more details.

noraplan ed ⚡


Electrostatically dissipative “ed” flooring for optimum ESD protection of electronic devices and equipment and resists most oils and greases.




noraplan environcare ed




7031
Baseball Game




7033
Tail Gating




7035
Snow Shoeing




7036
Clam Bake




7044
Egg Hunt




7045
Ice Skating




7051
Snowball Fight




7052
Sledding




7055
Champagne Toast




7056
Antiquing




7065
Pool Party



7066
Parade



7067
Yard Games



7076
County Fair

noraplan environcare ed 2.0 mm
 14

Art. 1390
⌚ ~49.21' x 48" (15.0 m x 1.22 m)

Art. 2390
□ ~24.015" x 24.015" (610 mm x 610 mm)




noraplan environcare ed 3.0 mm
 14

Art. 1523
⌚ ~39.37' x 48" (12.0 m x 1.22 m)





noraplan sentica ed



noraplan sentica ed 2.0 mm
12

Art. 1702
~49.21' x 48" (15.0 m x 1.22 m)

Art. 2702
~24.015" x 24.015" (610 mm x 610 mm)
~2.0 mm

noraplan sentica ed 3.0 mm
12


Art. 1703
~39.37' x 48" (12.0 m x 1.22 m)

~3.0 mm

noraplan® acoustic

For a high footfall sound absorption improvement of Δ IIC 23.
noraplan acoustic contains 29% recycled content.

noraplan environcare acoustic















noraplan environcare acoustic
12

Art. 1420
~39.37' x 48" (12.0 m x 1.22 m)

~1.6 mm
~2.4 mm
~4.0 mm

NOTE: noraplan® acoustic flooring must be welded with nora® heat weld.

noraplan sentica acoustic

			
6524 Frost Bite	6520 Snow Day	6521 Sunday Paper	6522 Expedition
			
6508 Wool	6513 Hayride	6505 Silk	6510 Dinner Rolls
			
6516 Aloe	6517 Cut Grass	6530 Waterfall	6531 Regatta

noraplan sentica acoustic
12

Art. 1705
~39.37' x 48" (12.0 m x 1.22 m)

~1.6 mm
~2.4 mm
~4.0 mm

NOTE: noraplan acoustic flooring must be welded with nora heat weld.



Kindergarten Völklingen, Völklingen, Germany

© arus gmbh willi latz | photographer: Norbert Miguletz

nora QuickShip


READY. SET. GO!

Available to ship within 15 days, the nora QuickShip program offers an array of norament and noraplan products in a variety of color and product combinations, including ESD flooring, stair treads, weld, and cove base options.

norament 825 round



0884
Dust Grey



0882
Platinum Grey



0749
Stone Grey



0716
Slate Grey



0702
Black

norament 825 round
5

Art. 1902
□ ~19.72" x 19.72" (501 mm x 501 mm)

~1.08" (27.5 mm) ~0.5 mm ~3.2 mm
~2.7 mm

norament round stairtreads
5

Art. 465 – width ~50.59" (1285 mm)

~19.88" (505 mm) ~6.5" (165 mm) ~3.34" (85 mm) ~9.65" (245 mm) ~1" (25 mm) ~0.5 mm ~4.5 mm

norament castello



5355
Palazzo




5354
Manor

norament castello
2


Art. 3167
□ ~39.53" x 39.53" (1004 mm x 1004 mm)

~3.5 mm


norament grano




5301
White Fir




5302
Angelica Root




5303
Frankincense




5304
Black Pepper




5306
Camphor




5319
Spikenard



5320
Sassafras



5329
Bergamot



5332
Geranium

norament grano
9

Art. 1880
□ ~39.53" x 39.53" (1004 mm x 1004 mm)

~3.5 mm

norament grano ed
Static-dissipative
3

Art. 1880
□ ~39.45" x 39.45" (1002 mm x 1002 mm)


~3.5 mm

norament grano stairtreads


Art. 479 – width ~50.59" (1285 mm)

~19.88" (505 mm) ~6.5" (165 mm) ~3.34" (85 mm) ~9.65" (245 mm) ~1" (25 mm) ~5 mm


norament satura




5110
Ara



5111
Castor



5107
Callisto



5116
Arcturus

norament satura
4

Art. 1880
□ ~39.53" x 39.53" (1004 mm x 1004 mm)

~3.5 mm

norament satura stairtreads

Art. 479 – width ~50.59" (1285 mm)

~19.88" (505 mm) ~6.5" (165 mm) ~3.34" (85 mm) ~9.65" (245 mm) ~1" (25 mm) ~5 mm

noraplan convia




7360
Stone Khaki



7355
Silver Sand



7356
Shale



7352
Lava Rock



7366
Patina Green



7370
Pigeon Blue

noraplan environcare


3.0 mm Color Range



7031
Baseball Game



7035
Snow Shoeing



7036
Clam Bake




7051
Snowball Fight




7052
Sledding




7053
Pot Luck



7061
Farmers Market



7065
Pool Party



7073
Apple Picking

noraplan convia



6

Art. 270F

□ ~24.015' x 24.015" (610 mm x 610 mm)



noraplan environcare (cont'd)

2.0 mm Color Range



7031
Baseball Game



7032
Sleigh Ride

noraplan environcare 2.0 mm



2

Art. 1462

⌚ ~49.21' x 48" (15.0 m x 1.22 m)



noraplan sentica

3.0 mm Color Range



6505
Silk




6506
Cashmere



6520
Snow Day



6524
Frost Bite



6525
Ocean Mist



6526
Mountain Air

noraplan sentica 3.0 mm



6

Art. 1701

⌚ ~39.37' x 48" (12.0 m x 1.22 m)



noraplan sentica 2.0 mm



1

Art. 1700

⌚ ~49.21' x 48" (15.0 m x 1.22 m)



2.0 mm Color Range



6520
Snow Day

nora cold weld













			
0702	0716	0749	0882
			
0884	1253	2382	2666
			
2781	2897	2931	4881
			
5107	5110	5111	5116
			
5121	5301	5302	5303
			
5306	5319	5354	5355
			
6505	6506	6520	6524
			
6525	6708	7052	7053
			
7061	7065	7073	

nora cold weld
35

Art. 928
10 fl. oz. (300 ml)
~50-60 LF per unit

Note: please remember, we have joint cutters,
spatulas and cold weld tape available for order.

nora sanitary base

			
2945	5111	5303	5304
			
5306	5319	6505	6506
			
6524	7035	7036	7052

nora sanitary base
12

Art. 817 – S 3019 D
Piece Length: ~32.81' (10 m)

*Conforms to ASTM F1861 – Standard
Specification for Resilient Wall Base, Type TP:
Thermoplastic Rubber, Group 1

Note: For floor covering thicknesses from
.12" to .14" (3.0 to 3.5 mm).

nora QuickShip Guidelines:

- Timing: Ships within 15 business days
- Maximum Order Quantities
 - noraplan and norament flooring (neutral colors): up to 600 m² (~6,458 SF)
 - noraplan and norament flooring (accent colors): up to 100 m² (~1,076 SF)
 - norament stairtreads: up to 75 pieces
 - nora cold weld: up to 15 units
 - nora sanitary base: up to 5 rolls
- Minimum Order Quantities
 - noraplan rolls: one roll
 - noraplan tiles: one box
 - norament tiles: one tile
 - norament stairtreads: one piece
 - nora cold weld: one unit
 - nora sanitary base: one roll
- Product sizes standard as published; no cutting
- norament stairtreads: 4 ft standard treads only; no routing or VI
- No overages
- No holds
- No allocations to an order for more than 48 hours
- Inventory allocated upon credit approval
- Consider transit times for shipments to Canada and Latin America



nora stairwell solutions

nora stairwell solutions

The first choice for smart, hard-working stairwells, nora offers a wide range of design options for floor coverings and stairs that can complement any interior.


Depending on your needs, we provide two distinct stairwell solutions. For angled stairs, the one-piece norament stairtreads are ideal. For other stairwells, your preferred nora floor covering can be used in combination with a stair nosing.

norament stairtreads

Our one-piece stair coverings include stair nosing, riser and tread and are built to fit straight steps with an angled edge. norament stairtreads are designed to withstand extremely heavy traffic while maintaining their good looks.


norament 920 stairtreads (Class A fire-rated) 🔥

Monochrome with a classic round pastille surface for special fire-protection requirements.




norament 920 stairtreads
4

Art. 465 – width ~50.59" (1285 mm)



- Meets Class A (ASTM E84 Tunnel Test) with a spread rate of 15 (flame) and 300 (smoke)
- Ideal for emergency exits and stairways
- For use in egress areas above 75 feet according to International Building Code (IBC)
- Class A photoluminescent visually impaired strips available



norament arago stairtreads


Flat, direction-oriented relief structure with fine grain design and modern marbling.



norament arago stairtreads
6


Art. 3170 – width ~50.59" (1285 mm)
Art. 3171 – width ~63.54" (1614 mm)
Art. 3172 – width ~78.89" (2004 mm)

Variations in color and design, even within one production batch, define the product's aesthetic character.



norament grano stairtreads



Rich, contrasting granular design with a hammered surface.



norament grano stairtreads
12


Art. 479 – width ~50.59" (1285 mm)
Art. 468 – width ~63.54" (1614 mm)
Art. 469 – width ~78.89" (2004 mm)

These colors can also be delivered as:
nora QuickShip program (Art. 479 only)




norament hammered stairtreads


Monochrome with a hammered surface.




5336
Rhino




0884
Dust Grey




5337
Ash




0702
Black




0007
Aluminum




0882
Platinum Grey




0749
Stone Grey




0716
Slate Grey



5343
Evergreen




0319 S
Slate Blue




0733
Steel Blue

norament hammered stairtreads
11
Art. 479 – width ~50.59" (1285 mm)
Art. 468 – width ~63.54" (1614 mm)
Art. 469 – width ~78.89" (2004 mm)




norament round stairtreads


Monochrome with a classic round pastille surface.




5336
Rhino




0884
Dust Grey




5337
Ash




0702
Black




0007
Aluminum




0882
Platinum Grey




0749
Stone Grey




0716
Slate Grey



5343
Evergreen





0319
Slate Blue



0733
Steel Blue


norament round stairtreads
11
Art. 465 – width ~50.59" (1285 mm)
Art. 466 – width ~63.54" (1614 mm)
Art. 467 – width ~78.89" (2004 mm)

These colors can also be delivered as:
nora QuickShip program (Art. 465 only)




norament satura staitreads


Tone-on-tone granular design with a hammered surface.





5102
Grus




5103
Mercury





 5107
Callisto




5108
Indus





 5110
Ara





5114
Circinus




 5115
Hercules




 5116
Arcturus






5121
Hydra



5127
Vela

norament satura staitreads
 10
Art. 479 – width ~50.59" (1285 mm)
Art. 468 – width ~63.54" (1614 mm)
Art. 469 – width ~78.89" (2004 mm)


These colors can also be delivered as:
 nora QuickShip program (Art. 479 only)




nora stair accessories

nora® stair nosings

Bring the full repertoire of nora floor coverings to more types of stairs, including specialty stairs like spiral staircases, by pairing nora stair nosings with nora flooring. nora stair nosings are designed for multiple flooring thicknesses and can be used on noraplan or norament floor coverings. Once the flooring is pre-cut to the dimension of an individual stair tread, the nora stair nosing insertion lip locks the flooring into place and protects the cut edge. And, nora stair nosings are both impact and shock resistant.

 8
Art. 805 – T 5049
Art. 802 – T 5044
Piece Length: ~8.2' (2.5 m)

0702	0749	5301	5310
0716	0884	5305	6179



nora® visually impaired strips

nora visually impaired strips, offered in textured or smooth surfaces in an array of high-contrast colors, may be inserted into any of our one-piece stair coverings. A photoluminescent option is also available on request.

Piece Width: ~2" (50.8 mm)

6


Textured:

Safety Yellow	Coral Red
Boardwalk	Black
Nite Glow	Ocean Grey

2

Smooth:

0122	0895
------	------



To ensure safety and performance, nora epoxy stair filler is used under the stairtread nosing when installed with nora visually impaired strips. See below.

nora® stepfix™ 240

nora stepfix 240 is an innovative and cost-effective adhesive tape suitable for new builds and renovation projects. Specifically designed for norament stairtreads, nora stepfix 240 makes installation 3-5 times faster than conventional installation methods, and the process is odorless, clean, and easy.

You can dry-fit the tread right on the covered adhesive tape, and stairs can be walked on immediately after installation. And nora stepfix 240 is GREENGUARD Gold certified for low VOC emissions, helping to improve indoor air quality.



Art. 907
Dimension of rolls: ~9.45" width x 164' length (240 mm x 50 m) = ~129 square feet (12 m²)

nora® epoxy stair filler

Art. 500875
A solvent-free, non-flammable, high-performance epoxy that sets to a hard, permanent bond. Use on stairs with greater than 1/4" radius or damaged edges to provide support under the stairtread nosing. Required for nora visually impaired strips.


- 13.5 oz dual cartridge applicator with special mixer application tip
- Two cartridge caulking gun required
- Coverage: ~40 linear feet with a .25" bead



nora® metal repair stair angle

Art. 6637
Prep rounded, wavy, damaged or bowed steps with the nora metal repair stair angle prior to installing nora stairwell products.

- Screws: middle of hole to middle of hole ~2.5" (63.5 mm) Piece Length: ~39.37" (1.0 m)



On stairs with round nosing, nora metal repair stair angle and/or nora epoxy stair filler must be used to fill the void.



Milford High School, Highland, MI

nora installation & care

Our nora install and care products ensure your floor installation is a success and your floor looks and performs exactly as it should for decades to come. From traditional to innovative installation systems, economic and ecological cleaning systems and accessories for your floor's finishing details, our range of options makes it easy to realize and preserve the value of your nora rubber floorcoverings.



nora® nTx™ The Revolutionary Fast Installation System

nora nTx is a unique technology for professional installation of nora rubber floor coverings. Ingeniously simple - nora nTx floor coverings brings adhesive strength along from the factory.

The flooring is cleanly and safely installed in a few steps then immediately ready for use. Install over concrete or cement substrates typical in new construction or over existing floor coverings during renovations. Even high residual moisture in the substrate is no problem for nora nTx.

nora also offers a range of tools and installation material to ensure clean and safe substrate preparation.

The advantages at a glance:



Reliable installation result

nora nTx reduces installation problems and is backed by our 10-year bond warranty*.



Immediate usability

Avoid drying and waiting times. Installation is possible during ongoing operations, and the floor can be used immediately after installation.



High efficiency

The preparation of the floor and the installation of nora nTx require only few work steps – for more space in less time.



For all types of substrates

nora nTx is suitable for all common-types of substrates—ideal also for problematic substrates and underfloor heating.



Use with residual moisture

Application in new buildings is possible even with increased residual moisture in the substrate.



Covering-over-covering installation

In the case of renovations, installation is possible directly over existing floor coverings in just a few steps.




nora nTx standard color




available as nora nTx with minimum order quantity

*Under the criteria detailed in our nora nTx Warranty - Americas at www.nora.com


norament® arago™ nTx™



5171
Fortitude




5172
Stamina



5175
Unity



5177
Balance



5178
Calm

norament arago nTx

5


Art. 3122

□ ~39.53" x 19.76" (1004 mm x 502 mm)



These tiles can also be supplied with beveled edges.


norament castello™ nTx™



5354
Manor



5355
Palazzo



5356
Domus



5357
Palais

norament castello nTx


4

Art. 3177


□ ~39.53" x 39.53" (1004 mm x 1004 mm)




norament® grano™ nTx™




5301
White Fir



5302
Angelica Root



5303
Frankincense




5304
Black Pepper

norament grano nTx


16

Art. 3111

□ ~39.53" x 39.53" (1004 mm x 1004 mm)




5305
Agar




5306
Camphor




5307
Fenugreek




5308
Myrrh




5315
Cedarwood



5318
Blue Tansy




5319
Spikenard




5320
Sassafras



5325
Balsam



5329
Bergamot



5331
Neroli




5332
Geranium

Note: Please call for lead times


norament® satura™ nTx™




5102
Grus



5105
Cygnus




5106
Vulpecula




5110
Ara




5111
Castor




5114
Circinus




5115
Hercules



5116
Arcturus



5121
Hydra



5122
Earth

norament satura nTx


10

Art. 3111


□ ~39.53" x 39.53" (1004 mm x 1004 mm)




norament® xp™ nTx™



5306
Camphor



5310
Helichrysum



5319
Spikenard



5330
Cassia

norament xp


4

Art. 1880


□ ~39.53" x 39.53" (1004 mm x 1004 mm)




norament® xp trac™ nTx™




5303
Frankincense



5306
Camphor



5319
Spikenard



5330
Cassia

norament xp trac

4

Art. 325


□ ~39.53" x 39.53" (1004 mm x 1004 mm)



Note: Please call for lead times

noraplan environcare™ nTx™

3.0 mm rolls



7033
Tail Gating



7051
Snowball Fight



7055
Champagne Toast



7056
Antiquing

noraplan environcare nTx 3.0 mm
7
Art. 187C
~39.37' x 48" (12.0 m x 1.22 m)
~3.0 mm



7061
Farmers Market



7065
Pool Party




7073
Apple Picking

2.0 mm rolls



7031
Baseball Game



7033
Tail Gating



7036
Clam Bake



7051
Snowball Fight

noraplan environcare nTx 2.0 mm
5
Art. 181C
~49.21' x 48" (15.0 m x 1.22 m)
~2.0 mm



7055
Champagne Toast

Note: Please call for lead times

noraplan® sentica™ nTx™

3.0 mm rolls



6505
Silk



6506
Cashmere



6520
Snow Day

noraplan sentica nTx 3.0 mm
3
Art. 186C
~39.37' x 48" (12.0 m x 1.22 m)
~3.0 mm

2.0 mm rolls




6505
Silk



6506
Cashmere




6520
Snow Day




6522
Expedition

noraplan sentica nTx 2.0 mm
5
Art. 182C
~49.21' x 48" (15.0 m x 1.22 m)
~2.0 mm



6529
Surf

nora nTx | the system configuration



1 Substrate **2** nora® nTx™ 020 (bond enhancer) **3** nora nTx floor covering with self-adhesive back

nora nTx includes a range of standard noraplan sheet and norament tile floor coverings that come equipped with a self-adhesive layer. The glue in the adhesive layer is protected with film until installation and—like our floor coverings—is rubber-based and particularly health-friendly. Specially developed installation materials and tools for nora nTx provide functional safety and ensure the highest quality standards.

Note: Please call for lead times

nora nTx installation materials

nora nTx 020 has been developed specifically for the nora nTx floor coverings. The perfect matching between the bond enhancer and the nora nTx floor coverings provides functional reliability and ensures the highest standards of quality. Moreover, nora nTx 020 can be applied to substrates with higher residual moisture levels.

nora® nTx™ 020

Bond enhancer

nora nTx 020 is a 1-component Polyurethane resin bond enhancer for use with the nora nTx system on absorptive and non-absorptive substrates.

- Ready to use
- Fast drying
- Alkali resistant
- Solvent free
- Ready for installation in about 1 hour
- Superior bonding to a wide range of substrates


Art. 6684
Bond enhancer for improved adhesion
2.6 gallon bottle



nora nTx tools

Diamabrush™ Concrete Prep Plus Tool
Sanding disc for preparing substrates

Dust Skirt



Diamabrush™ Concrete Prep Plus Tool

Art. 6502
Material # 502521 — 20"
Suitable sanding discs for the machines: Mambo, Columbus, and Orkan.
NOTE: Please specify the machine type in your order

Material # 502526 — 20"



Diamabrush™ Dust Skirt

nora dry adhesives

nora dryfix™ 750

nora dryfix 750 provides a quick, easy, and reliable alternative to conventional flooring adhesives. There is no mixing or adhesive clean-up necessary, and nora dryfix 750 allows for immediate traffic post-installation.

- Odorless
- Recommended for operating rooms
- Excellent for heavy traffic
- No necessary open time required
- Non-flammable and freeze/thaw stable
- Free of organic solvents, formaldehyde, asbestos, lindane, rosins, phthalates, benzoates, adipates, or any other volatile components
- GREENGUARD Gold certified for low VOC emissions
- In compliance with South Coast (CA) Air Quality Management District Rule 1168

Art. 6556
29.5" wide x 98.5' long (75 cm x 30 m)

nora dryfix™ mr

Moisture-resistant dry adhesive tape

nora dryfix mr is a double-sided dry adhesive tape for the installation of nora floor coverings in high moisture areas. It is easy to install with no mixing or adhesive clean up, and it allows for immediate traffic after installation is complete. With nora dryfix mr, there's no need for relative humidity testing, in-situ probes or waiting for adhesives to dry. Think of the cost savings and downtime eliminated.

- Quick and easy dry installation
- Less downtime with immediate trafficking after installation
- No RH testing and no vapor retarder required
- Suitable for all common substrates
- Reliable in high performance areas
- GREENGUARD Gold certified for low VOC emissions
- In compliance with South Coast (CA) Air Quality Management District Rule 1168

Art. 6556
30" x 250' (76 cm x 76.2 m)

nora dryfix™ ed

Conductive dry adhesive tape

nora dryfix ed provides a quick, easy, and reliable alternative to conventional conductive flooring adhesives. There is no mixing or adhesive clean-up necessary, and nora dryfix ed allows for immediate traffic post-installation.

- Odorless
- Excellent for heavy traffic
- Immediate use conductive adhesive
- Non-flammable and freeze/thaw stable
- Free of organic solvents, formaldehyde, asbestos, lindane, rosins, phthalates, or any other volatile components
- GREENGUARD Gold certified for low VOC emissions
- In compliance with South Coast (CA) Air Quality Management District Rule 1168

Art. 6706
29.5" wide x 98.5' long (75 cm x 30 m)

nora® profix™

nora profix tape is supplied in rolls for installation of nora sanitary base and flash coving. nora profix provides the following benefits:

- Odorless
- No necessary open time required
- Non-flammable and freeze/thaw stable
- Free of solvents, formaldehyde, asbestos, lindane, chlorinated biphenyls, pentachlorophenol, phthalates or other toxic substances
- GREENGUARD Gold certified for low VOC emissions
- In compliance with South Coast (CA) Air Quality Management District Rule 1168

profix™ 145	Art. 6650	5.71" wide x 164' long (145 mm x 50 m)
profix™ 90	Art. 993	3.54" wide x 164' long (90 mm x 50 m)
profix™ 50	Art. 992	1.97" wide x 164' long (50 mm x 50 m)

nora wet adhesives

nora® AC MR95™

Moisture-resistant acrylic adhesive

Easy-to-use, solvent free, water based acrylic adhesive able to resist high concrete relative humidity levels that has been specifically formulated for the installation of nora rubber floor coverings (2 mm – 4 mm).

- 95% humidity resistant
- High-bond strength
- Excellent for heavy traffic
- Non-flammable and freeze/thaw stable
- Free of organic solvents, formaldehyde, asbestos, lindane, rosins, phthalates or any other volatile components
- GREENGUARD Gold certified for low VOC emissions
- In compliance with South Coast (CA) Air Quality Management District Rule 1168

Art. 6694
4 gallon pail

nora® ED MR90™

Moisture-resistant conductive adhesive

Easy-to-use, wet set, conductive, water based acrylic adhesive that has been specifically formulated for the installation of nora ed rubber floor coverings (2 mm – 4 mm) on absorptive substrates.

- 90% humidity resistant
- High-bond strength
- Excellent for heavy traffic
- Non-flammable and freeze/thaw stable
- Free of organic solvents, formaldehyde, asbestos, lindane, rosins, plasticizers or any other volatile components
- In compliance with South Coast (CA) Air Quality Management District Rule 1168

Art. 6695
4 gallon pail

nora® PU MR95™

Moisture-resistant polyurethane adhesive

Two-component urethane adhesive designed specifically for the installation of specific nora rubber floor coverings on suitable substrates. When parts A & B are thoroughly mixed together, they form a reactive adhesive that cures to a tough, flexible film with a good resistance to surface moisture and many chemicals.

- 95% humidity resistant
- High-bond strength
- Non-flammable and freeze/thaw stable
- Free of organic solvents, formaldehyde, asbestos, lindane, rosins, phthalates or any other volatile components
- GREENGUARD Gold certified for low VOC emissions
- In compliance with South Coast (CA) Air Quality Management District Rule 1168

Art. 6696
1.5 gallon unit within a 2 gallon pail (Part A & B)

NOTE: Speak with your nora Sales Representative before selecting your adhesive to confirm the suitability for your project. Please refer to the nora Installation Instructions for proper installation methods of all nora products.


nora accessories

Accessory range made of rubber to suit nora floor coverings for convincing solutions both in visual and functional terms. The materials are impact- and shock-resistant, do not contain any phthalate plasticizers and retain their functional reliability long term.


nora® sanitary base

Easy to clean, suitable for areas with stringent hygienic requirements.



 28
Art. 817 — S 3019 D
Piece Length: ~32.81' (10.0 m)
*Conforms to ASTM-F-1861— Standard Specification for Resilient Wall Base, Type TP: Thermoplastic Rubber, Group 1

2409	5111	6504	7036
2780	5303	6505	7040
2787	5304	6506	7041
2930	5306	6509	7046
2944	5309	6524	7049
2945	5310	6528	7052
2963	5319	7035	7062




For floor covering thicknesses from ~.12" to ~.14" (3.0 to 3.5mm)

nora® wall base


The final touch to complete your flooring design.

nora wall base provides superb flexibility, no color drifts, a ribbed backing and reinforced cove for extraordinary durability.



 20
Art. 820
Delivery unit: rolls of 120'

6267	6233	6211	6254
6232	6205	6201	6240
6246	6286	6235	6214
6298	6266	6202	6248
6204	6229	6294	6249



nora wall base is intended to complement our floor coverings and will not match exact color due to variation in product recipes and production batches. Please do not specify or order solely using color names as a guide to color, as names are often shared across multiple products. We recommend ordering samples of each product prior to selection for the best results. Custom color matching is available.

nora® cold weld



It is recommended to weld joints in rooms permanently undergoing intensive wet cleaning or in areas with special hygienic requirements. For these special applications, welding of all norament and noraplan rubber flooring is recommended, with the exception of norament 992/992 grano.


Art. 928
10 fl. oz. (300 ml)
~50-60 linear feet per tube

Joint cutters, spatulas and cold weld tape available for order.

0007	2382	5105	5130	5352	6501	6525	6715	7050	7074
0131	2452	5106	5131	5353	6502	6526	6716	7051	7075
0319	2454	5107	5132	5354	6503	6527	6720	7052	7076
0702	2457	5108	5301	5355	6504	6528	6721	7053	7077
0716	2666	5109	5302	5356	6505	6529	6722	7054	7078
0733	2681	5110	5303	5357	6506	6530	7031	7055	7108
0749	2781	5111	5304	5358	6507	6531	7032	7056	7171
0882	2786	5112	5305	5363	6508	6532	7033	7057	7175
0884	2787	5113	5306	5364	6509	6533	7034	7058	7176
1146	2848	5114	5307	5367	6510	6534	7035	7059	
1150	2897	5115	5308	5368	6511	6535	7036	7060	
1253	2931	5116	5310	5508	6512	6536	7037	7061	
1254	2932	5117	5311	5509	6513	6537	7038	7062	
1279	2940	5118	5313	5512	6514	6601	7039	7063	
1299	2944	5119	5314	5513	6515	6603	7040	7064	
1385	2946	5120	5315	6009	6516	6613	7041	7065	
1578	2951	5121	5317	6016	6517	6620	7042	7066	
1581	2962	5122	5318	6129	6518	6621	7043	7067	
1582	4877	5124	5319	6172	6519	6624	7044	7068	
1585	4881	5125	5321	6178	6520	6703	7045	7069	
2070	5101	5126	5325	6179	6521	6708	7046	7070	
2142	5102	5127	5329	6325	6522	6709	7047	7071	
2226	5103	5128	5343	6449	6523	6713	7048	7072	
2306	5104	5129	5351	6500	6524	6714	7049	7073	

nora® heat weld

Matching welding rod can be delivered for all noraplan colors.



noraplan floors do not need to be welded, with the exception of noraplan acoustic, which does require welding due to its resilient structure.

nora heat welding is recommended when the nora flooring has been installed in rooms with continual and intensive wet cleaning, in areas with stringent requirements for hygiene or other special requirements such as operating rooms and laboratories.

Art. 946
Round, approx. .16" (4.0 mm)
Rolls of ~328 linear feet (100 linear meters)
Weight per roll ~3.0 lbs (1.3 kilograms)

nora pro clean™ system

A scrubber, nora® Pads and water is all you need.

The nora pro clean system eliminates the need to use harsh, unfriendly cleaning detergents on your nora® rubber flooring. The combination of nora's unique, dense, non-porous and dirt-repellent surface, water and our exclusive nora Pads provides a more cost-effective and sustainable cleaning solution. The continuous use of this system will make your nora flooring more resistant to scuffs and staining over time.

The key to the nora pro clean system is the nora Pads. For use only on nora rubber flooring, these exclusive pads are designed for all levels of maintenance needs, from the periodic cleaning of small spaces to the more intense post-installation or initial maintenance cleaning.

nora Pads will take you from post-installation maintenance, enhanced shine, daily maintenance, and periodic maintenance through your toughest cleaning challenges.



nora® Pads

nora pro clean pads are designed for post-installation, daily, periodic maintenance and enhanced shine on select nora rubber floor coverings. nora pro clean pads can be used with most standard types of cleaning equipment such as floor scrubbers and automatic floor scrubbers that are available in different sizes with 4 pads to a box.

nora Pad 0 is used for post installation (depending on amount of soil), daily and periodic maintenance and enhanced shine on select nora floor coverings.

	Art. 6502
nora Pad 0 — 20"	Material # 502355
nora Pad 0 — 17"	Material # 502354
nora Pad 0 — 16"	Material # 502353
nora Pad 0 — 14"	Material # 502352
nora Pad 0 — 13"	Material # 502351
nora Pad 0 — 12"	Material # 502350

nora pad 1 is used for periodic maintenance (depending on amount of soil) and enhanced shine on select nora floor coverings.

	Art. 6502
nora Pad 1 — 20"	Material # 501700
nora Pad 1 — 17"	Material # 501704
nora Pad 1 — 16"	Material # 502090
nora Pad 1 — 14"	Material # 501707
nora Pad 1 — 13"	Material # 501709
nora Pad 1 — 12"	Material # 502089

nora pad 2 is used for intensive cleaning (depending on amount of soil), and minor scratch repair (restoration) on select nora floor coverings. When using nora pad 2, you must follow up with enhanced shine protocol.

	Art. 6502
nora Pad 2 — 20"	Material # 501701
nora Pad 2 — 17"	Material # 501705
nora Pad 2 — 14"	Material # 501708
nora Pad 2 — 13"	Material # 501710

nora pad 3 is used for intensive cleaning and minor scratch repair (restoration) on select nora floor coverings. When using nora pad 3, you must follow up with enhanced shine protocol.

	Art. 6502
nora Pad 3 — 20"	Material # 501702
nora Pad 3 — 17"	Material # 501706

Contact the nora® Maintenance Department for instructions, including product suitability and usage.

nora® pro steamer™

Your occupied spaces,
deep cleaned with steam.

The quiet, non-disruptive cleaning power of steam gives you the ability to deep clean smaller spaces and hard to reach areas while still supporting a calming healing environment. Using only distilled water to create superheated dry steam – your patients will breathe easy and enjoy an improved experience in their clean surroundings.

nora pro steamer	Art. 6690
nora pro steamer Bottle	Art. 6692
nora pro steamer Pad	Art. 502541





nora services

nora services

You need more than a flooring vendor, you need a partner.


From design to post installation, Interface + nora have experts and tools to support your project at every step. And we can even be a valued resource for your organization's sustainability mission.

Your Design Partner

We make finding design solutions easier with Interface Design Studio--expert designers who know Interface + nora products inside and out. And it's complimentary. From concept to completion, they can work closely with you to create distinct designs that meet your vision and budget, no matter how large or small the project.

nora Technical Services

Whether you're a professional installer or a facilities manager, our experts are available for consultations before, during and after flooring installation. Our range of services - from detailed, hands-on training in the nora Technical Academy to comprehensive maintenance plans - deliver the tools for a successful installation, a greater return on investment and lower total cost of ownership.



Room Designer


Experience it in your project's room



nora Room Designer

- See how it looks in a real room:
- Use a sample room from the vast collection
 - Or upload a room image from your project
 - The software automatically recognizes the floor area
 - Print, save or share your visual experience with others

Experience how the selected floor will look in your project
www.nora.com/united-states/en/resources



Building Information Modeling (BIM)

Building Information Modeling (BIM) is a software-supported method used to optimize the planning, construction and management of buildings. All relevant material and building data is digitally captured, managed, combined and cross-linked. This information can be used throughout the entire life cycle of a building, starting with

the documentation of planning, through cost and project management to building operation.



We offer BIM files of the floor covering and stair tread standard portfolio for download on our website. Further information can be found at bim.nora.com



nora® by Interface®

Limited Warranty – Americas

nora systems, Inc. (nora) warrants the following nora® brand products (collectively, the “Warranted nora Brand Flooring Products”) as set forth below: norament® and noraplan® rubber flooring, norament® rubber stairtread (excluding visually impaired strips), accessories (excluding visually impaired strips), nora® nTx™ 020 bond enhancer and adhesives, and the conductivity of its Electrostatic Dissipative (“ESD”) flooring system (norament® ed and noraplan® ed flooring and adhesive).

nora Brand Flooring Products

- The Warranted nora Brand Flooring Products listed in the table below are warranted to the original end-use customer, for the period of time indicated in the table below, against blemishes and excessive wear due to normal traffic, provided the material was installed and maintained properly and strictly in accordance with the applicable nora Installation Instructions and Maintenance Guidelines, which can be found on the nora.com website and used as intended and recommended. For these purposes, “excessive wear” is defined as wear in excess of the following measurements: norament® products and norament® stairtreads, 0.0375” total; noraplan® products, 0.0525” total. All warranty claims must be made by the customer before the end of the time period stated in chart below; and
- The conductivity of ESD flooring system products are warranted to the original end-use customer for a period of 10 years from the date of invoice, provided the material was installed with nora’s conductive adhesive (acrylic or polyurethane), when tested according to the test procedures of ESD S7.1-94 and ASTM-F-150 under >30% relative humidity at room temperature to measure between 10⁶ and 10⁹ OHMS. All warranty claims must be made by the customer within the established 10-year period; and
- Installations of all Warranted nora Brand Flooring Products must be completed strictly in accordance with the applicable nora Installation Instructions, which can be found on the nora.com website. In all installations, there must be no visible moisture on the surface of the concrete slab. Written and photographic evidence showing moisture and mat bond test results must be maintained by the original end-use customer.

Product	Blemish and Excessive wear warranty period (years from date of invoice)
nora® stair nosing, wall base, sanitary base	5
noraplan® / noraplan nTx™: linee™, lona™	5
norament® stairtreads (exclusive of the visually impaired strips)	15
norament, norament nTx™, norament ed	15
noraplan, noraplan nTx™, noraplan acoustic, noraplan ed	15

If nora determines that a product is covered by this limited warranty, nora will correct the problem in the affected area by either repair or replacement with comparable product(s), at nora’s option, at no charge to the customer.

nora also warrants the Warranted nora Brand Flooring Products to the original end-use customer against defects arising out of the manufacturing process as stated below:

- If the product is determined to exhibit a manufacturing defect and the customer has made a warranty claim to nora within the first year following the date of invoice, nora will correct the problem in the affected area either (at nora’s option) by repair or replacement with comparable product(s) at no charge to the customer, as well as pay the reasonable labor costs (as determined by nora) associated with its repair or replacement;
- If the product is determined to exhibit a manufacturing defect and the customer has made a warranty claim to nora in the second year following the date of invoice, nora will correct the problem in the affected area either (at nora’s option) by repair or replacement with comparable product(s) at no charge to the customer, as well as pay fifty percent (50%) of the reasonable labor costs (as determined by nora) associated with its repair or replacement; and
- If the product is determined to exhibit a manufacturing defect and the customer has made a warranty claim to nora in the third, fourth, or fifth years following the date of invoice, nora will correct the problem in the affected area either (at nora’s option) by repair or replacement with comparable product(s) at no charge to the customer but will not be responsible for any labor costs associated with its repair or replacement.

nora Adhesive Products

As stated below, nora warrants to the original end-use customer that the following adhesives are free of manufacturing defects: nora® AC 100™, ED 120™, PU 102™, AC MR95™, ED MR90™, and PU MR95™, stepfix 240™, profix™, and nora dryfix™ 750, and nora dryfix™ ed and nora dryfix™ mr.

If the adhesive is determined to exhibit a manufacturing defect and the customer has made a warranty claim to nora within the first year following the date of invoice, nora will correct the problem in the affected area either (at nora’s option) by repair or replacement with comparable product(s) at no charge to the customer, as well as pay the reasonable labor costs (as determined by nora) associated with its repair or replacement.

nora dryfix mr Bond Warranty

nora hereby represents and warrants for a period of the ten (10) years as from the date of invoice that nora dryfix mr shall not delaminate due to slab relative humidity of less than 99% when tested in accordance with ASTM F2170 “Standard Test Method for Determining Relative Humidity in Concrete Floor Slabs Using in situ Probes” provided that the installation is compliant with ASTM F710, the nora installation instructions, that storage of the material prior to installation is in accordance with the product data sheet and shelf-life of the material is not expired at time of installation.

nora Warranty Limitations

In all cases in which a covered warranty condition is determined by nora to exist, the customer must provide reasonable cooperation to facilitate nora’s repair or replacement in the affected area. This warranty shall apply to standard Americas (AMS) nora brand flooring products; products sold in Europe, Africa, Asia and Australia (EAAA) shall be covered under the EAAA nora brand products warranty. Please contact your local representative with any inquiries.

This warranty does not cover cuts, loss of gloss, burns, scratches, indentations, stains or other damage, deterioration, problems, or loss caused by abuse, neglect, misuse, improper installation, improper maintenance, flood, or subfloor irregularities. This warranty does not cover fading or discoloration from prolonged, excessive exposure to sunlight or heat. Moisture testing, when applicable, at the installation site is not the responsibility of nora, and issues, problems or damage related to or arising from excessive moisture are specifically excluded from this warranty except as expressly set forth herein and in the applicable nora Installation Instructions and Maintenance Guidelines. This warranty does not cover any issues, problems or damages arising from or related to installation techniques or conditions not strictly meeting the requirements in the applicable Installation Instructions.

nora does not warrant installer’s workmanship unless the affected product was installed by nora affiliate Interface Services, Inc., (Interface Services), and then only in accordance with the terms of the Interface Services installation warranty.

Warranty claims must be made in writing to nora within the time frames indicated herein. Warranty claims must be addressed to: nora systems, Inc., Technical Operations Department, 9 Northeastern Blvd., Salem, NH 03079. Warranty claims must include contemporaneous documentation that all warranty conditions were and continue to be met. This warranty will be void if its terms are not followed. The customer must inspect all products, prior to installation, for patent defects and notify nora thereof, prior to installation; otherwise, this warranty will be void. No person other than an officer of nora may authorize a waiver or modification of the terms of this warranty, which must be in writing and signed by that officer.

This limited warranty and the applicable Installation Instructions and Maintenance Guidelines are subject to change at nora’s discretion and without notice. Please contact nora or visit the nora.com website for the latest versions. For additional information regarding usage in recommended applications, please refer to www.nora.com or call 1-800-332-NORA. Warranty periods commence on the date of invoice of the product to the original end-use customer.

The warranties herein are only made to the original end-use customer and no other parties. The remedies stated herein are the sole and exclusive remedies of the original end-use customer and the sole and exclusive liability of nora and its affiliates.

THE WARRANTY, REMEDY AND LIMITS OF LIABILITY CONTAINED HEREIN ARE EXPRESSLY IN LIEU OF AND EXCLUDE ALL OTHER WARRANTIES, REMEDIES AND LIABILITIES, WHETHER EXPRESS OR IMPLIED. NORA MAKES NO OTHER REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, AND HEREBY DISCLAIMS ANY AND ALL OTHER WARRANTIES THAT MAY ARISE BY OPERATION OF LAW, INCLUDING, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS OF ITS PRODUCTS FOR ANY PARTICULAR PURPOSES. NOTE THAT SOME JURISDICTIONS DO NOT PERMIT DISCLAIMERS OF SOME IMPLIED WARRANTIES, SO YOUR RIGHTS MAY BE DIFFERENT THAN STATED HEREIN. IN NO EVENT WILL NORA BE LIABLE FOR ANY INCIDENTAL, INDIRECT, SPECIAL, PUNITIVE, OR CONSEQUENTIAL DAMAGES OR LOSS OF USE, LOSS OF BUSINESS, LOST PROFITS OR REVENUES OR DIMINUTION IN VALUE REGARDLESS OF (A) WHETHER SUCH DAMAGES WERE FORESEEABLE, (B) WHETHER NORA OR ITS AFFILIATES WERE ADVISED OF THE POSSIBILITY OF SUCH DAMAGES OR (C) THE LEGAL OR EQUITABLE THEORY (CONTRACT, TORT OR OTHERWISE) UPON WHICH THE CLAIM IS BASED, AND NOTWITHSTANDING THE FAILURE OF ANY AGREED OR OTHER REMEDY OF ITS ESSENTIAL PURPOSE.

nora®, norament®, and noraplan® are trademarks owned by nora systems GmbH and registered in the United States, Canada, and other countries. All other trademarks are the property of their respective owners.

Supersedes all previous information. Effective October 5, 2023.

nora[®] by Interface[®]

nora[®] nTx Warranty – Americas

Warranty Coverage

nora systems, Inc. (“nora”), warrants nora[®] nTx when used in conjunction with nora[®] nTx 020), including the bond and resistance to moisture and/ or high alkalinity for a period of (10) ten years from the date of purchase by the buyer and/or end user, whichever is first, provided all nora nTx and nora nTx storage, preparation, installation and usage directions are followed.

nora will repair or replace defective areas of the nora nTx and pay the reasonable labor and material costs to remove, repair or replace the defective areas of the nora nTx, provided the buyer or end user complies with the terms of this limited warranty. nora nTx must be applied in strict accordance with nora’s written nora[®] nTx Installation Guide. Please contact nora systems, Inc. for the current version or go to www.nora.com/us website, as it is subject to change.

EXCEPT FOR THE LIMITED WARRANTIES SET FORTH HEREIN, NORA EXTENDS NO OTHER WARRANTIES OR GUARANTEES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR EXACT MATCHING OF SHADE, COLOR OR MOTTLING. NORA HEREBY DISCLAIMS ANY OTHER WARRANTY OR GUARANTEE UNLESS EXPRESSLY AUTHORIZED AND ENDORSED IN WRITING AS SET FORTH BELOW.

No agent, employee or representative of nora is authorized to make any warranty or guarantee concerning the products. Any alteration, amendment or waiver of this nora nTx limited warranty must be in writing and signed by an officer of nora.

Exclusions from Warranty Coverage

nora hereby disclaims any warranty coverage arising from the following; concrete slabs that have ASR (Alkali Silica Reaction) present, hydrostatic pressure, structural failure, inadequate sub-floor, or improper sub-floor preparation including failure to remove any bond breaking contaminants; damages caused by Acts of God, including, but not limited to hurricane, flooding, earthquake or other types of natural disaster, or as a result of unforeseen circumstances; acts of negligence, or product misuse or abuse, damage by a third party; failure to comply with our nora nTx Installation Guide and any other written instructions, applicable building codes and regulations, and other standard industry practices; variations of color, shade or texture from those shown on samples, product packaging or any other marketing materials; any changes due to exposure to sunlight and age; normal wear and tear resulting from usage; efflorescence and shading inherent in all cementitious products; and cracking due to structural movement after application, excessive deflection or other failure of the substrate.

Notice of Claims

To make a claim under any warranty, the buyer or end user must provide written notice to nora systems, Inc. at 9 Northeastern Blvd., Salem, NH 03079, within 30 days of discovery of any alleged defect of the product. nora must be given the opportunity to inspect and examine the product prior to buyer or end user repairing or replacing the defective product.

Limitation of Liability; Indemnity

nora will not be directly or indirectly liable for any other losses, claims or damages in excess of the cost of the products invoiced by nora and reasonable labor costs. nora shall not be liable for any consequential, incidental, enhanced or punitive damages whatsoever, whether arising out of breach of contract, warranty, tort, (including negligence and strict liability) or other theories of law with respect to goods and/or services sold by nora or any undertakings, acts, or omissions relating thereto, and nora hereby disclaims all such damages. Buyer shall indemnify nora against any and all losses, liabilities, damages and expenses (including, without limitation, attorneys’ fees and other costs of defense) which nora may incur as a result of any claim by buyer or others arising out of or in connection with the goods and/or services sold hereunder and based on product or service defects not proven to have been caused solely by nora’s negligence.

Governing Law; Venue

The rights and obligations of the parties hereto and the interpretation, construction and effect of any provision hereof or any contract formed pursuant hereto shall be governed by and construed in accordance with the laws of the state of New Hampshire, without reference to its conflict of law rules.

Supersedes all previous information. Effective February 2020.

nora[®] by Interface[®]

nora[®] pro steamer Warranty – Americas

Limited Product Warranty

nora systems, Inc. (“nora”), warrants its nora[®] pro steamer (the “Product“) to the original purchaser (the “Purchaser“) to be free from defects in material or workmanship for a period of one (1) year from the date of purchase from nora when used in accordance with nora’s Instruction Guide. If (i) nora is notified within the limited warranty period of any such defect as specified below and if (ii) the Purchaser has used the Product under normal use and in strict conformity with the Instruction Guide provided by nora, then nora, at its sole discretion, will use commercially reasonable efforts to repair or replace that portion of the Product found by nora to be defective in material or workmanship at no cost to the Purchaser (except for shipping and transportation costs associated with returning the Product to nora) or refund the purchase price of the Product or replace the Product or a portion of same if Product is returned to nora, freight and postage costs must be prepaid by the Purchaser. Repairs not covered by the warranty or outside the warranty period will require a fee determined by nora to cover the cost of repairs, labor, handling and shipping.

This warranty does not apply to defects, damage or loss caused in whole or in part by (i) abuse, modification, alteration, misuse or tampering of the Product, (ii) failure to strictly comply with nora’s Instruction Guide, (iii) use on any surface other than nora rubber flooring, (iv) lack of proper maintenance or (v) normal wear and tear. Repair or service of the Product by anyone other than nora systems, Inc. or its authorized representatives shall void this warranty.

EXCEPT FOR THE LIMITED WARRANTIES SET FORTH HEREIN, NORA EXTENDS NO OTHER WARRANTIES OR GUARANTEES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. REPAIR OR REPLACEMENT AS PROVIDED UNDER THIS WARRANTY IS THE EXCLUSIVE REMEDY OF THE CONSUMER OR PURCHASER. NORA SHALL NOT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES FOR BREACH OF ANY EXPRESS OR IMPLIED WARRANTY ON THIS PRODUCT. NORA HEREBY DISCLAIMS ANY OTHER WARRANTY OR GUARANTEE UNLESS EXPRESSLY AUTHORIZED AND ENDORSED IN WRITING AS SET FORTH BELOW.

nora’s maximum liability whether in tort, contract, or otherwise shall be the cost of the Product invoiced by nora.

No agent, employee or representative of nora is authorized to make any warranty or guarantee concerning the Product. Any alteration, amendment or waiver of this One-Year Limited Warranty must be in writing and signed by an officer of nora.

Limitation of Liability

nora shall not be directly or indirectly liable for any losses, claims or damages in connection with any use of nora pro steamer(s) that does not strictly comply with nora’s Instruction Guide, that was directly or indirectly caused by a third party, that was improperly repaired, or that was affected by any other mechanical influences. Please contact nora for the latest warranty versions. For additional information, please call 1-800-332-NORA.

It is understood that certain parts of the Product are not covered by this One-Year Limited Warranty due to the fact that they require replacement after multiple use. Such parts will eventually require replacement at the Purchaser’s cost and are explicitly excluded from this warranty.

nora shall not be liable for any losses, claims, or damages in excess of the cost of the Product invoiced by nora. nora shall not be liable for any incidental, consequential, enhanced or punitive damages.

Warranty for other conditions supplied upon request.

This warranty is to solely benefit the original purchaser of the Product. The warranty is not transferable beyond the original purchaser.

nora makes no warranty or representation that the Product complies with any local laws, rules or regulations and the original purchaser shall be responsible for obtaining all permits or authorizations required by any regulatory body for installation or use of the Product.

Notice of Claims

To make a claim under this One-Year Limited Warranty the original purchaser must provide written notice to nora systems, Inc. at 9 Northeastern Blvd., Salem, NH 03079, within thirty (30) days of discovery of any alleged defect of the Product. nora systems, Inc., must be given the opportunity to inspect and examine the Product.

Supersedes all previous information. Effective February 2020.

norament®

											Stairtreads		
Product	arago™, arago™ nTx™	castello™, grano™, pado™, satura™, grano™ nTx™, satura™ nTx™	grano ed	hammered	kivo™	825 round	xp™, xp™ nTx™	xp trac™, xp trac™ nTx™	920	992, 992 grano™	arago, grano, satura	round, hammered	920
ASTM F1344 Rubber Floor Tile	Type IB Grade 2	Type IB Grade 2	Type IB Grade 2	Type IA Grade 1	Type IB Grade 2	Type IA Grade 1	Type IB Grade 1	Type IB Grade 1	Type IA Grade 1	992: Type IIA 992 grano: Type IIB Grade 2	–	–	–
ASTM F2169 Resilient Stair Treads	–	–	–	–	–	–	–	–	–	–	Type TS Class 2 Group 1 or 2 Grade 2	Type TS Class 2 Group 1 or 2 Grade 2	Type TS Class 2 Group 1 or 2 Grade 1
Limited Warranty/years	15	15	15	15	15	15	15	15	15	15	15	15	15
nTx Bond Warranty/years	10	10	–	–	–	–	10	10	–	–	–	–	–
Conductivity Warranty/years	–	–	10	–	–	–	–	–	–	–	–	–	–
Flammability (E648/NFPA 253): ≥ 0.45 watts/sq cm for Class 1 required	Class 1 0.94 nTx: 0.98	Class 1 0.94 nTx: 0.97	Class 1 0.58	Class 1 0.87	Class 1 1.1	Class 1 0.80	Class 1 0.71 nTx: 0.54	Class 1 0.68	Class 1 0.94	Class 1 0.56	Class 1 1.0	Class 1 1.1	Class 1 0.94
Smoke Density (ASTM E662): < 450 required	296/16 nTx: 369/205	296/16 nTx: 346/145	418/285	162/208	231/234	413/367	197/36 nTx: 422/201	372/284	272/167	289/373	296/16	380/230	272/167
Tunnel Test (ASTM E84): flame/smoke	**	**	**	**	**	**	**	**	Class A 15/300	**	**	**	Class A 15/300
CAN/ULC-S102.2: Surface Burning for FSC1/SD	Contact the nora® Technical Department or refer to the nora® Guide Specification for details.												
Slip Resistance (ASTM D2047): ≥ 0.5 required	0.81/0.87	castello/pado: 0.87/0.93 grano/satura: 0.99/0.95	1.0/0.90	0.90/1.0	0.87/0.93	0.76/0.85	0.90/1.0	.99/98	0.85/0.76	0.93/0.93	arago: 0.81/0.87 0.99/0.95	round: 0.85/0.76 hammered 0.99/0.95	0.85/0.76
Bacteria Resistance (ASTM E2180/ASTM G21)	Resistant to bacteria, fungi, and micro-organism activity												
Latex Allergies (ASTM D6499)	Inhibition , results are below detection level												
Sound Absorption (ASTM E2179): compare ΔIIC values only	ΔIIC 18	ΔIIC 18	ΔIIC 15	ΔIIC 16	ΔIIC 13	ΔIIC 16	ΔIIC 14	ΔIIC 14	ΔIIC 18	**	**	**	**
Sound Absorption (ISO 10140-3): compare ΔLw values only	ΔLw 10 dB	ΔLw 11 dB	ΔLw 15 dB	ΔLw 9 dB	ΔLw 11 dB	ΔLw12 dB	**	**	ΔLw 13 dB	ΔLw 17 dB	**	**	**
Hardness (ASTM D2240): Shore Type A	82	82	84	89	82	89	89	89	91	77	82	82	91
Static Load (ASTM F970): with 800 lbs/psi ≤ 0.005 in with 250 lbs required	0.004	0.005	0.004	0.005	0.005	0.004	0.002	0.005	0.005	0.004	0.005	0.005	0.005
Rolling Load Limit (ASTM F2753): lbs/psi (1)	850	850	850	550	850	550	850	850	850	850	–	–	–
Forklift Traffic	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes	Yes	–	–	–

norament® (continued)

											Stairtreads		
Product	arago™, arago™ nTx™	castello™, grano™, pado™, satura™, grano™ nTx™, satura™ nTx™	grano ed	hammered	kivo™	825 round	xp™, xp™ nTx™	xp trac™, xp trac™ nTx™	920	992, 992 grano™	arago, grano, satura	round, hammered	920
Abrasion Resistance (ASTM D3389): H-18 Wheels 1.1 lb load and 1000 cycles ≤ 0.035 oz (1.0 g) required	0.008	0.002	0.004	0.006	0.002	0.005	0.005	0.005	0.007	0.005	arago: 0.006 0.002	round: 0.005 hammered: 0.006	0.007
Oil & Grease Resistance (ISO 26987)	Yes	Yes	Yes	No	Yes	No	No	No	Yes	Yes	Yes	Yes	Yes
Heat Resistance (ASTM F1514): Avg. ΔE ≤ 8.0 required	Easily achieved with all batches and regular maintenance.												
Static Generation (AATCC 134): 20% RH	< 1000 volts	< 1000 volts	–	< 1000 volts	< 1000 volts	< 1000 volts	< 1000 volts	< 1000 volts	< 1000 volts	< 1000 volts	< 1000 volts	< 1000 volts	< 1000 volts
Static Generation (ANSI ESD S97.2)*	–	–	< 20 volts	–	–	–	–	–	–	–	–	–	–
Conductivity (ASTM F150): ohms	–	–	10 ⁶ < 10 ⁹	–	–	–	–	–	–	–	–	–	–
Thermal Transmission (ASTM C518): R-value	-0.90	-0.90	**	**	**	**	**	**	**	**	**	**	**
Embodied Carbon (Gradle to Gate)	17.2 kg CO ₂ e/m³	17.2 kg CO ₂ e/m³	21.0 kg CO ₂ e/m³	-	17.2 kg CO ₂ e/m³	-	-	-	-	-	17.2 kg CO ₂ e/m³	17.2 kg CO ₂ e/m³	-
Full Life Cycle Carbon Emissions	3rd party certified carbon neutral throughout their entire life cycle through the Interface Carbon Neutral Floors™ program. Learn more at www.interface.com/carbonneutral												
Total Recycled Content (Pre Consumer)	-	-	-	-	-	-	-	-	-	11%	-	-	-
Indoor Air Quality	GREENGUARD Gold Certified for low VOC Emissions in compliance with CDPH 01350												
Disclosure of Environmental Impacts (EPD)	Yes	Yes	Yes	No	Yes	No	No	No	No	No	Yes	Yes	No
Disclosure of Product Ingredients (HPD)	Yes	Yes	Yes	No	Yes	No	No	No	No	No	Yes	Yes	No
Cradle to Cradle Certified® Silver	Yes	Yes	No	No	Yes	No	No	No	No	No	Yes	Yes	No
Greenhealth Approved	Yes	Yes	No	No	Yes	No	No	No	No	No	Yes	Yes	No
LEED v4	Refer to the nora® Guide Specification for details.												

(1) Wheel Types: No metal or hard plastic wheels, the shape of the contact surface of wheels must be flat with round edges. The shore hardness must be Type A ≤ 90.

* Tested with conductive shoes

** Not tested

Note: Exact values may vary due to the test methods and tolerance between batches. The ASTM minimum requirement must be achieved or exceeded.

nora®, norament®, and noraplan® are trademarks owned by nora systems GmbH and registered in the United States, Canada, and other countries. All other trademarks are the property of their respective owners.

	2 mm: convia™, dariva™, environcare™, sentica™, environcare™ nTx™, sentica™ nTx™	3 mm: dariva, environcare, sentica, environcare nTx, sentica nTx	2 mm: unita™	2 mm/3 mm: valua™	4 mm acoustic: environcare, sentica	2 mm/3 mm ed: environcare, sentica
ASTM F1344 Rubber Floor Tile	Type I Grade 1 (excludes nTx)	Type I Grade 1 (excludes nTx)	–	Type I Grade 1	–	Type I Grade 1 (2 mm only)
ASTM F1859 Rubber Sheet Floor Without Backing	Type I	Type I	Type I	Type I	–	Type I
ASTM F1860 Rubber Sheet Floor With Backing	–	–	–	–	Type I Grade 2	–
Limited Warranty/years	15	15	15	5	15	15
nTx Bond Warranty/years	10	10	–	–	–	
Conductivity Warranty/years	–	–	–	–	–	10
Flammability (E648/NFPA 253): ≥ 0.45 watts/sq cm for Class 1 required	Class 1 0.97 nTx: 0.83	Class 1 1.03 nTx: 0.82	Class 1 0.82	Class 1 2 mm: 0.98 3 mm: 1.08	Class 1 1.08	Class 1 1.0
Smoke Density (ASTM E662): < 450 required	70/41 nTx: 185/97	376/256 nTx: 282/155	216/315	2 mm: 134/109 3 mm: 360/203	299/153	2 mm: 81/122 3 mm: 352/342
CAN/ULC-S102.2: Surface Burning for FSC1/SD	Contact the nora® Technical Department or refer to the nora® Guide Specification for details.					
Slip Resistance (ASTM D2047): ≥ 0.5 required	0.93/0.90	0.93/0.91	0.84/079	0.97/0.85	1.0/0.90	0.92/0.89
Bacteria Resistance (ASTM E2180/ASTM G21)	Resistant to bacteria, fungi, and micro-organism activity					
Latex Allergies (ASTM D6499)	Inhibition ELISA, results are below detection level					
Sound Absorption (ASTM E2179): compare ΔIIC values only	ΔIIC 12	ΔIIC 13	ΔIIC 12	2 mm: ΔLw 12 dB 3 mm: ΔLw 13 dB	ΔIIC 23	ΔIIC 10
Sound Absorption (ISO 10140-3): compare ΔLw values only	ΔLw 8 dB	ΔLw 10 dB	ΔLw 8 dB	2 mm: ΔLw 8 dB (2 mm) 3 mm: ΔLw 10 dB	ΔLw 20 dB	2 mm: ΔLw 6 dB 3 mm: ΔLw 10 dB
Hardness (ASTM D2240): Shore Type A	92	92	92	92	92	92
Static Load (ASTM F970): with 800 lbs/psi ≤ 0.005 in with 250 lbs required	0.003 nTx: 0.002	0.003	0.003	2 mm: 0.002 3 mm: 0.003	0.003	0.003
Rolling Load Limit: lbs/psi (1)	450	550	450	2 mm: 450 3 mm: 550	450	2 mm: 450 3 mm: 550
Forklift Traffic	No	No	No	No	No	No
Abrasion Resistance (ASTM D3389): H-18 Wheels 1.1 lb load and 1000 cycles ≤ 0.035 oz (1.0 g) required	0.008	0.003	0.008	0.006	0.007	2 mm: 0.002 3 mm: 0.003

noraplan® (continued)

	2 mm: convia™, dariva™, environcare™, sentica™, environcare™ nTx™, sentica™ nTx™	3 mm: dariva, environcare, sentica, environcare nTx, sentica nTx	2 mm: unita™	2 mm/3 mm: valua™	4 mm acoustic: environcare, sentica	2 mm/3 mm ed: environcare, sentica
Oil & Grease Resistance (ISO 26987)	No	No	No	No	No	Yes
Heat Resistance (ASTM F1514): Avg. ΔE ≤ 8.0 required	Easily achieved with all batches and regular maintenance.					
Static Generation (AATCC 134): 20% RH	< 1000 volts	< 1000 volts	< 1000 volts	< 1000 volts	< 1000 volts	–
Static Generation (ANSI ESD S97.2)*	–	–	–	–	–	< 20 volts
Conductivity (ASTM F150): ohms	–	–	–	–	–	10 ⁶ < 10 ⁹
Thermal Transmission (ASTM C518): R-value	0.04	0.04	0.04	0.04	0.20	2 mm: 0.01 3 mm: 0.04
Embodied Carbon (Gradle to Gate)	5.87 kg CO ₂ e/m³	-	5.87 kg CO ₂ e/m³	2 mm: 5.87 kg CO ₂ e/m³	8.5 kg CO ₂ e/m³	2 mm: 12.2 kg CO ₂ e/m³
Full Life Cycle Carbon Emissions	3rd party verified carbon neutral throughout their entire life cycle through the Interface Carbon Neutral Floors™ program. Learn more at www.interface.com/carbonneutral .					
Total Recycled Content (Pre Consumer)	-	-	-	-	29%	-
Indoor Air Quality	GREENGUARD Gold Certified; CDPH 01350 compliant					
Disclosure of Environmental Impacts (EPD)	Yes	Yes	Yes	Yes	Yes	Yes
Disclosure of Product Ingredients (HPD)	Yes	Yes	Yes	Yes	No	Yes
Cradle to Cradle Certified® Silver	Yes	Yes	Yes	Yes	No	No
Greenhealth Approved	Yes	Yes	Yes	Yes	No	No
LEED v4	Refer to the nora® Guide Specification for details					

(1) Wheel Types: No metal or hard plastic wheels, the shape of the contact surface of wheels must be flat with round edges. The shore hardness must be Type A ≤ 90.

* Tested with conductive shoes

** Not tested

Note: Exact values may vary due to the test methods and tolerance between batches. The ASTM minimum requirement must be achieved or exceeded.

nora®, norament®, and noraplan® are trademarks owned by nora systems GmbH and registered in the United States, Canada, and other countries. All other trademarks are the property of their respective owners.

