



# General Industrial Coatings

CC-M29

## MIL-DTL-53022F, Type IV, Class U HAPS Free, 0 Lbs./Gal. VOC Enhanced Corrosion Primer

Light Gray (Component A).....E90A229 Catalyst, Fast Cure (Component B).....V93V234

### DESCRIPTION

**MIL-DTL-53022F, Type IV, Class U** is a two component, 0 lb./gal. \*VOC, HAPS free compliant, lead and chromate free epoxy primer. It meets the MIL-DTL-53022F Type IV, Class U composition and performance specification. It may be used as a primer under polyurethane chemical agent resistant coatings (CARC) specified in MIL-DTL-53039 or MIL-DTL-64159. It may also be used under MIL-PRF-22750 epoxy topcoats and under MIL-PRF-85285 (non-aircraft) polyurethane topcoats.

#### Advantages:

- Meets all the performance properties of MIL-DTL-53022F, Type IV.
- Passes 30 cycles GMW 14872 and 1,008 hours ASTM B117 salt spray
- Excellent hardness
- Non Isocyanate
- Air or force dry cure
- Excellent chemical resistance
- Complies with 0 \*VOC solvent emissions.
- HAPS free
- Free of lead and chromate hazards

The following MIL-DTL-53022F, Type IV products are approved by the U.S. Army Research Lab, Aberdeen Proving Grounds, Aberdeen, MD:

Sherwin-Williams	QPD
E90A229	Q1915
V93V234	Q1915

\* VOC Compliance limits vary from state to state; please consult local Air Quality rules and regulations.

An Environmental Data Sheet is available from your local Sherwin-Williams facility or at [www.PaintDocs.Com](http://www.PaintDocs.Com).

### CHARACTERISTICS

**60° Gloss:** 10-45

#### Volume Solids:

E90A229	53.6 ± 2 %
V93V234	46.1 ± 2 %
Admixed	52.1 ± 2 %

#### Viscosity (at 77° F):

E90A229	70-90 Krebs Units
V93V234	16-24 secs., #2 Zahn Cup
Admixed	20-25 secs., #2 Zahn Cup

#### Recommended Film Thickness (unreduced):

Mils Wet	3.0-5.0
Mils Dry	1.5-2.5

**Spreading Rate** (no application loss):  
558 ft.<sup>2</sup>/gal. at 1.5 mil DFT

#### Cure:

Air Dry  
Force Dry 30 mins. flash, 30 mins. at 140° F

The force dry schedule above is provided as a guide. Wet film thickness, humidity, flash off time, part size and oven characteristics will all have an effect on drying and cure. Test for your specific application and line conditions.

**Substrate Disclaimer:** Curing of coating at temperatures higher than the heat distortion parameters of the substrate may cause substrate issues.

#### Drying:

(1.5 mils dry at 77° F, 50% RH)

To Touch	60 minutes
To Dry Hard	5 hours
Through-Dry	8 hours
To Recoat w/ Itself	30-60 minutes
To Coat w/ Topcoat	30-60 minutes
Total (Full Properties)	7-10 days

#### Mixing Ratio (by volume):

E90A229	4 Parts
V93V234	1 Part

Shake E90A229 well before using.

**Induction Time:** 30 minutes

**Potlife (at 77° F):** 4-6 hours

### Flash Point (Pensky Martens Closed Cup):

E90A229	10° F
V93V234	53° F
Admixed	10° F

### Air Quality Data:

Photochemically Reactive  
Volatile Organic Compounds  
(VOC, less exempt solvents, maximum):

E90A229	0 lbs./gal., 0 g/L
V93V234	0 lbs./gal., 0 g/L
Admixed	0 lbs./gal., 0 g/L

**Recommended Storage:** Inside, sealed container, 40-120° F, no freeze hazard. Protect from moisture.

**Package Life:** 2 years, unopened  
Inside storage

### SPECIFICATIONS

#### CLEANING & PRETREATMENTS

Follow the most current revisions of MIL-DTL-53072 and/or TT-C-490 for required cleaning and pretreatment application before coating.

**Note:** See the current MIL-DTL-53072 for complete details regarding substrate preparation, coatings, and application.

**General:** All substrates should be free of mold release, oil, grease, dirt, fingerprints, drawing compounds, surface passivation treatments and any other contaminants to ensure optimum adhesion and coating performance. For non-military uses, consult Metal Preparation brochure CC-T1 for additional details.

**Testing:** The information, data, and recommendations set forth in this Product Data Sheet are based upon test results believed to be reliable. However, due to the wide variety of substrates, substrate properties, surface preparation methods, equipment and tools, application methods, and environments, the customer should test the complete system for adhesion, compatibility and performance prior to full scale application.

## APPLICATION

### Typical Setups

**Reduction:** If required, use only HAPS free solvents as recommended by the manufacturer. For applications or regions where VOC or HAPS are not regulated reduction with R6K30 (MAK), R6K38 (TBAC) and R2KS1 (Oxsol 100) are recommended.

For all application and usage guidelines, please consult and review the MIL-DTL-53072 & TT-C-490 specifications as well as your local Sherwin-Williams representative.

**Cleanup:** Clean tools / equipment immediately after use with R6K9 (Acetone), R6K10 (MEK), R6K16 (MIBK), R6K30 (MAK) or other epoxy thinners such as R91K210 (MIL-DTL-81772C T2 Epoxy Reducer).

Follow manufacturer's safety recommendations when using any solvent.

## PRODUCT LIMITATIONS

1. **This product must be properly catalyzed before using. DO NOT VARY CATALYST RATIO.** The catalyst ratio has been established for optimum properties
2. Surface preparation is important for coating performance.
3. If parts have been primed for longer than 7 days, they must be sanded and recoated with a mist coat of E90A229 before topcoating for good adhesion.
4. Due to the wide variety of substrates, surface preparation methods, application methods, and environments, the customer should test the complete system for adhesion and compatibility prior to full scale application.
5. On sandblasted surfaces, apply sufficient film thickness to fully protect the blast profile. This is typically 1.5 mil more than the blast profile.

All trademarks are the property of their respective owners.

## CAUTIONS

### FOR INDUSTRIAL SHOP APPLICATION ONLY

**Thoroughly review the product label and Safety Data Sheet (SDS) for safety information and cautions prior to using this product.**

To obtain the most current version of the Environmental Data Sheet (EDS), Product Data Sheet (PDS), or Safety Data Sheet (SDS) please visit your local Sherwin-Williams facility or [www.PaintDocs.Com](http://www.PaintDocs.Com).

Please direct any questions or comments to your local Sherwin-Williams facility.

#### **Note:**

All purchases of products from Sherwin-Williams are exclusively subject to Sherwin-Williams' [Standard Terms And Conditions Of Sale](#). Please review these terms and conditions prior to the purchase of the products.

Sherwin-Williams warrants the product to be free of manufacturing defect in accordance with Sherwin-Williams' quality control procedures. Except for the preceding sentence, due to factors that are outside of Sherwin-Williams' control, including substrate selection, and customer handling, preparation, and application, Sherwin-Williams cannot make any other warranties related to the product or the performance of the product. **SHERWIN-WILLIAMS DISCLAIMS ALL WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTY OF MERCHANTABILITY, THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE.**

Liability for products proven to be defectively manufactured will be limited solely to replacement of the defective product or the refund of the purchase price paid for the defective product, as determined by Sherwin-Williams. Under no circumstances shall Sherwin-Williams be liable for indirect, special, incidental, or consequential damages, lost profits or punitive damages arising from any cause whatsoever.