ENVIRONMENTAL DATA SHEET

(Certified Product Data Sheet)

Date of Preparation

Jan 20, 2024

14 00 [0850]

PRODUCT NUMBER

GP3513A59

PRODUCT NAME

Resuflor™ 3513 Scratch Coat Mastic (Part A), White

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115

This document includes all data required by 40 CFR 63.801(a) for a Certified Product Data Sheet under criteria specified in 40 CFR 63.805(a). All data given below are MAXIMUM THEORETICAL VALUES based on the product AS CURRENTLY FORMULATED. Variations may occur on individual batches due to adjustments made during production.

Hazard Category (for SARA 311.312)

GP3513A59 = | Acute | Chronic |

 Product Weight
 Specific Gravity
 FLASH POINT

 8.08 lb/gal
 0.97
 > 200 °F PMCC

AS MIXED (as per product data sheet): catalyzed GP3513A59 with BP3513B61

AS MIXED

Product WeightSpecific GravityFLASH POINT8.25 lb/gal0.99N.A.

Volatile Ingredients

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Ethylbenzene 100-41-4	N	Υ	Υ	Υ	0.1	< 1
Phenylmethanol 100-51-6	N	N	N	N	7	7
Hexylene Glycol 107-41-5	N	N	N	N	2	2

Regulated Compounds

	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Copper Compound	N	N	Υ	Ν	10	

Volatile Ingredients AS MIXED

Chemical / Compound	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Phenylmethanol 100-51-6	N	N	N	N	3	3
Hexylene Glycol 107-41-5	N	N	N	N	2	2

Regulated Compounds AS MIXED

	SARA 302 EHS	CERCLA	SARA 313 TC	HAPS 112	% by Weight	% by Volume
Copper Compound	N	N	Υ	N	7	

Volatile Organic Compounds - U.S. EPA / Canada

	GP3	513A59	AS MIXED catalyzed GP3513A59 with BP3513B61		
	LB/Gal	g/L	LB/Gal	g/L	
Coating Density	8.08	968	8.25	988	
	By wt	By vol	By wt	By vol	
Total Volatiles	9.8%	9.5%	5.1%	5.1%	
Federally exempt solvents					
Water	0.0%	0.0%	0.0%	0.0%	
Organic Volatiles	9.8%	9.5%	5.1%	5.1%	
Percent Non-Volatile	90.2%	90.5%	94.9%	94.9%	
VOC Content	LB/Gal	g/L	LB/Gal	g/L	
Total	0.79	94	0.41	50	
Less exempt solvents	0.79	94	0.41	50	
Of solids	0.87	104	0.44	52	
Of solids	0.10 lb/lb	0.10 kg/kg	0.05 lb/lb	0.05 kg/kg	
	By wt		By wt		
By wt LVP-VOC	0.6%		0.4%		

Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) **1.61**AS MIXED Maximum Incremental Reactivity (MIR) (per US EPA Aerosol Ctg Rule, MIR Values 2009) **0.71**

Volatile Organic Compounds - California

	GP3	513A59	AS MIXED catalyzed GP3513A59 with BP3513B61		
	LB/Gal	g/L	LB/Gal	g/L	
Coating Density	8.08	968	8.25	988	
	By wt	By vol	By wt	By vol	
Total Volatiles	9.8%	9.5%	5.1%	5.1%	
Exempt solvents					
Water	0.0%	0.0%	0.0%	0.0%	
Organic Volatiles	9.8%	9.5%	5.1%	5.1%	
Percent Non-Volatile	90.2%	90.5%	94.9%	94.9%	
VOC Content	LB/Gal	g/L	LB/Gal	g/L	
Total	0.79	94	0.41	50	
Less exempt solvents	0.79	94	0.41	50	
Of solids	0.87	104	0.44	52	
Of solids	0.10 lb/lb	0.10 kg/kg	0.05 lb/lb	0.05 kg/kg	
	By wt		By wt		
By wt LVP-VOC	0.6%		0.4%		

Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) **0.42**AS MIXED Maximum Incremental Reactivity (MIR) (per California Air Resources Board Aerosol Products Regulation, MIR Values 2010) **0.19**

Volatile Organic Compounds - South Coast Air Quality Management District, California, US

	GP3	513A59	AS MIXED catalyzed GP3513A59 with BP3513B61		
	LB/Gal	g/L	LB/Gal	g/L	
Coating Density	8.08	968	8.25	988	
	By wt	By vol	By wt	By vol	
Total Volatiles	9.8%	9.5%	5.1%	5.1%	
Exempt solvents					
Water	0.0%	0.0%	0.0%	0.0%	
Organic Volatiles	9.8%	9.5%	5.1%	5.1%	
Percent Non-Volatile	90.2%	90.5%	94.9%	94.9%	
VOC Content	LB/Gal	g/L	LB/Gal	g/L	
Total	0.79	94	0.41	50	
Less exempt solvents	0.79	94	0.41	50	
Of solids	0.87	104	0.44	52	
Of solids	0.10 lb/lb	0.10 kg/kg	0.05 lb/lb	0.05 kg/kg	

Volatile Organic Compounds - EU Directive 2004/42/EC

	GP35	13A59	AS MIXED catalyzed GP3513A59 with BP3513B61		
	By wt	By vol	By wt	By vol	
Total Volatiles	10.2%	9.9%	5.6%	5.5%	
VOC Content	LB/Gal	g/L	LB/Gal	g/L	
Total	0.82	98	0.45	55	

Volatile Organic Compounds - EU Directive 2010/75/EU

	GP35	13A59	AS MIXED catalyzed GP3513A59 with BP3513B61		
	By wt	By vol	By wt	By vol	
Total Volatiles	7.6%	7.3%	3.5%	3.4%	
VOC Content	LB/Gal	g/L	LB/Gal	g/L	
Total	0.61	74	0.28	34	

Volatile Organic Compounds - Mexico

	GP3	513A59	AS MIXED catalyzed GP3513A59 with BP3513B61		
	LB/Gal	g/L	LB/Gal	g/L	
Coating Density	8.08	968	8.25	988	
	By wt	By vol	By wt	By vol	
Total Volatiles	9.8%	9.5%	5.1%	5.1%	
Exempt solvents					
Water	0.0%	0.0%	0.0%	0.0%	
Organic Volatiles	9.8%	9.5%	5.1%	5.1%	
Percent Non-Volatile	90.2%	90.5%	94.9%	94.9%	
VOC Content	LB/Gal	g/L	LB/Gal	g/L	
Total	0.79	94	0.41	50	
Less exempt solvents	0.79	94	0.41	50	
Of solids	0.87	104	0.44	52	
Of solids	0.10 lb/lb	0.10 kg/kg	0.05 lb/lb	0.05 kg/kg	

Hazardous Air Pollutants (Clean Air Act, Section 112(b))

	GP3513A59				MIXED A59 with BP3513B61	
		LB/Gal		kg/L	LB/Gal	kg/L
Volatile HAPS		0.00		0.000	0.00	0.000
Of solids		0.00		0.001	0.00	0.000
Of solids	<	0.01lb/lb	<	0.01 kg/kg	0.00 lb/lb	0.00 kg/kg

Air Quality Data

Density of Organic Solvent Blend

8.28 lb/gal

Photochemically Reactive

Nο

Density of Organic Solvent Blend AS MIXED

8.21 lb/gal

Photochemically Reactive AS MIXED

Nο

Waste Disposal

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Addition of reducers or other additives to this product may substantially alter the above data. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.