



Installation Method



Ashlar

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product UR501 **Color** Flax **Collection** Urban Retreat Collection **Backing** GlasBac™

Product Specifications

Product Number	127340AK00
Product Construction	Tufted Sheared
Yarn System	100% Recycled Content Nylon
Yarn Manufacturer	Aquafil
Dye Method	100% Solution Dyed
Soil/Stain Protection	Protekt ² ®
Preservative Protection	InterSept®

More Product Specifications

	Imperial	Metric
Tufted Yarn Weight	25 oz/yd ²	848 g/m ²
Machine Gauge	1/10 in	39.4 ends/10cm
Pile Height	0.17 in	4.30 mm
Pile Thickness	0.15 in	4.00 mm
Stitches	11.00 /in	43.31 ends/10cm
Pile Density	6,164 oz/yd ³	228,560 g/m ³
Size	9.845 in x 39.38 in	25cm x 1m

Performance Specifications

Flooring Radiant Panel	(ASTM E-648) Passes
Smoke Density	(ASTM E-662) ≤ 450
Flammability	Passes Methenamine Pill Test (DOC-FF1-70)
Lightfastness	(AATCC 16 - E) ≥ 4.0 @ 60 AFU's
Static	(AATCC - 134) < 3.0 KV
Dimensional Stability	AACHEN Din 54318 < 0.10%
Traffic Classification	Heavy
Fiber Modification Ratio	1.9 to 2.2
Preservative Efficacy	(AATCC 174 Parts 2&3) 99% Reduction/No Mold 7 Days (ASTM E-2471) Complete Inhibition

Health + Environmental Specifications

Embodied Carbon (Cradle to Gate)	5.17 Kg CO ₂ /M ²
Full Life Cycle Carbon Emissions	Certified Carbon Neutral Floors™
Total Recycled Content	70.36 %
Recycled Content (Pre Consumer)	57.72 %
Recycled Content (Post Consumer)	12.64 %
Indoor Air Quality	Green Label Plus #GLP0820 CDPH 01350
Material Composition	Free of Added Heavy Metals, Formaldehyde, Fluorinated Chemicals (PFAS), and Halogenated Flame Retardants.
Disclosure of Environmental Impacts	Environmental Product Declaration
Disclosure of Product Ingredients	Health Product Declaration
Environmental Certifications	NSF/ANSI 140 Gold GreenCircle Certified Recyclable
LEED v4	Contributes to multiple IEQ and MR credits
End of Life	Carpet to Carpet Recycling through ReEntry®

Technical Information

Installation	Interface Installation Guidelines
Maintenance	Recommended Interface Maintenance Guidelines
Reclamation	Recyclable through ReEntry® - Call 1.888.733.6873 (U.S.) / 1.866.398.3191 (Canada)
Warranty	15 Year Standard Carpet Warranty
Installation Method	Ashlar
Manufacturing Location	ISO 9001 & 14001 Certified facilities in Troup County, Georgia, United States