




Installation Method



Ashlar



Herringbone

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see [www.interface.com/disclaimer](http://www.interface.com/disclaimer).

**Product** Touch Of Timber **Color** Bamboo **Backing** CQuest™Bio

**Product Specifications**

Product Number	106210AK0B
Product Construction	Microtuft Patterned Level Loop Pile
Yarn System	100% Recycled Content Nylon
Yarn Manufacturer	Aquafil
Dye Method	100% Solution Dyed
Soil/Stain Protection	Protekt <sup>2</sup> ®

**More Product Specifications**

	Imperial	Metric
Tufted Yarn Weight	15 oz/yd <sup>2</sup>	509 g/m <sup>2</sup>
Machine Gauge	5/64 in	50.4 ends/10cm
Pile Height	0.06 in	1.50 mm
Pile Thickness	0.01 in	0.40 mm
Stitches	9.40 /in	37.00 ends/10cm
Pile Density	36,000 oz/yd <sup>3</sup>	1,334,872 g/m <sup>3</sup>
Size	9.845 in x 39.38 in	25cm x 1m

**Performance Specifications**

Flooring Radiant Panel	(ASTM E-648) Passes
Smoke Density	(ASTM E-662) ≤ 450
Flammability	Passes Methenamine Pill Test (DOC-FF1-70)
Lightfastness	(AATCC 16 - E) ≥ 4.0 @ 60 AFU's
Static	(AATCC - 134) - 3.0 KV
Dimensional Stability	AACHEN Din 54318 < 0.10%
Traffic Classification	Severe
Fiber Modification Ratio	1.9 to 2.2

**Health + Environmental Specifications**

Embodied Carbon (Cradle to Gate)	2.38 Kg CO <sub>2</sub> /M <sup>2</sup>
Full Life Cycle Carbon Emissions	Certified Carbon Neutral Floors™
Biobased Content	<a href="#">Interface Modular Carpet on CQuestBio contains 47% USDA certified biobased content</a>
Total Recycled Content	61.42 %
Recycled Content (Pre Consumer)	61.16 %
Recycled Content (Post Consumer)	0.26 %
Indoor Air Quality	K1
Material Composition	Free of Added Heavy Metals, Formaldehyde, Fluorinated Chemicals (PFAS), and Halogenated Flame Retardants.
Disclosure of Environmental Impacts	<a href="#">Environmental Product Declaration</a>
Disclosure of Product Ingredients	<a href="#">Health Product Declaration</a>
Environmental Certifications	K1
LEED v4	K1
End of Life	Reclaimed through ReEntry®

**Technical Information**

Installation	<a href="#">Interface Installation Guidelines</a>
Maintenance	<a href="#">Recommended Interface Maintenance Guidelines</a>
Reclamation	Reclaimed through ReEntry®
Warranty	<a href="#">15 Year Standard Carpet Warranty</a>
Installation Method	Ashlar Herringbone
Manufacturing Location	<a href="#">ISO 9001 &amp; 14001 Certified facilities in Troup County, Georgia, United States</a>