



#### Installation Method



Ashlar

Herringbone

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see [www.interface.com/disclaimer](http://www.interface.com/disclaimer).

**Product** Northern Grain **Color** Chiffon Oak

#### Product Specifications

Product Number	A026
Product Construction	High Performance Luxury Vinyl Tile
Class / ASTM F1700	Class III Printed Vinyl Plank
Wear Layer Thickness	22 mil
Total Thickness	4.5 mm
Backing Class	Commercial Grade
Finish	Ceramor™
Nominal Dimensions	25 cm x 1 m (9.845 in x 39.38 in)

#### Performance Specifications

IIC Sound Rating	(ASTM E492-09) 64 IIC
Slip Resistance	(ASTM D2047) >0.55 wet/dry, ADA Compliant
Static Load Limit	(ASTM F970) 1500 psi
Flexibility	(ASTM F137) Passes
Resistance to Heat	(ASTM F1514) Passes
Resistance to Light	(ASTM F1515) Passes
Radiant Flux	ASTM E648 Class I
Smoke Density	(ASTM E-662) ≤ 450
Size & Squareness	(ASTM F2055) Passes, +/- 0.016 in. per linear foot
Thickness	(ASTM F386) Passes
Dimensional Stability	(ASTM F2199) Passes
Residual Indentation	(ASTM F1914) Passes
Resistance to Chemicals	(ASTM F925) Passes

#### Health + Environmental Specifications

Embodied Carbon (Cradle to Gate)	9.2 Kg CO <sub>2</sub> /M <sup>2</sup>
Full Life Cycle Carbon Emissions	Carbon Neutral Floors™
Total Recycled Content (Pre Consumer)	39%
Indoor Air Quality	FloorScore® SCS-FS-04366 CDPH 01350 compliant GREENGUARD Gold
Material Composition	Free of Ortho Phthalates, Added Formaldehyde and Heavy Metal Stabilizers
Disclosure of Environmental Impacts	<a href="#">Environmental Product Declaration</a>
Disclosure of Product Ingredients	<a href="#">Health Product Declaration</a>
Environmental Certifications	NSF/ANSI 332, Meets Certification Guidelines
LEED v4	Contributes to IEQ: Low Emitting Materials; M&R: EPD and EPR

#### Packaging

Quantity per Carton	26.91 ft <sup>2</sup> (2.5 m <sup>2</sup> )
Pieces per Carton	10
Weight Per Carton	40 lb (18 kg )
Cartons per Pallet	40
Pallets per Truckload	20

#### Technical Information

Installation	<a href="#">Interface LVT Installation Guidelines</a>
Maintenance	<a href="#">Recommended Interface LVT Maintenance Guidelines</a>
Reclamation	Recyclable through ReEntry® - Call 1.888.733.6873 (U.S.) / 1.866.398.3191 (Canada)
Warranty	<a href="#">15 Year Standard LVT Warranty</a>
Installation Method	Ashlar Herringbone