





Installation Method



Ashlar Brick Non Directional



Quarter turn Monolithic

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product Criterion Classic Wovens **Color** Twine **Collection** Criterion Classic Collection

Product Specifications

Product Number	C003
Product Construction	High Performance Luxury Vinyl Tile
Class / ASTM F1700	Class III Printed Vinyl Tile
Wear Layer Thickness	22 mil
Total Thickness	3.0 mm
Backing Class	Commercial Grade
Finish	Ceramor™
Nominal Dimensions	50 cm x 50 cm (19.69 in x 19.69 in)

Performance Specifications

IIC Sound Rating	(ASTM E492-09) 56 IIC
Slip Resistance	(ASTM D2047) >0.55 wet/dry, ADA Compliant
Static Load Limit	(ASTM F970) 1000 psi
Flexibility	(ASTMF137) Passes
Resistance to Heat	(ASTM F1514) Passes
Resistance to Light	(ASTM F1515) Passes
Radiant Flux	(ASTM E648) Class I
Smoke Density	(ASTM E-662) ≤ 450
Thickness	(ASTM F386) Passes
Residual Indentation	(ASTM F1914) Passes
Resistance to Chemicals	(ASTM F925) Passes

Health + Environmental Specifications

Embodied Carbon (Cradle to Gate)	7.27 Kg CO ₂ /M ²
Full Life Cycle Carbon Emissions	Carbon Neutral Floors™
Total Recycled Content (Pre Consumer)	39%
Indoor Air Quality	FloorScore® SCS-FS-04366 CDPH 01350 compliant GREENGUARD Gold
Material Composition	Free of Ortho Phthalates, Added Formaldehyde and Heavy Metal Stabilizers
Disclosure of Environmental Impacts	Environmental Product Declaration
Disclosure of Product Ingredients	Health Product Declaration
Environmental Certifications	NSF/ANSI 332
LEED v4	Contributes to IEQ: Low Emitting Materials; M&R: EPD and EPR

Packaging

Quantity per Carton	37.67 ft ² (3.5 m ²)
Pieces per Carton	14
Weight Per Carton	42 lb (19 kg)
Cartons per Pallet	44
Pallets per Truckload	20

Technical Information

Installation	Interface LVT Installation Guidelines
Maintenance	Recommended Interface LVT Maintenance Guidelines
Warranty	15 Year Standard LVT Warranty
Installation Method	Monolithic Quarter Turn Non Directional Ashlar Brick