

Everywear III & Everywear Plus

Style	Everywear Plus 22 & 26 Broadloom	Everywear Plus 22 & 26 Modular
Construction	Enhanced Graphic Loop	Enhanced Graphic Loop
Face Fiber	Type 6,6 Nylon	Type 6,6 Nylon
Dye Method	Solution / Yarn	Solution / Yarn
Gauge	1/10 (39.37 per 10 cm)	1/10 (39.37 per 10 cm)
Stitches Per Inch	22 oz - 8.0 (31.5 per 10 cm), 26 oz - 9.33 (36.73 per 10 cm)	22 oz - 8.0 (38.07 per 10 cm), 26 oz - 9.33 (36.73 per 10 cm)
Density	22 oz - 6,139 (228.11 kg/m³), 26 oz - 5,813 (216.00 kg/m³)	22 oz - 6,139 (228.11 kg/m³), 26 oz - 5,813 (216.00 kg/m³)
Pile Thickness	22 oz - 0.126" (3.28 mm), 26 oz - 0.161" (4.09 mm)	22 oz - 0.126" (3.28 mm), 26 oz - 0.161" (4.09 mm)
Weight	22 oz/yd² (746 g/m²), 26 oz/yd² (881 g/m²)	22 oz/yd² (746 g/m²), 26 oz/yd² (881 g/m²)
Backing Type	UltraBac® RE, Integra HP®	Infinity® 2 Modular
Sizes	12' Width (3.66 m)	Modular: 24" x 24" (60.96 x 60.96 cm)
Colors	9	9
Pattern Repeat	N/A	N/A
Packaging	N/A	8 yd² / 18 Tiles
Adhesive	Mannington Ultra Adhesive Mannington Integra Adhesive	Infinity 2 Adhesive
Installation Method	N/A	Monolithic
Testing		
Dimensional Stability AACHEN Test	Passes	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 KV	Less than 3.0 KV
Radiant Panel (ASTM E648)	≥ 0.45 watts/cm², Passes (Class 1)	≥ 0.45 watts/cm2, Passes (Class 1)
Smoke Density (ASTM E662)	≤ 450-Passes	≤ 450-Passes
Methenamine Pill Test (ASTM D-2859)	Passes	Passes
Hexapod (ASTM D5252) TARR Rating (XX)	22 oz - 4, 26 oz - 3.5	22 oz & 26 oz - 3.5
Environmental Data		
NSF / ANSI-140 Certification	UltraBac® RE - Gold / Integra® HP - Gold	Infinity® 2 Modular - Gold
Recycled Content	Contains Post and Pre Consumer	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	EPD, HPD	
LEED Scoreboard	May contribute to LEED Credits: Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials	
mindful Materials	Visit mM Origin website, mindfulmaterials.origin.build, for current transparency information	
Manufacturing	Calhoun, Georgia (USA) - ISO 14001 Certified	
Warranty		
	Limited Lifetime Wear & Backing Limited 15-Year XGuard Stain Resistant Limited 15-Year ColorSafe Bleach Resistant	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and to avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backings or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Cut piles, cut and loops, and tip-sheared constructions are not recommended for heavy commercial traffic, corridors, or through channeled traffic. Please contact your Mannington representative for information regarding these constructions and your specific end use application.

\* Please make a final selection from actual swatch. To order samples go to manningtoncommercial.com or call 800.241.2262 ext. 6913