



Everywear III & Everywear Plus

Mannington
COMMERCIAL



Cover: Everywear III (Modular) - Copper Luster 8509
Installation - Monolithic
Above: Everywear III (Broadloom) - Copper Luster 8509



Everywear Plus (Broadloom) - Rhapsody 3404



Everywear Plus (Modular) - Rhapsody 3404
Installation - Monolithic



Everywear Plus (Modular) - Rhapsody 3404
Installation - Monolithic
Recoarse II (Entryway System) - Boulevard Blue 3517



Everywear III (Broadloom) - Pearl 3304



Everywear III (Modular) - Pearl 3304
Installation - Monolithic

Everywear III & Everywear Plus

Style	Everywear III Broadloom	Everywear III Modular
Construction	Enhanced Graphic Loop	Enhanced Graphic Loop
Face Fiber	Type 6,6 Nylon	Type 6,6 Nylon
Dye Method	Solution	Solution
Guage	1/10 (39.37 per 10 cm)	1/10 (39.37 per 10 cm)
Stitches Per Inch	8.0 (31.5 per 10 cm)	8.0 (31.5 per 10 cm)
Density	6,139 (228.11 kg/m³)	6,139 (228.11 kg/m³),
Pile Thickness	0.126" (3.28 mm)	0.126" (3.28 mm)
Weight	22 oz/yd² (746 g/m²)	22 oz/yd² (746 g/m²)
Backing Type	UltraBac® RE, Integra HP®	Infinity® 2 Modular
Size	12' Width (3.66 m)	24" x 24" (60.96 x 60.96 cm)
Colors	21	21
Pattern Repeat	N/A	N/A
Packaging	N/A	8 yd² / 18 Tiles
Adhesive	Mannington Ultra Adhesive, Mannington Integra Adhesive	Infinity® 2 Adhesive
Installation Method	N/A	Monolithic
Testing		
Dimensional Stability (Aachen Test)	Passes	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	Less than 3.0 kV
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm²	Passes - Class 1; ≥ 0.45 watts/cm²
Smoke Density (ASTM E662)	Passes - ≤ 450	Passes - ≤ 450
Methenamine Pill Test (ASTM D2859)	Passes	Passes
Hexapod (ASTM D5252) TARR	3.5 - severe	3.5 - severe
Environmental Data		
NSF/ANSI 140 Certification	Infinity® 2 Modular - Gold, UltraBac® RE - Gold, Integra® HP - Gold	
Recycled Content	Contains recycled content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	Third Party Verified EPD, HPD	
Carbon Offset	105% Cradle to Gate (A1 - A3), visit website for more information	
LEED	May contribute to LEED credits: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials	
mindful MATERIALS	Visit mindfulmaterials.com for current transparency information	
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered	
Warranty		
	Limited Lifetime Wear & Backing Warranty Limited 15-Year XGUARD® Stain Resistant Warranty Limited 15-Year ColorSafe® Bleach Resistant Warranty	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Cut piles, cut and loops and tip-sheared constructions are not recommended for heavy commercial traffic, corridors or through channeled traffic. Please contact your Mannington Commercial representative for information regarding these constructions and your specific end use application
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262 ext. 6913.

Everywear III & Everywear Plus

Style	Everywear Plus 22 & 26 Broadloom	Everywear Plus 22 & 26 Modular
Construction	Enhanced Graphic Loop	Enhanced Graphic Loop
Face Fiber	Type 6,6 Nylon	Type 6,6 Nylon
Dye Method	Solution / Yarn	Solution / Yarn
Guage	1/10 (39.37 per 10 cm)	1/10 (39.37 per 10 cm)
Stitches Per Inch	22 oz - 8.0 (31.5 per 10 cm), 26 oz - 9.33 (36.73 per 10 cm)	22 oz - 8.0 (38.07 per 10 cm), 26 oz - 9.33 (36.73 per 10 cm)
Density	22 oz - 6,139 (228.11 kg/m³), 26 oz - 5,813 (216.00 kg/m³)	22 oz - 6,139 (228.11 kg/m³), 26 oz - 5,813 (216.00 kg/m³)
Pile Thickness	22 oz - 0.126" (3.28 mm), 26 oz - 0.161" (4.09 mm)	22 oz - 0.126" (3.28 mm), 26 oz - 0.161" (4.09 mm)
Weight	22 oz/yd² (746 g/m²), 26 oz/yd² (881 g/m²)	22 oz/yd² (746 g/m²), 26 oz/yd² (881 g/m²)
Backing Type	UltraBac® RE, Integra HP®	Infinity® 2 Modular
Size	12' Width (3.66 m)	Modular: 24" x 24" (60.96 x 60.96 cm)
Colors	9	9
Pattern Repeat	N/A	N/A
Packaging	N/A	8 yd² / 18 Tiles
Adhesive	Mannington Ultra Adhesive Mannington Integra Adhesive	Infinity 2 Adhesive
Installation Method	N/A	Monolithic
Testing		
Dimensional Stability (Aachen Test)	Passes	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	Less than 3.0 kV
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm²	Passes - Class 1; ≥ 0.45 watts/cm²
Smoke Density (ASTM E662)	Passes - ≤ 450	Passes - ≤ 450
Methenamine Pill Test (ASTM D2859)	Passes	Passes
Hexapod (ASTM D5252) TARR	22 oz - 4, 26 oz - 3.5 - severe	22 oz & 26 oz - 3.5 - severe
Environmental Data		
NSF/ANSI 140 Certification	Infinity® 2 Modular - Gold, UltraBac® RE - Gold, Integra® HP - Gold	
Recycled Content	Contains recycled content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	Third Party Verified EPD, HPD	
Carbon Offset	105% Cradle to Gate (A1 - A3), visit website for more information	
LEED	May contribute to LEED credits: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials	
mindful MATERIALS	Visit mindfulmaterials.com for current transparency information	
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered	
Warranty		
	Limited Lifetime Wear & Backing Warranty Limited 15-Year XGUARD® Stain Resistant Warranty Limited 15-Year ColorSafe® Bleach Resistant Warranty	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Cut piles, cut and loops and tip-sheared constructions are not recommended for heavy commercial traffic, corridors or through channeled traffic. Please contact your Mannington Commercial representative for information regarding these constructions and your specific end use application
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262 ext. 6913.