



Edge Effects® Collection

Mannington
COMMERCIAL



Cover: Cetera - Beach Sand 030, **Montgomery** (Broadloom) - Stirling 14113
Above: Etched - White 401, **Intersect** - Foundation PD111



Simplicity - Sea Green 088, **Uninterrupted Wood** - Heartwood Oak UN204
Pre-mitered inside and outside corners are available to match various wall base heights.

Edge Effects® Sculptured Wall Base Packaging

Style	Total Thickness	Roll LF per Carton	Roll Carton Weight	8' Lengths Pcs per Carton	8' Lengths LF per Carton	8' Lengths Carton Weight	Inside/Outside Corners Pcs per Carton	Carton Weight
Cache (3")	3/8"	50 lf (15.24 m)	23 lbs (10.43 kg)	8	64 lf (19.51 m)	33 lbs (14.97 kg)	20	5 lbs (2.268 kg)
Cache (4 1/4")	3/8"	50 lf (15.24 m)	37 lbs (16.78 kg)	8	64 lf (19.51 m)	51 lbs (23.13 kg)	20	8 lbs (3.629 kg)
Cetera (4")	5/16"	36 lf (10.97 m)	44 lbs (19.96 kg)	8	64 lf (19.51 m)	79 lbs (35.84 kg)	20	14 lbs (6.35 kg)
Cetera (4 1/2")	5/16"	36 lf (10.97 m)	44 lbs (19.96 kg)	8	64 lf (19.51 m)	105 lbs (47.63 kg)	20	16 lbs (7.257 kg)
Double Etched (4")	1/4"	50 lf (15.24 m)	44 lbs (19.96 kg)	8	64 lf (19.51 m)	57 lbs (25.85 kg)	20	9 lbs (4.082 kg)
Double Etched (4 1/4")	1/4"	50 lf (15.24 m)	45 lbs (20.41 kg)	8	64 lf (19.51 m)	61 lbs (27.67 kg)	20	10 lbs (4.536 kg)
Effectual Chair Rail (4")*	1/4"	n/a	n/a	5	40 lf (12.19 m)	46 lbs (20.87 kg)	n/a	n/a
Elegance (6")	3/16"	36 lf (10.97 m)	43 lbs (19.5 kg)	4	32 lf (9.754 m)	43 lbs (19.5 kg)	20	18 lbs (8.165 kg)
Etched (4")	1/4"	50 lf (15.24 m)	44 lbs (19.96 kg)	8	64 lf (19.51 m)	57 lbs (25.85 kg)	20	9 lbs (4.082 kg)
Etched (4")	3/8"	n/a	n/a	8	64 lf (19.51 m)	59 lbs (26.76 kg)	20	10 lbs (4.536 kg)
Etched (4 1/4")	1/4"	50 lf (15.24 m)	47 lbs (21.32 kg)	6	64 lf (19.51 m)	63 lbs (28.58 kg)	20	10 lbs (4.536 kg)
Etched (4 1/4")	3/8"	n/a	n/a	8	64 lf (19.51 m)	67 lbs (30.39 kg)	20	10 lbs (4.536 kg)
Etched (6")	1/4"	36 lf (10.97 m)	57 lbs (25.85 kg)	4	32 lf (9.754 m)	54 lbs (24.49 kg)	20	24 lbs (10.89 kg)
Flair (3")	5/16"	50 lf (15.24 m)	38 lbs (17.24 kg)	8	64 lf (19.51 m)	52 lbs (23.59kg)	20	9 lbs (4.082 kg)
Iconic (4 1/4")	3/8"	50 lf (15.24 m)	39 lbs (17.69 kg)	8	64 lf (19.51 m)	53 lbs (24.04 kg)	20	9 lbs (4.082 kg)
Illusion (3 1/4")	3/8"	36 lf (10.97 m)	30 lbs (13.61 kg)	8	64 lf (19.51 m)	57 lbs (25.85 kg)	20	9 lbs (4.082 kg)
Lunar (4")	5/16"	36 lf (10.97 m)	43 lbs (19.5 kg)	8	64 lf (19.51 m)	77 lbs (34.93 kg)	20	14 lbs (6.35 kg)
Lunar (4 1/2")	5/16"	36 lf (10.97 m)	44 lbs (19.96 kg)	8	64 lf (19.51 m)	80 lbs (36.29 kg)	20	16 lbs (7.257 kg)
Marquee (4 1/4")	3/8"	50 lf (15.24 m)	39 lbs (17.69 kg)	8	64 lf (19.51 m)	53 lbs (24.04 kg)	20	9 lbs (4.082 kg)
Quarter Round (1/2")*	1/2"	n/a	n/a	20	240 lf (73.15 m)	35 lbs (15.88 kg)	n/a	n/a
Regal (5 1/4")	3/8"	25 lf (7.62 m)	40 lbs (18.14 kg)	4	32 lf (9.754 m)	52 lbs (23.59 kg)	20	21 lbs (9.525 kg)
Simple (4")	1/4"	50 lf (15.24 m)	44 lbs (19.96 kg)	8	64 lf (19.51 m)	57 lbs (25.85 kg)	20	9 lbs (4.082 kg)
Simple (4")	3/8"	50 lf (15.24 m)	44 lbs (19.96 kg)	8	64 lf (19.51 m)	59 lbs (26.76 kg)	20	9 lbs (4.082 kg)
Simple (4 1/4")	1/4"	50 lf (15.24 m)	45 lbs (20.41 kg)	8	64 lf (19.51 m)	61 lbs (27.67 kg)	20	10 lbs (4.536 kg)
Simple (4 1/4")	3/8"	50 lf (15.24 m)	45 lbs (20.41 kg)	8	64 lf (19.51 m)	59 lbs (26.76 kg)	20	10 lbs (4.536 kg)
Simplicity (3")	3/8"	n/a	n/a	8	64 lf (19.51 m)	57 lbs (25.86kg)	20	9 lbs (4.082 kg)
Simplicity (4")	5/16"	36 lf (10.97 m)	44 lbs (19.96 kg)	8	64 lf (19.51 m)	80 lbs (36.29 kg)	20	16 lbs (7.257 kg)
Simplicity (4 1/2")	5/16"	36 lf (10.97 m)	45 lbs (20.41 kg)	8	64 lf (19.51 m)	80 lbs (36.29 kg)	20	11 lbs (4.99 kg)
Simplicity (6")	5/16"	36 lf (10.97 m)	57 lbs (25.85 kg)	4	32 lf (9.754 m)	54 lbs (24.49 kg)	20	24 lbs (10.89 kg)
Sophisticate (4 1/4")	3/8"	50 lf (15.24 m)	39 lbs (17.69 kg)	8	64 lf (19.51 m)	53 lbs (24.04 kg)	20	9 lbs (4.082 kg)

* Ships in 12' Lengths

Edge Effects® Collection

Style	Double Etched*, Effectual® Chair Rail, Etched*, Simple	Elegance
Construction	Co-extruded Thermoplastic Rubber, Type TP	Co-extruded Thermoplastic Rubber, Type TP
Classification	ASTM F1861 Type TP, Group 1	ASTM F1861 Type TP, Group 1
Finish	Matte	Matte
Total Thickness	1/4" (6.35 mm)	3/16" (4.76 mm)
Profile	Smooth	Smooth
Profile Height	Double Etched, Etched, Simple - 4" or 4 1/4" Effectual® Chair Rail - 4" Etched - 6"	6"
Colors	40 (36 are Accord)	40 (36 are Accord)
Packaging	See Packaging Chart, p.4	See Packaging Chart, p.4
Adhesive	MR101 Acrylic	MR101 Acrylic
Testing		
HUD/FHA	Meets / Exceeds	
ADAG (American Disability Act Guidelines)	Passes	
Flexibility (ASTM F137)	Passes - 1/4" Mandrel - No Crack/Break	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm²	
Smoke Density (ASTM E662)	Passes - < 450	
Chemical Resistance (ASTM F925)	Passes - No More Than Slight Change	
Resistance to Heat (ASTM F1514)	Passes - < 8 Delta E Color Change	
Resistance to Mold/Mildew (ASTM G21/E2180)	Passes - No More Than Slight Change	
Environmental Data		
Indoor Air Quality	FloorScore Certified; CDPH v1.2-2017	
Product Declarations	HPD	
LEED	May contribute to LEED credits: Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials	
mindful MATERIALS	For current transparency information visit mindfulmaterials.com	
Manufacturing	USA	
Warranty		
Limited 5-Year Commercial Warranty		

Edge Effects® Collection

Style	Cetera®, Flair®, Lunar, Simplicity*	Cache®, Etched, Iconic®, Illusion, Marquee®, Regal®, Simple, Sophisticate®*
Construction	Co-extruded Thermoplastic Rubber, Type TP	Co-extruded Thermoplastic Rubber, Type TP
Classification	ASTM F1861 Type TP, Group 1	ASTM F1861 Type TP, Group 1
Finish	Matte	Matte
Total Thickness	5/16" (7.94 mm)	3/8" (9.52 mm)
Profile	Smooth	Smooth
Profile Height	Flair, Simplicity - 3" Cetera®, Lunar, Simplicity - 4" or 4 1/2" Simplicity - 6"	Cache® - 3" Illusion® - 3 1/4" Etched, Simple - 4" Cache®, Iconic®, Marquee®, Sophisticate® - 4 1/4" Regal - 5 1/4"
Colors	40 (36 are Accord)	40 (36 are Accord)
Packaging	See Packaging Chart, p.4	See Packaging Chart, p.4
Adhesive	MR101 Acrylic	MR101 Acrylic
Testing		
HUD/FHA	Meets / Exceeds	
ADAG (American Disability Act Guidelines)	Passes	
Flexibility (ASTM F137)	Passes - 1/4" Mandrel - No Crack/Break	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²	
Smoke Density (ASTM E662)	Passes - < 450	
Chemical Resistance (ASTM F925)	Passes - No More Than Slight Change	
Resistance to Heat (ASTM F1514)	Passes - < 8 Delta E Color Change	
Resistance to Mold/Mildew (ASTM G21/E2180)	Passes - No More Than Slight Change	
Environmental Data		
Indoor Air Quality	FloorScore Certified; CDPH v1.2-2017	
LEED	May contribute to LEED credits: Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials	
mindful MATERIALS	For current transparency information visit mindfulmaterials.com	
Manufacturing	USA	
Warranty		
	Limited 5-Year Commercial Warranty	

Edge Effects® Collection

Style	Quarter Round	*Pre-mitered Inside and Outside corners also available
Construction	Co-extruded Thermoplastic Rubber, Type TP	Co-extruded Thermoplastic Rubber, Type TP
Classification	ASTM F1861 Type TP, Group 1	ASTM F1861 Type TP, Group 1
Finish	Matte	Matte
Total Thickness	1/2" (12.7 mm)	3/16" (4.76 mm)
Profile	Smooth	Smooth
Colors	40 (36 are Accord)	40 (36 are Accord)
Packaging	See Packaging Chart, p.4	See Packaging Chart, p.4
Adhesive	MR101 Acrylic	MR101 Acrylic
Testing		
HUD/FHA	Meets / Exceeds	
ADAG (American Disability Act Guidelines)	Passes	
Flexibility (ASTM F137)	Passes - 1/4" Mandrel - No Crack/Break	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²	
Smoke Density (ASTM E662)	Passes - < 450	
Chemical Resistance (ASTM F925)	Passes - No More Than Slight Change	
Resistance to Heat (ASTM F1514)	Passes - < 8 Delta E Color Change	
Resistance to Mold/Mildew (ASTM G21/E2180)	Passes - No More Than Slight Change	
Environmental Data		
Indoor Air Quality	FloorScore Certified; CDPH v1.2-2017	
LEED	May contribute to LEED credits: Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials For current transparency information visit mindfulmaterials.com	
mindful MATERIALS		
Manufacturing	USA	
Warranty		
	Limited 5-Year Commercial Warranty	