

Model: OXO LINE BLANCO 13"X39" approx.

Codes: 100292649

Water absorption: BIII - Revestimiento ( $10\% \leq E \leq 20\%$ )



## DIMENSIONAL FEATURES

|                             |                |          |
|-----------------------------|----------------|----------|
| Thickness                   | 7/16" approx   | +/-5%*   |
| Width                       | 13 1/8" approx |          |
| Length                      | 39 3/8" approx |          |
| Length and width deviation  | Below 0.15%    | +/-0.3%* |
| Side straightness deviation | Below 0.15%    | +/-0.3%* |
| Squareness deviation        | Below 0.15%    | +/-0.3%* |
| Surface flatness deviation  | Below 0.15%    | +/-0.4%* |

## MECHANICAL FEATURES

|                    |                  |          |
|--------------------|------------------|----------|
| Breaking strength  | 291.25 LBF       | >125LBF* |
| Modulus of rupture | 7.78 LBF         | >=3LBF*  |
| Crazing resistance | Resists 3 cycles |          |

## HYGIENIC FEATURES

|                     |                                                                                                            |         |
|---------------------|------------------------------------------------------------------------------------------------------------|---------|
| Chemical resistance | Class "A" for swimming pools and cleaning products (resists attack). Minimum Class "B" for acids and bases | B Min.* |
| Stain resistance    | Class 5. Easy cleaning with water                                                                          | 3 Min.* |

## PACKING

|                        |                |  |
|------------------------|----------------|--|
| Sales units per box    | 14.34 SQF/CS   |  |
| Sales units per pallet | 630.85 SQF/PAL |  |
| Sales units per unit   | 3.58 SQF/ST    |  |

## SCOPE OF USE

|                  |                  |  |
|------------------|------------------|--|
| Technical code-1 | 1 - Use on walls |  |
|------------------|------------------|--|

### System Certification



Do not use cleaning agents containing hydrofluoric acid.

It is recommended to fix tiles with a minimum joint of 1,5 mm. Do not fix without joint.

For big sizes, it is recommended to fix with mortars containing polymeric additives and to use the double glueing technique.

Mosaic tiles must be grouted.

This document is only commercial and cannot be used as expert opinion, documentary evidence or in any legal or administrative procedure unless authorized by PORCELANOSA S.A.