

CODE NUMBER

33250105

DESCRIPTION

1.28 gpf, A5, Polished Chrome Finish, Fixture Connection , Single Flush, Hardwired, Metal Button Fixture Wall Actuator Push Button, Piezo, PWT™ Concealed Solenoid (less sensor) Water Closet PWT Flushometer.

DETAILS

- Flush Volume: 1.28 gpf (4.8 Lpf)
- Finish: Polished Chrome (CP)
- Power Type: Hardwired
- Battery Life: 5 years
- Valve: Diaphragm
- Fixture Type: Water Closet
- Program: A5 (PRGM-A5)
- Push Button: Metal Button Fixture Wall Actuator (MBFW)

FEATURES

- Supports HE 1.28 gpf
- A series program set to dorm setting
- Program is field changeable to 15, 30, 45 or 60 minute lockout times
- Can be used with stainless-steel water closet fixtures from Acorn®, Bradley®, Metcraft® and other manufacturers
- PERMEX® Synthetic Rubber Diaphragm with Dual Filtered Fixed Bypass
- Single Flush
- Solenoid operated
- Includes standard touch button for operation
- Stainless steel, vandal proof button, chemical resistant button operation designed with non-hold-open feature to keep fixture from surpassing intended water consumption
- 3' Connector cable has white arrows for easy alignment
- Hardwire power with battery backup
- 18" power cable for connection
- Use with EAF-11 plug-in transformer
- Up to 8 valve connections per EAF-11
- Four (4) Size AA Batteries
- Low Battery flashing LED
- Valve shall be in compliance to the applicable sections of ASSE 1037
- **Retrofit Kit for**
- **Manual flushometers:**
 - Royal 603
 - Royal 611
 - Royal 613
- **Hydraulic flushometers:**
 - Royal 9603
 - Royal 9611



COMPLIANCES & CERTIFICATIONS



(ADA Compliant, BAA Compliant, cUPC Certified, UL Certified, UPC Certified, WaterSense Listed)

RECOMMENDED SPECIFICATION

Valve shall be in compliance to the applicable sections of ASSE 1037.

ELECTRICAL SPECIFICATIONS

- Battery Life: 5 years

VALVE OPERATING PRESSURE (FLOWING)

15–80 PSI (103–552 kPa). Specific fixtures may require greater minimum flowing pressure - consult manufacturer requirements.

DOWNLOADS

- [8603-ESM Retrofit Installation Instructions](#)
- [8603-ESM Maintenance Guide](#)
- [Additional Downloads](#)

NOTES

All information contained within this document subject to change without notice.

Looking for other variations of the PWT-ESM-HW-RESS product?
[View the general spec sheet with all options.](#)

WaterSense compliant when used with a WaterSense compliant fixture

Battery life varies according to actual usage and restroom conditions.

WARRANTY

[View Warranty Information](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

- Royal 9613
- **Can convert other vendor's valves with addition of 3325524
EBV31A Retrofit Kit Coupling Ring**