

CODE NUMBER

10103001

DESCRIPTION

SU-1019 Urinal and CX 8198 Flushometer.

COMPONENTS

• Flushometer: Code 3400321 • Urinal: Code 1101019

DETAILS

• Flush Volume: 0.125 gpf (0.5 Lpf)

• Nominal Dimensions: 14 $\frac{1}{4}$ " × 17 $\frac{1}{4}$ " × 25 $\frac{1}{2}$ " (362 × 438 × 648mm)

FIXTURE FEATURES

- White Vitreous China
- Washdown flushing action
- Integral flushing rim
- ¾" I.P.S. rear spud inlet
- 2" NPT outlet flange
- Vandal resistant strainer assembly included
- All mounting hardware included
- 100% factory flush tested

VIDEOS

- CX Flushometer Product Video
- CX Flushometer Sensor Installation
- CX Flushometer Sensor Vacuum Service
- CX Flushometer Sensor Piston Service
- CX Flushometer Product Video (Spanish)
- **PVD Special Finishes**



COMPLIANCES & CERTIFICATIONS





















(ADA Compliant, BAA Compliant, cUL Certified, cUPC Green Certified, LEED V4 Water Efficiency Credit, WaterSense Listed, EPD, HPD, LEED Materials & Resources HPD Credit, WELL **Building Standard)**

DOWNLOADS

- Standard Spud Urinal Installation Instructions
- CX 8158/8198 Installation Instructions
- Additional Downloads


All information contained within this document subject to change without notice.


WARRANTY

View Warranty Information



ROUGH-IN





NOTE: ADA urinal rim height requirements allow all heights 17" and below. Sloan strongly recommends roughing in the drain to achieve a 16½" rim height or less to ensure compliance.

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com