

CODE NUMBER

10051310

DESCRIPTION

SU-1009 Urinal and SLOAN 186 ESS Flushometer.

COMPONENTS

- Flushometer: Code 3772640
- Urinal: Code 1101009

DETAILS

- Flush Volume: 0.5 gpf (1.9 Lpf)
- Nominal Dimensions: 14 ¼" x 17 ¼" x 25 ½" (362 x 438 x 648mm)

FIXTURE FEATURES

- White Vitreous China
- Washdown flushing action
- Integral flushing rim
- ¾" I.P.S. top spud inlet
- 2" NPT outlet flange
- Vandal resistant strainer assembly included
- All mounting hardware included
- 100% factory flush tested



COMPLIANCES & CERTIFICATIONS



(ADA Compliant, BAA Compliant, BREEAM Water Credit, CalGreen Compliant, CEC Compliant, cUPC Green Certified, UL Certified, EPD, Green Globes Water Credit, HPD, LEED V4 Water Efficiency Credit, Satisfies LEED Credits, WELL Building Standard)

DOWNLOADS

- [Standard Spud Urinal Installation Instructions](#)
- [SS/ST/SU/WETS/WEUS Fixtures Repair and Maintenance Guide](#)
- [Optima ESS Repair and Maintenance Guide](#)
- [Additional Downloads](#)

NOTES

All information contained within this document subject to change without notice.

WARRANTY

[View Warranty Information](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

The image contains two sets of technical drawings for a flush valve and toilet fixture. The left set shows side elevations, and the right set shows front elevations.

Left Side Elevation (Flush Valve):

- Top view: Shows a flush valve with a 1" I.P.S. SUPPLY (DN 20 mm) connection. The distance from the centerline of the supply to the centerline of the fixture is 4-3/4" (121 mm). The distance from the centerline of the fixture to the centerline of the electrical box is 2-3/4" (70 mm). The distance from the centerline of the electrical box to the centerline of the supply is 2-1/4" MIN. (57 mm).
- Side view: Shows the flush valve with a 1" I.P.S. SUPPLY (DN 20 mm) connection. The distance from the centerline of the supply to the centerline of the fixture is 4-3/4" (121 mm). The distance from the centerline of the fixture to the centerline of the electrical box is 2-3/4" (70 mm). The distance from the centerline of the electrical box to the centerline of the supply is 2-1/4" MIN. (57 mm).
- Bottom view: Shows the flush valve with a 1" I.P.S. SUPPLY (DN 20 mm) connection. The distance from the centerline of the supply to the centerline of the fixture is 4-3/4" (121 mm). The distance from the centerline of the fixture to the centerline of the electrical box is 2-3/4" (70 mm). The distance from the centerline of the electrical box to the centerline of the supply is 2-1/4" MIN. (57 mm).

Right Side Elevation (Toilet Fixture):

- Top view: Shows a toilet fixture with a 1" I.P.S. SUPPLY (DN 25 mm) connection. The distance from the centerline of the supply to the centerline of the fixture is 4-3/4" (121 mm). The distance from the centerline of the fixture to the centerline of the electrical box is 2-3/4" (70 mm). The distance from the centerline of the electrical box to the centerline of the supply is 2-1/4" MIN. (57 mm).
- Side view: Shows the toilet fixture with a 1" I.P.S. SUPPLY (DN 25 mm) connection. The distance from the centerline of the supply to the centerline of the fixture is 4-3/4" (121 mm). The distance from the centerline of the fixture to the centerline of the electrical box is 2-3/4" (70 mm). The distance from the centerline of the electrical box to the centerline of the supply is 2-1/4" MIN. (57 mm).
- Bottom view: Shows the toilet fixture with a 1" I.P.S. SUPPLY (DN 25 mm) connection. The distance from the centerline of the supply to the centerline of the fixture is 4-3/4" (121 mm). The distance from the centerline of the fixture to the centerline of the electrical box is 2-3/4" (70 mm). The distance from the centerline of the electrical box to the centerline of the supply is 2-1/4" MIN. (57 mm).

Page 2 of 2